

Package ‘ReGenesees’

May 5, 2016

Type Package

Title R Evolved Generalized Software for Sampling Estimates and Errors
in Surveys

Description Design-Based and Model-Assisted analysis of complex sampling surveys.
Multistage, stratified, clustered, unequally weighted survey designs.
Horvitz-Thompson and Calibration Estimators. Variance Estimation for
nonlinear smooth estimators by Taylor-series linearization. Estimates,
standard errors, confidence intervals and design effects for: Totals,
Means, absolute and relative Frequency Distributions (marginal, conditional
and joint), Ratios, Shares and Ratios of Shares, Multiple Regression
Coefficients and Quantiles. Automated Linearization of Complex Analytic
Estimators. Design Covariance and Correlation. Estimates, standard errors,
confidence intervals and design effects for user-defined analytic estimators.
Estimates and sampling errors for subpopulations. Generalized Variance
Functions (GVF) method for predicting variance estimates.

Version 1.8.1

Author Diego Zardetto

Maintainer Diego Zardetto <zardetto@istat.it>

License EUPL

Imports stats, MASS

Depends R (>= 2.14.0)

ByteCompile TRUE

R topics documented:

ReGenesees-package	2
AF.gvf	5
aux.estimate	6
bounds.hint	8
check.cal	11
collapse.strata	13
contrasts.RG	17
Corr	23
data.examples	27
des.addvars	28
des.merge	30
drop.gvf.points	32

e.calibrate	36
e.svydesign	51
estimator.kind	55
ext.calibrated	57
extractors	61
fill.template	62
find.lon.strata	66
fit.gvf	67
fpcdat	72
g.range	73
get.residuals	75
getBest	78
getR2	80
GVF.db	82
gvf.input	88
gvf.misc	90
plot.gvf.fit	93
pop.desc	96
pop.template	99
population.check	102
predictCV	104
ReGenesees.options	109
sbs	112
svystat	113
svystatB	118
svystatL	123
svystatQ	128
svystatR	131
svystatS	135
svystatSR	138
svystatTM	141
weights	147
write.svystat	148
Zapsmall	149
%into%	150

Index	154
--------------	------------

ReGenesees-package	<i>ReGenesees: a Package for Design-Based and Model-Assisted Analysis of Complex Sample Surveys</i>
--------------------	---

Description

ReGenesees is an R package for design-based and model-assisted analysis of complex sample surveys. It handles multistage, stratified, clustered, unequally weighted survey designs. Sampling variance estimation for nonlinear (smooth) estimators is obtained by Taylor-series linearization. Sampling variance estimation for multistage designs can be obtained both under the Ultimate Cluster approximation or by means of an actual multistage computation. Estimates, standard errors, confidence intervals and design effects are provided for: Totals, Means, absolute and relative Frequency Distributions (marginal, conditional and joint), Ratios, Shares and Ratios of Shares, Multiple Regression Coefficients and Quantiles (variance via the Woodruff method). **ReGenesees** also handles

Complex Estimators, i.e. any user-defined estimator that can be expressed as an analytic function of Horvitz-Thompson or Calibration estimators of Totals or Means, by automatically linearizing them. The Design Covariance and Correlation between Complex Estimators is also provided. All analyses above can be carried out for arbitrary subpopulations. In addition, **ReGenesees** offers a Generalized Variance Functions (GVF) infrastructure, i.e. facilities for defining, fitting, testing and plotting GVF models, and to exploit them to predict variance estimates.

The **ReGenesees package** is the fundamental building block of a full-fledged R-based software *system*: the **ReGenesees System**. The latter has a clear-cut two-layer architecture. The application layer of the system is embedded into package **ReGenesees**. A second R package, called **ReGenesees.GUI**, implements the presentation layer of the system, namely a user-friendly Tcl/Tk GUI.

A Quick Reading Guide to the Reference Manual

This reference manual reports a documentation entry for each (user visible) function of package **ReGenesees**. As you may have noticed by reading section ‘R topics documented’ (page 1 of the pdf manual), these documentation entries are automatically sorted according to the alphabetic ordering of the names of the functions. Such an ordering doesn’t provide any clue about where should a user start reading, nor on the best way to proceed further.

In section ‘Table of Contents’, I tried to cluster the most important topics documented in the reference manual into few broad groups, based on both the statistical goals and on the software design of the underlying functions.

Moreover, I provided a *relevance code* for each documented topic/function. The meaning of such codes, along with the corresponding *reading suggestions*, are reported in the following table:

Relevance Codes Legend

CODE	RELEVANCE	READING SUGGESTION
***	Very Important.....	Read these topics as soon as possible. A clear understanding of these functions is mandatory in order to start using profitably the package.
**	Important.....	Read these topics once you have been experiencing for a while with (at least some of) the 'Very Important' functions.
*	Useful.....	These functions are ancillary (albeit in different ways) to the 'Very Important' and 'Important' ones (and their usage is generally simpler).
.	Advanced.....	These topics are very relevant but, unfortunately quite difficult. As they involve technical details, you should postpone their reading until you become familiar with the package.

Important Notice

It goes without saying that the ‘**Examples**’ sections at the end of each documented topic **represent a crucial part of this reference manual**.

TABLE OF CONTENTS**Survey Design:**

- *** e.svydesign.....Specification of a Complex Survey Design
- * weights.....Retrieve Sampling Units Weights
- * find.lon.strata.....Find Strata with Lonely PSUs
- ** collapse.strata.....Collapse Strata Technique for Eliminating Lonely PSUs
- * des.addvars.....Add Variables to Design Objects
- * des.merge.....Merge New Survey Data into Design Objects

Calibration:

- ** pop.template.....Template Data Frame for Known Population Totals
- * population.check.....Compliance Test for Known Totals Data Frames
- * pop.desc.....Natural Language Description of Known Totals Templates
- ** fill.template.....Fill the Known Totals Template for a Calibration Task
- * bounds.hint.....A Hint for Range Restricted Calibration
- *** e.calibrate.....Calibration of Survey Weights
- * check.cal.....Calibration Convergence Check
- * g.range.....Range of g-Weights
- * get.residuals.....Calibration Residuals of Interest Variables
- * ext.calibrated.....Make ReGenesees Digest Externally Calibrated Weights
- . contrasts.RG.....Set, Reset or Switch Off Contrasts for Calibration Models
- . %into%.....Compress Nested Factors

Estimates and Sampling Errors:

- *** svystatTM.....Estimation of Totals and Means in Subpopulations
- *** svystatR.....Estimation of Ratios in Subpopulations
- *** svystatS.....Estimation of Shares in Subpopulations
- *** svystatSR.....Estimation of Share Ratios in Subpopulations
- *** svystatB.....Estimation of Population Regression Coefficients
- *** svystatQ.....Estimation of Quantiles in Subpopulations
- *** svystatL.....Estimation of Complex Estimators in Subpopulations
- ** aux.estimated.....Quick Estimates of Auxiliary Variables Totals
- ** CoV, Corr.....Design Covariance and Correlation of Complex Estimators in Subpopulations
- * write.svystat.....Export Survey Statistics
- * extractors.....Extractor Functions for Variability Statistics
- . ReGenesees.options...Variance Estimation Options for the ReGenesees Package

Generalized Variance Functions Method:

- *** GVF.db.....Archive of Registered GVF Models
- *** gvf.input.....Prepare Input Data to Fit GVF Models
- *** svystat.....Compute Many Estimates and Errors in Just a Single Shot

```

*** fit.gvf.....Fit GVF Models
** plot.gvf.fit.....Diagnostic Plots for Fitted GVF Models
** drop.gvf.points.....Drop Outliers and Refit a GVF Model
* getR2, AIC, BIC.....Quality Measures on Fitted GVF Models
* getBest.....Identify the Best Fit GVF Model
*** predictCV.....Predict CV Values via Fitted GVF Models
* gvf.misc.....Miscellanea: Methods for Fitted GVF Models
* estimator.kind.....Which Estimator Did Generate these
                        Survey Statistics?

```

Utilities:

```

* Zapsmall.....Zapsmall Data Frame Columns and Numeric Vectors

```

Data Sets:

```

** data.examples.....Artificial Household Survey Data
** fpcdat.....A Small But Not Trivial Artificial Sample
                        Data Set
** sbs.....Artificial Structural Business Statistics Data
** AF.gvf.....Example Data for GVF Model Fitting

```

The ordering of the above ‘Table of Contents’ reflects only loosely the procedural sequence in which functions could be used. For instance, while you cannot apply function [e.calibrate](#) unless you have previously built a design object by using [e.svydesign](#), you can exploit, e.g., function [collapse.strata](#) also after calibration. As a further example, all functions in group ‘Estimates and Sampling Errors’ can be used on objects created by [e.svydesign](#) (yielding estimates and sampling errors for functions of Horvitz-Thompson estimators), as well as on objects created by [e.calibrate](#) (yielding estimates and sampling errors for functions of Calibration estimators).

AF.gvf

Example Data for GVF Model Fitting

Description

File `AF.gvf` contains a set of summary statistics that can be used to illustrate **ReGenesees** facilities for fitting Generalized Variance Functions models. These summary statistics have kind ‘Absolute Frequency’ (see function [estimator.kind](#)), i.e. involve estimates and errors of counts.

Usage

```
data(AF.gvf)
```

Format

Each row of the `ee.AF` data frame represents an estimated absolute frequency along with its estimated sampling error (expressed in terms of standard error, coefficient of variation and variance). The data frame has 349 rows, and the following 5 columns:

`name` The name of the original estimate, factor with 349 levels.
`Y` The value of the original estimate (an absolute frequency), `numeric`.
`SE` The standard error of the original estimate, `numeric`.
`CV` The coefficient of variation of the original estimate, `numeric`.
`VAR` The variance of the original estimate, `numeric`.

Details

Object `AF` is a list storing estimates and errors of counts (namely, summary statistics of kind ‘Absolute Frequency’) computed on survey design object `exdes`. The names of the slots of list `AF` indicate the nature of the corresponding estimates, e.g. element `AF[["sex.marstat"]]` stores estimates and errors of the joint absolute frequency distribution of variables `sex` and `marstat` (see ‘Examples’).

Object `ee.AF` is the `gvf.input` object built upon all such summary statistics, via function `gvf.input` (see ‘Examples’).

See Also

`estimator.kind` to assess what kind of estimates are stored inside a survey statistic object, `GVF.db` to manage **ReGenesee**s archive of registered GVF models, `gvf.input` and `svyestat` to prepare the input for GVF model fitting, `fit.gvf` to fit GVF models, `plot.gvf.fit` to get diagnostic plots for fitted GVF models, `drop.gvf.points` to drop alleged outliers from a fitted GVF model and simultaneously refit it, and `predictCV` to predict CV values via fitted GVF models.

Examples

```
data(AF.gvf)

# Inspect object AF
class(AF)
length(AF)
names(AF)
AF$sex.marstat
class(AF$sex.marstat)

# Inspect gvf.input object ee.AF
head(ee.AF)
str(ee.AF)
plot(ee.AF)

# The design object used to compute ee.AF is the following:
exdes

# How has object ee.AF been built?
foo <- gvf.input(exdes, stats = AF)
identical(ee.AF, foo)
```

aux.estimate

Quick Estimates of Auxiliary Variables Totals

Description

Quickly estimates the totals of the auxiliary variables of a calibration model.

Usage

```
aux.estimate(design,
             calmodel = if (inherits(template, "pop.totals"))
                           attr(template, "calmodel"),
             partition = if (inherits(template, "pop.totals"))
```

```

        attr(template, "partition") else FALSE,
template = NULL)

```

Arguments

design	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
calmodel	Formula defining the linear structure of the calibration model.
partition	Formula specifying the variables that define the "calibration domains" for the model (see 'Details'); FALSE (the default) implies no calibration domains.
template	An object of class <code>pop.totals</code> , be it a template or the actual known totals data frame for the calibration task.

Details

The main purpose of function `aux.estimate` is to make easy the task of estimating the totals of *all* the auxiliary variables involved in a calibration model (separately inside distinct calibration domains, if specified). Even if such totals can be estimated also by repeatedly invoking function `svyestat`, this may reveal very tricky in practice, because real-world calibration tasks (e.g. in the field of Official Statistics) can simultaneously involve hundreds of auxiliary variables. Moreover, total estimates provided by function `svyestat` are always complemented by sampling errors, whose estimation is very computationally demanding.

Function `aux.estimate`, on the contrary, *only* provides estimates of totals (i.e. without associated sampling errors), thus being very quick to be executed. Moreover, `aux.estimate` is able to compute, *in just a single shot*, all the totals of the auxiliary variables of a calibration model, no matter how complex the model is. Lastly, as a third strong point, the totals estimated by `aux.estimate` will be returned exactly in the same *standard format* in which the known population totals for the related calibration task need to be represented (see `pop.template`, `population.check`, `fill.template`).

It may be useful to point out that, besides having been designed to handle auxiliary variables involved in calibration models, function `aux.estimate` could be also used for computing *general* estimates of totals inside subpopulations in a very effective way (see 'Examples').

Value

An object of class `pop.totals`, thus inheriting from class `data.frame` storing the estimated totals in a standard format.

Author(s)

Diego Zardetto

See Also

`e.svydesign` to bind survey data and sampling design metadata, `svyestat` for calculating estimates and standard errors of totals, `e.calibrate` for calibrating weights, `pop.template` for constructing known totals data frames in compliance with the standard required by `e.calibrate`, `population.check` to check that the known totals data frame satisfies that standard, `fill.template` to automatically fill the template when a sampling frame is available.

Examples

```
# Load sbs data:
data(sbs)

# Build a design object:
sbsdes<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,fpc=~fpc)

# Now suppose you have to perform a calibration process which
# exploits as auxiliary information:
# i) the total number of employees (emp.num)
#    by class of number of employees (emp.cl) crossed with nace.macro;
# ii) the total number of enterprises (ent)
#    by region crossed with nace.macro;

# Build a template for the known totals:
pop<-pop.template(sbsdes,
  calmodel=~emp.num:emp.cl + region -1,
  partition=~nace.macro)

# Use the fill.template function to automatically compute
# the totals from the universe (sbs.frame) and safely fill
# the template:
pop<-fill.template(sbs.frame,template=pop)
pop

# You can now use aux.estimates to verify how much difference
# exists between the target totals and the initial HT estimates:
aux.HT<-aux.estimates(sbsdes,template=pop)
aux.HT

# If you calibrate, ...
sbscal<-e.calibrate(sbsdes,pop)

# ... you can verify that CAL estimates exactly match the known totals:
aux.CAL<-aux.estimates(sbscal,template=pop)
aux.CAL

# Recall that you can also use aux.estimates for computing
# general estimates of totals inside subpopulations (even
# not related to any calibration task).
# E.g. estimate the total of value added inside areas:
aux.estimates(sbsdes,~va.imp2-1,~area)

# ...and compare to svystatTM (notice also
# the increased execution time):
svystatTM(sbsdes,~va.imp2,~area)
```

bounds.hint

A Hint for Range Restricted Calibration

Description

Suggests a sound bounds value for which e.calibrate is likely to converge.

Usage

```
bounds.hint(design, df.population,
            calmodel = if (inherits(df.population, "pop.totals"))
                          attr(df.population, "calmodel"),
            partition = if (inherits(df.population, "pop.totals"))
                          attr(df.population, "partition") else FALSE,
            msg = TRUE)
```

Arguments

design	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
df.population	Data frame containing the known population totals for the auxiliary variables.
calmodel	Formula defining the linear structure of the calibration model.
partition	Formula specifying the variables that define the "calibration domains" for the model; FALSE (the default) implies no calibration domains.
msg	Enables printing of a summary description of the result (the default is TRUE).

Details

The function `bounds.hint` returns a bounds value for which `e.calibrate` is *likely* to converge. This interval is just a sound hint, *not* an exact result (see ‘Note’).

The mandatory argument `design` identifies the `analytic` object on which the calibration problem is defined.

The mandatory argument `df.population` identifies the known totals data frame.

The argument `calmodel` symbolically defines the calibration model you want to use: it identifies the auxiliary variables and the constraints for the calibration problem. The design variables referenced by `calmodel` must be numeric or factor and must not contain any missing value (NA). The argument can be omitted provided `df.population` is an object of class `pop.totals` (see [population.check](#)).

The optional argument `partition` specifies the variables that define the calibration domains for the model. The default value (FALSE) means either that there are not calibration domains or that you want to solve the problem globally (even though it could be factorized). The design variables referenced by `partition` (if any) must be factor and must not contain any missing value (NA). The argument can be omitted provided `df.population` is an object of class `pop.totals` (see [population.check](#)).

The optional argument `msg` enables/disables printing of a summary description of the achieved result.

Value

A numeric vector of length 2, representing the *suggested* value for the bounds argument of `e.calibrate`. The attributes of that vector store additional information, which can lead to better understand why a given calibration problem is (un)feasible (see ‘Examples’).

Note

Assessing the feasibility of an arbitrary calibration problem is not an easy task. The problem is even more difficult whenever additional “*range restrictions*” are imposed. Indeed, even if one assumes

that the calibration constraints define a consistent system, one also has to choose the bounds such that the feasible region is non-empty.

One can argue that there must exist a minimum-length interval $I = [L, U]$ such that, if it is covered by bounds, the specified calibration problem is feasible. Unfortunately in order to compute exactly that minimum-length interval I one should solve a big linear programming problem [Vanderhoeft 01]. As an alternative, a trial and error procedure has been frequently proposed [Deville et al 1993; Sautory 1993]: (i) start with a very large interval bounds.0; (ii) if convergence is achieved, shrink it so as to obtain a new interval bounds.1; (iii) repeat until you get a sufficiently tight feasible interval bounds.n. The drawback is that this procedure can cost a lot of computer time since, for each choice of the bounds, the full calibration problem has to be solved.

A rather easy task is, on the contrary, the one of finding at least a given specific interval $I^* = [L^*, U^*]$ such that, if it is *not* covered by bounds, the current calibration problem is *surely unfeasible*. This means that any feasible bounds value must necessarily contain the I^* interval. The function bounds.hint: (i) first identifies such an I^* interval (by computing the range of the ratios between known population totals and corresponding direct Horvitz-Thompson estimates), (ii) then builds a new interval I^{sugg} with same midpoint and double length. The latter is the *suggested* value for the bounds argument of e.calibrate. The return value of bounds.hint should be understood as a useful starting guess for bounds, even though there is definitely no warranty that the calibration algorithm will actually converge.

Author(s)

Diego Zardetto

References

- Vanderhoeft, C. (2001) "*Generalized Calibration at Statistic Belgium*", Statistics Belgium Working Paper n. 3.
- Deville, J.C., Sarndal, C.E. and Sautory, O. (1993) "*Generalized Raking Procedures in Survey Sampling*", Journal of the American Statistical Association, Vol. 88, No. 423, pp.1013-1020.
- Sautory, O. (1993) "*La macro CALMAR: Redressement d'un Echantillon par Calage sur Marges*", Document de travail de la Direction des Statistiques Demographiques et Sociales, no. F9310.

See Also

[e.calibrate](#) for calibrating weights, [pop.template](#) for constructing known totals data frames in compliance with the standard required by e.calibrate, [population.check](#) to check that the known totals data frame satisfies that standard, [g.range](#) to compute the range of the obtained g-weights, and [check.cal](#) to check if calibration constraints have been fulfilled.

Examples

```
# Creation of the object to be calibrated:
data(data.examples)
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
  weights=~weight)

# Calibration (partitioned solution) on the marginal distribution
# of age in 5 classes (age5c) inside provinces (procod)
# (totals in pop06p). Get a hint for feasible bounds:
hint<-bounds.hint(des,pop06p,~age5c-1,~procod)

# Let's verify if calibration converges with the suggested
```

```

# value for the bounds argument (i.e. c(0.219, 1.786) ):
descal06p<-e.calibrate(design=des,df.population=pop06p,
                      calmodel=~age5c-1,partition=~procod,calfun="logit",
                      bounds=hint,aggregate.stage=2)

# Now let's verify that calibration fails, if bounds don't cover
# the interval [0.611, 1.394]:
## Not run:
descal06p<-e.calibrate(design=des,df.population=pop06p,
                      calmodel=~age5c-1,partition=~procod,calfun="logit",
                      bounds=c(0.62,1.50),aggregate.stage=2,force=FALSE)

## End(Not run)
# The warning message raised by e.calibrate tells that
# the population total of variable age5c5 (i.e. the fifth
# age class frequency) was not matched.

# By analysing ecal.status one understands that calibration
# failed due to the sub-task identified by procod 30:
ecal.status

# this is easily explained by inspecting the "bounds"
# attribute of the bounds.hint output object:
attr(hint,"bounds")

# indeed the specified lower bound (0.62) was too high
# for procod 30, where instead a value ~0.61 was required.

# Recall that you can always "force" a calibration task that
# would not converge:
descal06p.forced<-e.calibrate(design=des,df.population=pop06p,
                             calmodel=~age5c-1,partition=~procod,calfun="logit",
                             bounds=c(0.62,1.50),aggregate.stage=2,force=TRUE)

# Notice, also, that forced sub-tasks can be tracked down by
# directly looking at ecal.status...
ecal.status

# ...or by using function check.cal:
check.cal(descal06p.forced)

```

check.cal

Calibration Convergence Check

Description

Checks whether Calibration Constraints are fulfilled; if not, assesses constraints violation degree.

Usage

```
check.cal(cal.design)
```

Arguments

cal.design Object of class cal.analytic.

Details

The function verifies if all the imposed Calibration Constraints are actually fulfilled by object `cal.design`. If it is not the case, the function evaluates the degree of violation of the constraints and prints a summary of the mismatches between population totals and achieved estimates (see also Section 'Calibration process diagnostics' in the help page of [e.calibrate](#)).

Value

The main purpose of the function is to print on screen; anyway a list is invisibly returned, which summarizes the results of the check.

Author(s)

Diego Zardetto

See Also

[e.calibrate](#) for calibrating weights (in particular, Section 'Calibration process diagnostics').

Examples

```
# Load sbs data:
data(sbs)

# Build a design object:
sbsdes<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,fpc=~fpc)

## Example 1
# Build template...
pop<-pop.template(sbsdes,~emp.num:emp.cl+ent-1,~region)
# Fill template...
pop<-fill.template(sbs.frame,pop)
# Calibrate...
sbscal<-e.calibrate(sbsdes,pop,sigma2=~emp.num)
# Check calibration...
check.cal(sbscal)

## Example 2
# Build template...
pop<-pop.template(sbsdes,~emp.num+ent-1,~area)
# Fill template...
pop<-fill.template(sbs.frame,pop)
# Calibrate with tight bounds...
sbscal<-e.calibrate(sbsdes,pop,sigma2=~emp.num,bounds=c(0.8,1.2))
# Check calibration...
check.cal(sbscal)

# Now try to calibrate with suggested bounds...
hint <- bounds.hint(sbsdes,pop)
sbscal<-e.calibrate(sbsdes,pop,sigma2=~emp.num,bounds=hint)
# Check calibration...
check.cal(sbscal)
```

collapse.strata

*Collapse Strata Technique for Eliminating Lonely PSUs***Description**

Modifies a stratified design containing lonely PSUs by collapsing its design strata into superstrata.

Usage

```
collapse.strata(design, block.vars = NULL, sim.score = NULL)
```

Arguments

design	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
block.vars	Formula specifying blocking variables: only strata belonging to the same block will be aggregated (see ‘Details’). If <code>NULL</code> (the default option) no constraints will be imposed.
sim.score	Formula specifying a similarity score for strata: lonely strata will be paired with the most similar stratum in each block (see ‘Details’). If <code>NULL</code> (the default option) random pairs will be formed.

Details

Lonely PSUs (i.e. PSUs which are alone inside a not self-representing stratum) are a concern from the viewpoint of variance estimation. As a general solution, the **ReGenesees** package can handle the lonely PSUs problem by setting proper variance estimation options (see [ReGenesees.options](#)). The `collapse.strata` function implements a widely used alternative: the so called collapsed strata technique. The basic idea is to build artificial “superstrata” by aggregating strata containing lonely PSUs to other strata, and then to use such superstrata for variance estimation (see e.g. [Wolter 85] and [Rust, Kalton 87]).

The optional argument `block.vars` identifies “blocking variables” that can be used to constrain the way lonely strata are collapsed to form superstrata. More specifically: first, blocking variables are used to partition sample data in “blocks” via factor crossing, then, only lonely strata belonging to the same block are aggregated. If `block.vars=NULL` (the default option), no constraint will act on collapsing. The design variables referenced by `block.vars` (if any) should be of type factor. Errors will be raised if (i) blocks cut across strata, or (ii) `block.vars` generate any non-aggregable strata (i.e. lonely strata which are a singleton inside a block).

The optional argument `sim.score` can be used to specify a similarity score for strata aggregation. This means that each lonely stratum will be collapsed with the stratum that has the most similar value of variable `sim.score` inside the block. Thus the similarity of two strata is actually measured by the (absolute value of the) difference among the corresponding `sim.score` values. Only one design variable can be referenced by the `sim.score` formula: (i) it must be of type numeric, (ii) it must be constant inside each stratum, and (iii) it should be positive (otherwise its `abs()` will be silently used). Note that if no similarity score is specified (i.e. `sim.score=NULL`), the achieved strata aggregation will depend on the ordering of input sample data in `design`.

The collapsing algorithm will, whenever possible, build superstrata by pairing a lonely stratum to another not-yet-aggregated stratum. Therefore, in general, superstrata will contain only two design strata. Rare exceptions can arise, e.g. due to constraints, with at most three design strata inside a superstratum. The choice to collapse strata in pairs has been taken because it is known to be

appropriate for large-scale surveys with many strata (at least for national level estimates, see e.g. [Rust, Kalton 87]).

The `collapse.strata` function handles correctly finite population corrections. If design has been built by passing strata sampling fractions via the `fpc` argument, the function re-computes sampling fractions inside superstrata by exploiting the achieved mapping of strata to superstrata and the `fpc` slot of design.

Value

An object of the same class as `design`, without strata containing lonely PSUs.

Strata Collapse Process Diagnostics

As already observed in the ‘Details’ Section, there are three non trivial reasons why function `collapse.strata` can run into errors: (1) the blocks cut across strata, (2) some blocks contain a stratum needing to be aggregated while this stratum happens to be the only one inside the block, (3) the similarity score for strata aggregation varies inside strata. In order to help the user to identify such data anomalies, hence taking a step forward to eliminate them, every call to `collapse.strata` generates, by side effect, a diagnostics data structure named `clps.strata.status` into the `.GlobalEnv` (see ‘Examples’).

The `clps.strata.status` list has three components: the first reports the error message, the second stores a vector identifying the data subsets that have been hit by the anomaly, the third reports the call to `collapse.strata` that generated the list. For instance, when error condition (1) holds, the second element of `clps.strata.status` identifies the strata that are cut by blocks; if, instead, error condition (2) holds, the second element of the list identifies the blocks containing non-aggregable strata.

It must be stressed that *every call* to `collapse.strata` generates the `clps.strata.status` list, *even* when the strata collapsing process ends *successfully*. In such cases, the first element of the list reports the number of lonely strata that have undergone aggregation, whereas the second is a useful data frame (named `clps.table`) mapping collapsed strata to superstrata. To be more specific: each row of `clps.table` identifies a stratum that has been mapped to a superstratum, while the columns of `clps.table` give: (i) the block to which the stratum belongs, (ii) the stratum name, (iii) a flag indicating if the stratum was lonely or not, (iv) the name of the superstratum to which it has been mapped.

Methodological Warning

A warning must be emphasized: strata similarity score `sim.score` should be based on prior knowledge and/or on expectations on *true* values of stratum means for the variable(s) to be estimated, not on current sample data. Indeed, building `sim.score` by estimating stratum means with the current sample can lead to severe *underestimation* of sampling variance, i.e. to too tight confidence intervals.

Author(s)

Diego Zardetto

References

- Wolter, K.M. (2007) *"Introduction to Variance Estimation"*, Second Edition, Springer-Verlag, New York.
- Rust, K., Kalton, G. (1987) *"Strategies for Collapsing Strata for Variance Estimation"*, Journal of Official Statistics, Vol. 3, No. 1, pp. 69-81.

See Also

[ReGenesees.options](#) for a different way to handle the lonely PSUs problem (namely by setting variance estimation options).

Examples

```
#####
# Explore alternative collapsing strategies. #
#####

# Build a survey design with lonely PSU strata:
data(data.examples)
exdes <- e.svydesign(data= example, ids= ~ towcod+famcod,
                    strata= ~ stratum, weights= ~ weight)
exdes

# Explore 3 possible collapsing strategies:
# 1) Aggregate lonely strata by forming random pairs
exdes.clps1 <- collapse.strata(exdes)
exdes.clps1

# 2) Aggregate lonely strata in pairs under constraints:
#   i. aggregated strata must be both not self-representing
#   ii. aggregated strata must belong to the same province (which
#       is appropriate if e.g. provinces are planned estimation domains)
exdes.clps2 <- collapse.strata(exdes, ~sr:procod)
exdes.clps2

# 3) A WRONG strategy: compute strata similarity score by using
#     sample estimates of the interest variable (y1) inside strata:
old.op <- options("RG.lonely.psu"="remove")
stat.score <- svystatTM(design= exdes, ~y1, by= ~ stratum)
options(old.op)
exdes2<-des.addvars(exdes,
                    sim.score=stat.score[match(stratum,stat.score$stratum),2])
exdes.clps3 <- collapse.strata(exdes2,~sr:procod,~sim.score)
exdes.clps3

# Compute total estimates of y1 at the province level
# for all 3 designs with collapsed strata:
stat.clps1 <- svystatTM(design= exdes.clps1, y= ~ y1, by= ~ procod,
                       estimator= "Total", vartype= "cvpct")
stat.clps2 <- svystatTM(design= exdes.clps2, y= ~ y1, by= ~ procod,
                       estimator= "Total", vartype= "cvpct")
stat.clps3 <- svystatTM(design= exdes.clps3, y= ~ y1, by= ~ procod,
                       estimator= "Total", vartype= "cvpct")

# Compute the same estimates by using two alternatives
# to handle lonely PSUs:
# "adjust" option
old.op <- options("RG.lonely.psu"="adjust")
stat.adj <- svystatTM(design= exdes, y= ~ y1, by= ~ procod,
                     estimator= "Total", vartype= "cvpct")
options(old.op)
# "average" option
old.op <- options("RG.lonely.psu"="average")
```

```

stat.ave <- svyestatTM(design= exdes, y= ~ y1, by= ~ procd,
                      estimator= "Total", vartype= "cvpct")
options(old.op)

# Lastly, compare achieved estimates for CV percentages:
stat.clps1
stat.clps2
stat.clps3
stat.adj
stat.ave

# Thus the qualitative features are as expected: the "adjust" option
# tends to give conservative sampling variance estimates, the WRONG collapsing
# strategy 3) tends to underestimate sampling variance, while other methods
# give results in-between those extrema.

#####
# A simple way for defining the strata similarity scores. #
#####
# Suppose that strata have been clustered in groups of similar
# strata. You can, then, use the integer codes of the factor
# variable identifying the clusters as a similarity score.
# You can do as follows:

# Load some data:
data(fpcdat)

# Build a design object:
fpcdes<-e.svydesign(data=fpcdat,ids=~psu+ssu,strata=~stratum,weights=~w)
fpcdes

# As we deliberately omitted to specify fpcs, this design
# has 2 lonely strata out of 5:
find.lon.strata(fpcdes)

# Now, suppose that factor variable pl.domain identifies clusters of
# similar strata...
table(fpcdat$stratum,fpcdat$pl.domain)

# ...hence, the similarity score can be obtained simply...
fpcdes<-des.addvars(fpcdes,score=unclass(pl.domain))

# ...and readily be used to drive the strata collapsing:
fpcdes.clps<-collapse.strata(fpcdes,sim.score=~score)
fpcdes.clps
clps.strata.status

# As we expected from the groups defined by pl.domain, lonely stratum S.2
# has been paired to S.3, and lonely stratum S.5 to S.4.

# Should we have omitted to specify a similarity score, we would have
# obtained different superstrata:
fpcdes.clps2<-collapse.strata(fpcdes)
fpcdes.clps2
clps.strata.status

```



```
#####
# Few examples to inspect the clps.strata.status list generated #
# for diagnostics purposes.                                     #
#####

# 1) Ill defined blocks: cutting across strata:
## Not run:
clps.err1 <- collapse.strata(exdes,~sex)

## End(Not run)
clps.strata.status

# 2) Ill defined blocks: generating non-aggregable strata
## Not run:
clps.err2 <- collapse.strata(exdes,~regcod:stratum)

## End(Not run)
clps.strata.status

# 3) Successful collapsing: explore strata to superstrata mapping
exdes.ok <- collapse.strata(exdes,~sr:regcod:procod)
clps.strata.status
```

contrasts.RG

Set, Reset or Switch Off Contrasts for Calibration Models

Description

These functions control the way **ReGenesees** translates a symbolic calibration model (as specified by the calmodel formula in [e.calibrate](#), [pop.template](#), [fill.template](#), [aux.estimate](#), ...) to its numeric encoding (i.e. the model-matrix used by the internal algorithms to perform actual computations).

Usage

```
contrasts.RG()
contrasts.off()
contrasts.reset()
contr.off(n, base = 1, contrasts = TRUE, sparse = FALSE)
```

Arguments

n	Formally as in function <code>contr.treatment</code> (see ‘Details’).
base	Formally as in function <code>contr.treatment</code> (see ‘Details’).
contrasts	Fictitious, but formally as in function <code>contr.treatment</code> . (see ‘Details’)
sparse	Formally as in function <code>contr.treatment</code> . (see ‘Details’)

Details

All the calibration facilities in package **ReGenesees** transform symbolic calibration models (as specified by the user via `calmodel`) into numeric model-matrices. Factor variables occurring in `calmodel` play a special role in such transformations, as the encoding of a factor can (and, by default, do) *depend* on the *structure* of the formula in which it occurs. The **ReGenesees** functions documented below control the way factor levels are translated into auxiliary variables and mapped to columns of population totals data frames. The underlying technical tools are [contrasts](#) handling functions (see Section ‘Technical Remarks and Warnings’ for further details).

Under the calibration perspective, ordered and unordered factors appearing in `calmodel` must be treated the same way. This obvious constraint defines the **ReGenesees** default for contrasts handling. Such a default is silently set when loading the package. Moreover, you can set it also by calling `contrasts.RG()`. As can be understood by reading Section ‘Technical Remarks and Warnings’ below, the default setup can be seen as **“efficient-but-slightly-risky”**.

A call to `contrasts.off()` simply disables all contrasts and imposes a complete dummy coding of factors. Under this setup, all levels of factors occurring in `calmodel` generate a distinct model-matrix column, *even if some of these columns can be linearly dependent*. To be very concise, the `contrasts.off()` setup can be seen as **“safe-but-less-efficient”** as compared to the default one (read Section ‘Technical Remarks and Warnings’ for more details).

Function `contr.off` is not meant to be called directly by users: it serves only the purpose of enabling the `contrasts.off()` setup.

A call to `contrasts.reset()` restores R factory-fresh defaults for contrasts (which do distinguish ordered and unordered factors). Users may want to use this function after having completed a **ReGenesees** session, e.g. before switching to other R functions relying on contrasts (such as `lm`, `glm`, ...).

Technical Remarks and Warnings

“[...] the corner cases of model.matrix and friends is some of the more impenetrable code in the R sources.”

Peter Dalgaard

Contrasts handling functions tell R how to encode the model-matrix associated to a given model-formula on specific data (see, e.g., `contr.treatment`, `contrasts`, `model.matrix`, `formula`, and references therein). More specifically, contrasts control the way factor-terms and interaction-terms occurring in formulae get actually represented in the model matrix. For instance, R (by default) avoids the complete dummy coding of a factor whenever it is able to understand, on the basis of the structure of the model-formula, that some of the factor levels would generate linearly dependent (i.e. redundant) columns in the model-matrix (see Section ‘Examples’).

The usage of contrasts to build smaller, full-rank calibration model-matrices would be a good opportunity for **ReGenesees**, provided it comes *without any information loss*. Indeed, smaller model-matrices mean less population totals to be provided by users, and higher efficiency in computations.

Unfortunately, few controversial cases have been signalled in which R ability to “simplify” a model-matrix on the basis of the structure of the related model-formula seems to lead to strange, unexpected results (see, e.g., [this R-help thread](#)). No matter whether such R behaviour is or not an actual bug with respect to its impact on R linear model fitting or ANOVA facilities, it surely represents a concern for **ReGenesees** with respect to calibration (see Section ‘Examples’). The risk is the following: there could be rare cases in which exploiting R contrasts handling functions inside **ReGenesees** ends up with a *wrong* (i.e. incomplete) population totals template, and (eventually) with *wrong* calibration results.

Though one could adopt several ad-hoc countermeasures to sterilize the risk described above while still taking advantage of contrasts (see Section ‘Examples’), the choice of completely disabling contrasts via `contrasts.off()` would result in a **100% safety guarantee**. If computational efficiency is not a serious concern for you, switching off contrasts may determine the best **ReGenesees** setup for your analyses.

Author(s)

Diego Zardetto

References

Chambers, J. M. and Hastie, T. J. (1992) *Statistical models*. Chapter 2 of *Statistical Models in S* eds J. M. Chambers and T. J. Hastie, Wadsworth & Brooks/Cole.

"Why does the order of terms in a formula translate into different models/model matrices?", R-help thread.

See Also

[e.calibrate](#), [pop.template](#), [fill.template](#), and [aux.estimates](#) for the meaning and the usage of `calmodel` in **ReGenesees**. [formula](#), [model.matrix](#), [contrasts](#), and [contr.treatment](#) to understand the role of contrasts in R.

Examples

```
#####
# Easy things first: #
#####

# 1) When ReGenesees is loaded, its standard way of handling contrasts
#     (i.e. no ordered-unordered factor distinction) is silently set:
options("contrasts")

# 2) To switch off contrasts (i.e. apply always dummy coding to factors),
#     simply type:
contrasts.off()

# 3) To restore R factory-fresh defaults for contrasts, simply type:
contrasts.reset()

# 4) To switch on again standard ReGenesees contrasts, simply type:
contrasts.RG()

#####
# A simple calibration example to understand the effects of #
# switching off contrasts.                                     #
#####

# Load sbs data:
data(sbs)

# Create a design object:
sbsdes<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,fpc=~fpc)

# Suppose you want to calibrate on the marginals of 'region' (a factor
```

```

# with 3 levels: "North", "Center", and "South") and 'dom3' (a factor
# with 4 levels: "A", "B", "C", and "D").
# Let's see how things go under the 'contrast on' (default) and 'contrasts off'
# setups:

#####
# 1) ReGenesees default: contrasts ON. #
#####
# As you see contrasts are ON:
options("contrasts")

# Build and fill the population totals template:
temp1<-pop.template(data=sbsdes,calmodel=~region+dom3-1)
pop1<-fill.template(universe=sbs.frame,template=temp1)

# Now inspect the obtained known totals data.frame:
pop1

# As you see: (i) it has only 6 columns, and (ii) the "A" level of
# factor 'dom3' is missing. This is because contrasts are ON, so that
# R is able to understand that only 6 out of the 3 + 4 marginal counts
# are actually independent. Indeed, the "A" counts...
sum(sbs.frame$dom3=="A")

# ...are actually redundant, since they can be deduced by pop1:
sum(pop1[,1:3])-sum(pop1[,4:6])

# Now calibrate:
cal1<-e.calibrate(sbsdes,pop1)

#####
# 2) Switch OFF contrasts: dummy coding for all! #
#####
# To switch off contrasts simply call:
contrasts.off()

# Build and fill the population totals template:
temp2<-pop.template(data=sbsdes,calmodel=~region+dom3-1)
pop2<-fill.template(universe=sbs.frame,template=temp2)

# Now inspect the obtained known totals data.frame:
pop2

# As you see: (1) it has now 7 columns, and (2) the "A" level of factor
# 'dom3' has been resurrected. This is because contrasts are OFF,
# so that each level of factors in calmodel are coded to dummies.

# Now calibrate. Since only 6 out of 7 dummy auxiliary variables are
# actually independent, the model.matrix computed by e.calibrate will not be
# full-rank. As a consequence, e.calibrate would use the Moore-Penrose
# generalized inverse (in practice, this could depend on the machine R
# is running on):
cal2<-e.calibrate(sbsdes,pop2)

# Compare the calibration weights generated under setups 1) and 2):
all.equal(weights(cal2),weights(cal1))

```

```

# Lastly set back contrasts to ReGenesees default:
contrasts.RG()

#####
# Weird results, risks and countermeasures. #
# ("When the going gets tough...")          #
#####

# Suppose you want to calibrate on: (A) the joint distribution of 'region' (a
# factor with 3 levels: "North", "Center", and "South") and 'nace.macro' (a
# factor with 4 levels: "Agriculture", "Industry", "Commerce", and "Services")
# and, at the same time, on (B) the total number of employees ('emp.num', a
# numeric variable) by 'nace.macro'.
#
# You rightly expect that  $3 \times 4 + 4 = 16$  population totals are needed for such a
# calibration task. Indeed, knowing the enterprise counts for the  $3 \times 4$  cells of
# the joint distribution (A) doesn't tell anything on the number of employees
# working in the 4 nace macrosectors (B), and vice-versa.
#
# Moreover, you might expect that calibration models:
# (i) calmodel = ~region:nace.macro + emp.num:nace.macro - 1
# (ii) calmodel = ~emp.num:nace.macro + region:nace.macro - 1
#
# should produce the same results.
# Unfortunately, WHEN CONTRASTS ARE ON, this is not the case: only model (i)
# leads to the expected, right results. Let's see.

#####
# A strange result when contrasts are ON: #
# the order of terms in calmodel matters! #
#####
# As you see contrasts are ON:
options("contrasts")

# Start with (i) calmodel = ~region:nace.macro + emp.num:nace.macro - 1
# Build and fill the population totals template:
temp1<-pop.template(data=sbsdes,~region:nace.macro+emp.num:nace.macro-1)
pop1<-fill.template(universe=sbs.frame,template=temp1)

# Now inspect the obtained known totals data.frame:
pop1

# and verify it stores the right, expected number of totals (i.e. 16):
dim(pop1)

# Now calibrate:
cal1<-e.calibrate(sbsdes,pop1)

# Now compare with (ii) calmodel = ~emp.num:nace.macro + region:nace.macro - 1
# Build and fill the population totals template:
temp2<-pop.template(data=sbsdes,~emp.num:nace.macro+region:nace.macro-1)
pop2<-fill.template(universe=sbs.frame,template=temp2)

# First check if it stores the right, expected number of totals (i.e. 16):

```

```

dim(pop2)

# Apparently 4 totals are missing; let's inspect the known totals data.frame
# to understand which ones:
pop2

# Thus we are missing the 4 'nace.macro' totals for 'region' level "North".
# Everything goes as if R contrasts functions mistakenly treated the term
# emp.num:nace.macro as a factor-factor interaction (i.e. a 2 way joint
# distribution), which would have justified to eliminate the 4 missing totals
# as redundant.

# Notice that calibrating on pop2 would generate wrong results...
cal2<-e.calibrate(sbsdes,pop2)

# ...indeed the 4 estimates of 'nace.macro' for 'region' level "North" are not
# actually calibrated (look at the magnitude of SE estimates):
svystatTM(cal2,~region,~nace.macro)

#####
# A possible countermeasure (still working with contrasts ON). #
#####
# Empirical evidence tells that the weird case above is extremely rare
# and that it manifests whenever a numeric (say X) and a factor (say F) both
# interact with the same factor (say D), i.e. calmodel=~(X+F):D-1.
#
# The risky order-dependent nature of such models can be sterilized (while
# still taking advantage of contrasts-driven simplifications for large,
# complex calibrations) by using a numeric variable with values 1 for
# all sample units.
#
# For instance, one could use variable 'ent' in the sbs data.frame, to
# handle the (A) part of the calibration constraints. Indeed you may easily
# verify that both the calmodel formulae below:
# (i) calmodel = ~ent:region:nace.macro + emp.num:nace.macro - 1
# (ii) calmodel = ~emp.num:nace.macro + ent:region:nace.macro - 1
#
# produce exactly the same, right results.

#####
# THE ULTIMATE, 100% SAFE, COUNTERMEASURE: switch contrasts OFF! #
#####
# No contrasts means no model-matrix simplifications at all, hence
# also no unwanted, wrong simplifications. Let's see:

# To switch off contrasts simply call:
contrasts.off()

# Compare again, with contrasts OFF, the calibration models:
# (i) calmodel = ~region:nace.macro + emp.num:nace.macro - 1
# (ii) calmodel = ~emp.num:nace.macro + region:nace.macro - 1

# Build and fill the population totals templates:
temp1<-pop.template(data=sbsdes,~region:nace.macro+emp.num:nace.macro-1)
pop1<-fill.template(universe=sbs.frame,template=temp1)

```

```

pop1

temp2<-pop.template(data=sbsdes,~emp.num:nace.macro+region:nace.macro-1)
pop2<-fill.template(universe=sbs.frame,template=temp2)
pop2

# Verify they store the same, right number of totals (i.e. 16):
dim(pop1)
dim(pop2)

# Verify they lead to right calibrated objects...
cal1<-e.calibrate(sbsdes,pop1)
cal2<-e.calibrate(sbsdes,pop2)

# ...with the same calibrated weights:
all.equal(weights(cal2),weights(cal1))

# Lastly set back contrasts to ReGenesees default:
contrasts.RG()

```

Corr

Design Covariance and Correlation of Complex Estimators in Subpopulations

Description

Estimates the covariance and the correlation of Complex Estimators in subpopulations. A Complex Estimator can be any analytic function of (Horvitz-Thompson or Calibration) estimators of Totals and Means.

Usage

```

CoV(design, expr1, expr2,
     by = NULL, na.rm = FALSE)
Corr(design, expr1, expr2,
     by = NULL, na.rm = FALSE)

```

Arguments

design	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
expr1	R expression defining the first Complex Estimator (see ‘Details’).
expr2	R expression defining the second Complex Estimator (see ‘Details’).
by	Formula specifying the variables that define the "estimation domains". If <code>NULL</code> (the default option) estimates refer to the whole population.
na.rm	Should missing values (if any) be removed from the variables of interest? The default is <code>FALSE</code> (see ‘Details’).

Details

This function allows to estimate the covariance and the correlation of two arbitrary Complex Estimators. Estimates are calculated using the Taylor linearization technique.

The mandatory arguments `expr1` and `expr2` identify the Complex Estimators: both must be of class `expression`. For further details on the syntax and the semantics of such expressions, see [svyestatL](#).

The optional argument `by` specifies the variables that define the "estimation domains", that is the subpopulations for which the estimates are to be calculated. If `by=NULL` (the default option), the estimates produced by `CoV (Corr)` refer to the whole population. Estimation domains must be defined by a formula: for example the statement `by=~B1:B2` selects as estimation domains the subpopulations determined by crossing the modalities of variables `B1` and `B2`. Notice that a formula like `by=~B1+B2` will be automatically translated into the factor-crossing formula `by=~B1:B2`: if you need to compute estimates for domains `B1` and `B2` *separately*, you have to call `CoV (Corr)` twice. The design variables referenced by `by` (if any) should be of type `factor`, otherwise they will be coerced.

Missing values (NA) in interest variables should be avoided. If `na.rm=FALSE` (the default) they generate NAs in estimates (or even an error, if design is calibrated). If `na.rm=TRUE`, observations containing NAs are dropped, and estimates gets computed on non missing values only. This implicitly assumes that missing values hit interest variables *completely at random*: should this be not the case, computed estimates would be *biased*.

Value

An object inheriting from the `data.frame` class, whose detailed structure depends on input parameters' values.

Author(s)

Diego Zardetto

References

Sarndal, C.E., Swensson, B., Wretman, J. (1992) *"Model Assisted Survey Sampling"*, Springer Verlag.

See Also

Estimators of Totals and Means [svyestatTM](#), Ratios between Totals [svyestatR](#), Shares [svyestatS](#), Ratios between Shares [svyestatSR](#), Multiple Regression Coefficients [svyestatB](#), Quantiles [svyestatQ](#), and Complex Analytic Functions of Totals and/or Means [svyestatL](#).

Examples

```
#####
# Some checks and some simple examples #
# to illustrate the syntax.             #
#####
# Load survey data:
data(data.examples)

# Creation of a design object:
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
weights=~weight)
```



```

# Let's start with some natural checks:
## The covariance of any estimator with itself is its variance
## (use mean income as an example):
CoV(des,expression(income/ones),expression(income/ones))
VAR(svystatL(des,expression(income/ones)))
VAR(svystatTM(des,~income,estimator="Mean"))

## The correlation of any estimator with itself is 1
## (use mean income as an example):
Corr(des,expression(income/ones),expression(income/ones))

# Switch to non trivial examples:
## Correlation of mean income with population size:
Corr(des,expression(income/ones),expression(ones))

## Correlation of mean income with total income:
# at population level:
Corr(des,expression(income/ones),expression(income))
# for regions:
Corr(des,expression(income/ones),expression(income),by=~regcod)

## Correlation of a product of two totals and a ratio of two totals:
# at population level:
Corr(des,expression(y1*y2),expression(x1/x2))
# for provinces:
Corr(des,expression(income/ones),expression(income),by=~procod)

#####
# A more meaningful and complex example: correlation #
# between Geometric, Harmonic and Arithmetic Means. #
#####
# Creation of another design object:
data(sbs)
sbsdes<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,
  fpc=~fpc)

# Let's use variable emp.num, which is ok as it is always strictly positive:
## Add a convenience variable for estimating the harmonic mean (see ?svystatL
## for details) and prepare the formal estimator expression:
sbsdes<-des.addvars(sbsdes,emp.num.m1=1/emp.num)
h<-expression(ones/emp.num.m1)

## Add a convenience variable for estimating the geometric mean (see ?svystatL
## for details) and prepare the formal estimator expression:
sbsdes<-des.addvars(sbsdes,log.emp.num=log(emp.num))
g<-expression(exp(log.emp.num/ones))

## prepare the formal estimator expression for the arithmetic mean:
m<-expression(emp.num/ones)

# Now compute correlations:
## Harmonic with Arithmetic:
Corr(sbsdes,h,m)

## Geometric with Arithmetic:

```

```

Corr(sbsdes,g,m)

## Harmonic with Geometric:
Corr(sbsdes,h,g)

## Hence, while correlations g-m and g-h are high, correlation h-m is low.

#####
# Another example: is a ratio estimator of a total #
# expected to be more efficient than an HT one?    #
#####

# Let's recall that the ratio estimator of a total is
# expected to be more efficient than HT, if the
# correlation of numerator and denominator exceeds
# half of the ratio between the CVs of denominator
# and numerator.

# Compute the HT estimate of the total of value added (variable va.imp2):
VA<-svystatTM(sbsdes,~va.imp2)
VA

# Compute the HT estimate of the total of emp.num:
EMP<-svystatTM(sbsdes,~emp.num)
EMP

# Now estimate the correlation of the numerator
# and denominator totals:
corr <- Corr(sbsdes,expression(va.imp2),expression(emp.num))
corr

# and compare it with  $(1/2) * (CV(den)/CV(num))$ 
stopifnot( corr > 0.5*cv(EMP)/cv(VA) )

# As the comparison holds TRUE, we expect an efficiency gain
# of the ratio estimator of the total compared to HT.
# Let's check...:

# Compute the ratio estimate of the total of value added using
# as auxiliary variable the number of employees, whose total
# is 984394:
TOT.emp.num <- sum(sbs.frame$emp.num)
TOT.emp.num

VA.ratio<-svystatL(sbsdes, expression(TOT.emp.num * (va.imp2/emp.num)))
VA.ratio

# Compare standard errors sizes:
SE(VA.ratio)
SE(VA)
stopifnot( SE(VA.ratio) < SE(VA) )

# ...as expected.

```

data.examples

*Artificial Household Survey Data***Description**

Example data frames. Allow to run R code contained in the ‘Examples’ section of the **ReGenesees** package help pages.

Usage

```
data(data.examples)
```

Format

The main data frame, named `example`, contains (artificial) data from a two stage stratified cluster sampling design. The sample is made up of 3000 final units, for which the following 21 variables were observed:

`towcod` Code identifying "variance PSUs": towns (PSUs) in not-self-representing (NSR) strata, families (SSUs) in self-representing (SR) strata, numeric

`famcod` Code identifying families (SSUs), numeric

`key` Key identifying final units (individuals), numeric

`weight` Initial weights, numeric

`stratum` Stratification variable, factor with levels 801 802 803 901 902 903 904 905 906 907 908 1001 1002 1003 1004 1005 1006 1007 1008 1009 1101 1102 1103 1104 3001 3002 3003 3004 3005 3006 3007 3008 3009 3010 3011 3012 3101 3102 3103 3104 3105 3106 3107 3108 3201 3202 3203 3204 5401 5402 5403 5404 5405 5406 5407 5408 5409 5410 5411 5412 5413 5414 5415 5416 5501 5502 5503 5504 9301 9302 9303 9304 9305 9306 9307 9308 9309 9310 9311 9312

`SUPERSTRATUM` Collapsed strata variable (eliminates lonely PSUs), factor with levels 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55

`sr` Strata type, integer with values 0 (NSR strata) and 1 (SR strata)

`regcod` Code identifying regions, factor with levels 6 7 10

`procod` Code identifying provinces, factor with levels 8 9 10 11 30 31 32 54 55 93

`x1` Indicator variable (integer), numeric

`x2` Indicator variable (integer), numeric

`x3` Indicator variable (integer), numeric

`y1` Indicator variable (integer), numeric

`y2` Indicator variable (integer), numeric

`y3` Indicator variable (integer), numeric

`age5c` Age variable with 5 classes, factor with levels 1 2 3 4 5

`age10c` Age variable with 10 classes, factor with levels 1 2 3 4 5 6 7 8 9 10

`sex` Sex variable, factor with levels f m

`marstat` Marital status variable, factor with levels married unmarried widowed

`z` A continuous quantitative variable, numeric

`income` Income variable, numeric

Details

Objects `pop01`, ..., `pop07pp` contain known population totals for various calibration models. Object pairs with names differing in the 'p' suffix (such as `pop03` and `pop03p`) refer to the *same* calibration problem but pertain to *different* solution methods (global and partitioned respectively, see [e.calibrate](#)). The two-component numeric vector bounds expresses a possible choice for the allowed range for the ratios between calibrated weights and direct weights in the aforementioned calibration problems.

Warning

Data in the example data frame are artificial. The *structure* of example intentionally resamples the one of typical household survey data, but the *values* it stores are unreliable. The only purpose of such data is that they can be fruitfully exploited to illustrate the syntax and the working mechanism of the functions provided by the **ReGenesees** package.

Examples

```
data(data.examples)
head(example)
str(example)
```

des.addvars

Add Variables to Design Objects

Description

Modifies an analytic object by adding new variables to it.

Usage

```
des.addvars(design, ...)
```

Arguments

<code>design</code>	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
<code>...</code>	<code>tag = expr</code> arguments defining columns to be added to design.

Details

This function adds to the data frame contained in `design` the *new* variables defined by the `tag = expr` arguments. A `tag` can be specified either by means of an identifier or by a character string; `expr` can be any expression that it makes sense to evaluate in the design environment.

For each argument `tag = expr` bound to the formal argument `...` the added column will have *name* given by the `tag` value and *values* obtained by evaluating the `expr` expression on `design`. Any input expression not supplied with a `tag` will be ignored and will therefore have no effect on the `des.addvars` return value.

Variables to be added to the input object have to be *new*: namely it is not possible to use `des.addvars` to modify the values in a pre-existing design column. This an intentional feature meant to safeguard the integrity of the relations between survey data and sampling design metadata stored in `design`.

Value

An object of the same class of design, containing new variables but supplied with exactly the same metadata.

Author(s)

Diego Zardetto

See Also

[e.svydesign](#) to bind survey data and sampling design metadata, [e.calibrate](#) for calibrating weights.

Examples

```
data(data.examples)

# Creation of an analytic object:
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
  weights=~weight)

# Adding the new 'ones' variable to estimate the number
# of final units in the population:
des<-des.addvars(des,ones=1)
svystatTM(des,~ones)

# Recoding a qualitative variable:
des<-des.addvars(des,agerange=factor(ifelse(age5c==1,
  "young","not-young")))
svystatTM(des,~agerange,estimator="Mean")
svystatTM(des,~income,~agerange,estimator="Mean",conf.int=TRUE)

# Algebraic operations on numeric variables:
des<-des.addvars(des,z2=z^2)
svystatTM(des,~z2,estimator="Mean")

# A more interesting example: estimating the
# percentage of population with income below
# the poverty threshold (defined as 0.6 times
# the median income for the whole population):
Median.Income <- coef(svystatQ(des, ~income,probs=0.5))
Median.Income
des <- des.addvars(des,
  status = factor(
    ifelse(income < (0.6 * Median.Income),
      "poor", "non-poor")
  )
)
svystatTM(des,~status,estimator="Mean")
# Mean income for poor and non-poor:
svystatTM(des,~income,~status,estimator="Mean")
```

des.merge

*Merge New Survey Data into Design Objects***Description**

Modifies an analytic object by joining the original survey data with a new data frame via a common key.

Usage

```
des.merge(design, data, key)
```

Arguments

design	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
data	Data frame containing a key variable, plus new variables to be merged to design data.
key	Formula identifying the common key variable to be used for merging.

Details

This function updates the survey variables contained into design (i.e. `design$variables`), by merging the original data with those contained into the data data frame. The merge operation exploits a *single* variable key, which must be common to both design and data.

The function preserves both the original *ordering* of the survey data stored into design, as well as all the original sampling design *metadata*.

The variable referenced by key must be a *valid* unique key for both design and data: it must not contain duplicated values, nor NAs. Moreover, the values of key in design and data must be in *1:1 correspondence*. These requirements are meant to ensure that the *new* survey data (that is the merged ones) will have exactly the same number of rows as the *old* survey data stored into design.

Should design and data contain further common variables besides the key, only their original design version will be retained. Thus, `des.merge` cannot modify any pre-existing design columns. This an intentional feature intended to safeguard the integrity of the relations between survey data and sampling design metadata stored in design.

Value

An object of the same class of design, containing additional survey data but supplied with exactly the same metadata.

Practical Purpose

In the field of Official Statistics, it is not unfrequent that calibration weights must be computed even several months before the target variables of the survey are made available for estimation. Such a time lag follows from the fact that target variables typically undergo much more thorough editing and imputation procedures than auxiliary variables.

In such production scenarios, function `des.merge` allows to tackle the task of computing estimates and errors for the fresh-released target variables *without* any need of *repeating* the calibration step. Indeed, by using the function, one can join the data contained into an already calibrated design

object with new data made available only after the calibration step. The merge operation is made easy and safe, and preserves all the original calibration metadata (e.g. those needed for variance estimation).

Author(s)

Diego Zardetto

See Also

[e.svydesign](#) to bind survey data and sampling design metadata, [e.calibrate](#) for calibrating weights, [des.addvars](#) to add new variables to design objects.

Examples

```
data(data.examples)

# Create a design object:
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
  weights=~weight)

# Create a calibrated design object as well (e.g. using population totals
# stored inside pop03p):
cal<-e.calibrate(design=des,df.population=pop03p,
  calmodel=~marstat-1,partition=~sex,calfun="logit",
  bounds=bounds)

# Lastly create a new data frame to be merged into des and cal:
set.seed(12345) # RNG seed fixed for reproducibility
new.data<-example[,c("income","key")]
new.data$income <- 1000 + new.data$income # altered income values
new.data$NEW.f<-factor(sample(c("A","B"),nrow(new.data),rep=TRUE))
new.data$NEW.n<-rnorm(nrow(new.data),10,2)
new.data <- new.data[sample(1:nrow(new.data)), ] # rows ordering changed
head(new.data)

#####
# Example 1: merge new data into a non calibrated design. #
#####

# Merge new data inside des (note the warning on income):
des2<-des.merge(design=des,data=new.data,key=~key)

# Compare visually:
## before:
head(des$variables)
## after:
head(des2$variables)

# New data can be used as usual:
svystatTM(des2,~NEW.n,~NEW.f,vartype="cvpct")

# Old data are unaffected, as it must be:
svystatTM(des,~income,estimator="Mean",vartype="cvpct")
svystatTM(des2,~income,estimator="Mean",vartype="cvpct")

#####
```

```
# Example 2: merge new data into a calibrated design. #
#####

# Merge new data inside cal (note the warning on income):
cal2<-des.merge(design=cal,data=new.data,key=~key)

# Compare visually:
## before:
head(cal$variables)
## after:
head(cal2$variables)

# New data can be used as usual:
svystatTM(cal2,~NEW.n,~NEW.f,vartype="cvpct")

# Old data are unaffected, as it must be:
svystatTM(cal,~income,estimator="Mean",vartype="cvpct")
svystatTM(cal2,~income,estimator="Mean",vartype="cvpct")
```

drop.gvf.points

Drop Outliers and Refit a GVF Model

Description

This function drops observations (alleged outliers) from a fitted GVF model and simultaneously re-fits the model.

Usage

```
drop.gvf.points(x, method = c("pick", "cut"), which.plot = 1:2,
               res.type = c("standard", "student"), res.cut = 3,
               id.n = 3, labels.id = NULL,
               cex.id = 0.75, label.pos = c(4, 2),
               cex.caption = 1, col = NULL, drop.col = "red",
               ...)
```

Arguments

x	An object containing a <i>single</i> fitted GVF model (i.e. of class <code>gvf.fit</code> or <code>gvf.fit.gr</code>).
method	character specifying the method for identifying observations to be dropped (see ‘Details’); it may be either ‘pick’ (the default) or ‘cut’.
which.plot	integer controlling the nature of the plot(s) that are used to identify and/or visualize the observations to be dropped: 1 means ‘Observed vs Fitted’, 2 means ‘Residuals vs Fitted’ (see ‘Details’).
res.type	character specifying what kind of residuals must be used.
res.cut	A positive value: observations to be dropped will be those with residuals whose absolute value exceeds ‘res.cut’. Only meaningful if method is ‘cut’.
id.n	Number of points to be initially labelled in each plot, starting with the most extreme. Only meaningful if method is ‘pick’.
labels.id	Vector of labels, from which the labels for extreme points will be chosen. NULL uses observation numbers.

cex.id	Magnification of point labels.
label.pos	Positioning of labels, for the left half and right half of the graph(s) respectively.
cex.caption	Controls the size of caption.
col	Color to be used for the points in the plot(s).
drop.col	Color to be used to visualize and annotate the points to be dropped in the plot(s).
...	Other parameters to be passed through to plotting functions.

Details

This function drops observations (alleged outliers) from a *single* fitted GVF model and simultaneously re-fits the model. As a side effect, the function prints on screen the induced change for selected quality measures (see, e.g., [getR2](#)).

If `method = "pick"`, observations to be dropped are identified interactively by clicking on points of a plot (see 'Note'). Argument `which.plot` determines the nature of the plot: value 1 is for '*Observed vs Fitted*', value 2 is for '*Residuals vs Fitted*'. In the latter case, argument `res.type` specifies what kind of residuals have to be plotted. Argument `id.n` specifies how many points have to be labelled initially, starting with the most extreme in terms of the selected residuals: this applies to both kinds of plots.

If `method = "cut"`, observations to be dropped are those with residuals whose absolute value exceeds the value of argument `res.cut`. Again, argument `res.type` specifies what kind of residuals have to be used (and plotted). The points which have been cut will be highlighted on a plot, whose nature is again specified by argument `which.plot`. If `which.plot = 1:2`, dropped points will be visualized on both the '*Observed vs Fitted*' and the '*Residuals vs Fitted*' graphs simultaneously.

Argument `drop.col` controls the color to be used to visualize and annotate in the plot(s) the points to be dropped. All the other arguments have the same meaning as in function [plot.lm](#).

Value

An object of the same class as `x` (i.e. either `gvf.fit` or `gvf.fit.gr`), containing the original GVF model re-fitted after dropping (alleged) outliers.

Note

For `method = "pick"`, function `drop.gvf.points` is only supported on those screen devices for which function [identify](#) is supported. The identification process can be terminated either by right-clicking the mouse and selecting 'Stop' from the menu, or from the 'Stop' menu on the graphics window.

Author(s)

Diego Zardetto

See Also

[GVF.db](#) to manage **ReGenesees** archive of registered GVF models, [gvf.input](#) and [svystat](#) to prepare the input for GVF model fitting, [fit.gvf](#) to fit GVF models, [plot.gvf.fit](#) to get diagnostic plots for fitted GVF models, and [predictCV](#) to predict CV values via fitted GVF models.

Examples

```

# Load example data:
data(AF.gvf)

# Inspect available estimates and errors of counts:
str(ee.AF)

# List available registered GVF models:
GVF.db

# Fit example data to registered GVF model number one:
m <- fit.gvf(ee.AF, model=1)
m
summary(m)

#####
# Method 'pick': identify outlier observations to be dropped #
# interactively by clicking on points of a plot.           #
#####
# Using the 'Observed vs Fitted' plot (the default):
## Not run:
m1 <- drop.gvf.points(m)
m1
summary(m1)

## End(Not run)

# Using the 'Residuals vs Fitted' plot with standardized
# residuals (the default) and increasing id.n to get more
# labelled points to guide your choices:
## Not run:
m1 <- drop.gvf.points(m, which.plot = 2, id.n = 10)
m1
summary(m1)

## End(Not run)

# The same as above, but with studentized residuals and
# playing with colors:
## Not run:
m1 <- drop.gvf.points(m, which.plot = 2, id.n = 10, res.type = "student",
                      col = "blue", drop.col = "green", pch = 20)
m1
summary(m1)

## End(Not run)

#####
# Method 'cut': identify outlier observations to be dropped #
# by specifying a threshold for the absolute values of the #
# residuals.                                               #
#####
# Using default threshold on standardized residuals and visualizing
# dropped observations on both 'Observed vs Fitted' and 'Residuals
# vs Fitted' plots:

```

```

m1 <- drop.gvf.points(m, method ="cut")
m1
summary(m1)

# Using a custom threshold on studentized residuals and visualizing
# dropped observations on the 'Observed vs Fitted' plot:
m1 <- drop.gvf.points(m, method ="cut", res.type = "student",
                      res.cut = 2.5, which.plot = 1)
m1
summary(m1)

# The same as above, but visualizing dropped observations on the
# 'Residuals vs Fitted' plot:
m1 <- drop.gvf.points(m, method ="cut", res.type = "student",
                      res.cut = 2.5, which.plot = 2)
m1
summary(m1)

# You can obviously "cut"/"pick" alleged outliers again from an already
# "cut"/"picked" fitted GVF model:
m2 <- drop.gvf.points(m1, method ="cut", res.type = "student",
                      res.cut = 2.5, col = "blue", pch = 20)
m2
summary(m2)

#####
# Identifying outlier observations to be dropped from "grouped" #
# GVF fitted models (i.e. x has class 'gvf.fit.gr').           #
#####
# Recall we have at our disposal the following survey design object
# defined on household data:
exdes

# Now use function svystat to prepare "grouped" estimates and errors
# of counts to be fitted separately (here groups are regions):
ee <- svystat(exdes, y=~ind, by=~age5c:marstat:sex, combo=3, group=~regcod)
ee
plot(ee)

# Fit registered GVF model number one separately inside groups:
m <- fit.gvf(ee, model=1)
m
summary(m)

# Now drop alleged outliers separately inside groups:

#####
# Method 'pick': work interactively group by group. #
#####
## Not run:
m1 <- drop.gvf.points(m, which.plot = 2, res.type = "student", col = "blue",
                      pch = 20)

m1
summary(m1)

## End(Not run)

```

```
#####
# Method 'cut': apply the same threshold to all groups. #
#####
m1 <- drop.gvf.points(m, method = "cut", res.type = "student", res.cut = 2)
m1
summary(m1)
```

e.calibrate

*Calibration of Survey Weights***Description**

Adds to an analytic object the calibrated weights column.

Usage

```
e.calibrate(design, df.population,
            calmodel = if (inherits(df.population, "pop.totals"))
                        attr(df.population, "calmodel"),
            partition = if (inherits(df.population, "pop.totals"))
                        attr(df.population, "partition") else FALSE,
            calfun = c("linear", "raking", "logit"),
            bounds = c(-Inf, Inf), aggregate.stage = NULL,
            sigma2 = NULL, maxit = 50, epsilon = 1e-07, force = TRUE)
```

Arguments

design	Object of class analytic (or inheriting from it) containing survey data and sampling design metadata.
df.population	Data frame containing the known population totals for the auxiliary variables.
calmodel	Formula defining the linear structure of the calibration model.
partition	Formula specifying the variables that define the "calibration domains" for the model ((see 'Details'); FALSE (the default) implies no calibration domains.
calfun	character specifying the distance function for the calibration process; the default is 'linear'.
bounds	Allowed range for the ratios between calibrated and initial weights; the default is c(-Inf, Inf).
aggregate.stage	An integer: if specified, causes the calibrated weights to be constant within sampling units at this stage.
sigma2	Formula specifying a possible heteroskedasticity effect in the calibration model; NULL (the default) implies homoskedasticity.
maxit	Maximum number of iterations for the Newton-Raphson algorithm; the default is 50.
epsilon	Tolerance for the absolute relative differences between the population totals and the corresponding estimates based on the calibrated weights; the default is 10^{-7} .
force	If TRUE, whenever the calibration algorithm does not converge, forces the function to return a value (see 'Details' and 'Calibration process diagnostics'); the default is TRUE.

Details

This function creates an object of class `cal.analytic`. A `cal.analytic` object makes it possible to compute estimates and standard errors of calibration estimators [Deville, Sarndal 92] [Deville, Sarndal, Sautory 93].

The mandatory argument `calmodel` symbolically defines the calibration model you intend using, that is - in the language of the Generalized Regression Estimator - the assisting linear regression model underlying the calibration problem. More specifically, the `calmodel` formula identifies the auxiliary variables and the constraints for the calibration problem, with a notation inspired by [Wilkinson, Rogers 73]. For example, `calmodel=~(X+Z):C+(A+B):D-1` defines the calibration problem in which constraints are imposed: (i) on the totals of auxiliary (quantitative) variables *X* and *Z* within the subpopulations identified by the (qualitative) classification variable *C* and, at the same time, (ii) on the absolute frequency of the (qualitative) variables *A* and *B* within the subpopulations identified by the (qualitative) classification variable *D*.

The design variables referenced by `calmodel` must be numeric or factor and must not contain any missing value (NA).

Problems for which one or more qualitative variables can be "*factorized*" in the formula that specifies the calibration model, are particularly interesting. These variables split the population into non-overlapping subpopulations known as "*calibration domains*" for the model. An example is provided by the statement `calmodel=~(A+B+X+Z):D-1` in which the variable that identifies the calibration domains is *D*; similarly, the formula `calmodel=~(A+B+X+Z):D1:D2-1` identifies as calibration domains the subpopulations determined by crossing the modalities of *D1* and *D2*. The interest in models of this kind lies in the fact that the *global* calibration problem they describe can, actually, be broken down into *local* subproblems, one per calibration domain, which can be solved separately [Vanderhoeft 01]. Thus, for example, the global problem defined by `calmodel=~(A+B+X+Z):D-1` is equivalent to the sequence of problems defined by the "*reduced model*" `calmodel=~A+B+X+Z-1` in each of the domains identified by the modalities of *D*. The opportunity to separately solve the subproblems related to different calibration domains achieves a significant reduction in computation complexity: the gain increases with increasing survey data size and (most importantly) with increasing auxiliary variables number.

The optional argument `partition` makes it possible to choose, in cases in which the calibration problem can be factorized, whether to solve the problem globally or in a partitioned way (that is, separately for each calibration domain). The global solution (which is the default option) can be selected invoking the `e.calibrate` function with `partition=FALSE`. To request the partitioned solution - a strongly recommended option when dealing with a lot of auxiliary variables and big data sizes - it is necessary to specify via `partition` the variables defining the calibration domains for the model. If a formula is passed through the `partition` argument (for example: `partition=~D1:D2`), the program checks that `calmodel` actually describes a "reduced model" (for example: `calmodel=~A+B+X+Z-1`), that is it does *not* reference any of the partition variables; if this is not the case, the program stops and prints an error message. Notice that a formula like `partition=~D1+D2` will be automatically translated into the factor-crossing formula `partition=~D1:D2`.

The design variables referenced by `partition` (if any) must be factor and must not contain any missing value (NA).

The mandatory argument `df.population` is used to specify the known totals of the auxiliary variables referenced by `calmodel` within the subpopulations (if any) identified by `partition`. These known totals must be stored in a data frame whose structure (i) depends on the values of `calmodel` and `partition` and (ii) must conform to a standard. In order to facilitate understanding of and compliance with this standard, the **ReGeneseees** package provides the user with four functions: `pop.template`, `population.check`, `pop.desc` and `fill.template`. The `pop.template` function is able to guide the user in constructing the known totals data frame for a specific calibration problem, the `pop.desc` function provides a natural language description of the template structure, the

`fill.template` function can be exploited to automatically fill the template when a sampling frame is available, while the `population.check` function allows to check whether a known totals data frame conforms to the standard required by `e.calibrate`. In any case, if the `df.population` data frame does not comply with the standard, the `e.calibrate` function stops and prints an error message: the meaning of the message should help the user diagnose the cause of the problem.

The `calfun` argument identifies the distance function to be used in the calibration process. Three built-in functions are provided: "linear", "raking", and "logit" (see [Deville, Sarndal, Sautory 93]). The default is "linear", which corresponds to the euclidean metric and yields the Generalized Regression Estimator (provided that no range restrictions are imposed on the g-weights). The "raking" distance corresponds to the "*multiplicative method*" of [Deville, Sarndal, Sautory 93].

The `bounds` argument allows to add "*range constraints*" to the calibration problem. To be precise, the interval defined by `bounds` will contain the values of the ratios between final (calibrated) and initial (direct) weights. The default value is `c(-Inf, Inf)`, i.e. no range constraints are imposed. These constraints are optional unless the "logit" function is selected: in the latter case the range defined by `bounds` has to be finite (see, again, [Deville, Sarndal, Sautory 93]).

The value passed by the `aggregate.stage` argument must be an integer between 1 and the number of sampling stages of design. If specified, causes the calibrated weights to be constant within sampling units selected at the `aggregate.stage` stage (actually this is only allowed if the initial weights had already this property, as it is sometimes the case in multistage cluster sampling). If not specified, the calibrated weights may differ even for sampling units with identical initial weights. The same holds if some final units belonging to the same cluster selected at the stage `aggregate.stage` fall in distinct calibration domains (i.e. if the domains defined by partition "cut across" the `aggregate.stage`-stage clusters).

The argument `sigma2` can be used to take into account a possible heteroskedasticity effect in the (assisting linear regression model underlying the) calibration problem. In such cases, `sigma2` must identify some variable to which the variances of the error terms are believed to be proportional. Notice that `sigma2` can also be interpreted from a "purely calibration-based" point of view: it corresponds to the $1/q_k$ unit-weights appearing inside the distance measures of [Deville, Sarndal 92] [Deville, Sarndal, Sautory 93]. The final effect is, on average, that calibrated weights associated to higher values of `sigma2` tend to stay closer to their corresponding initial weights. The `sigma2` formula can reference just a single design variable: such variable must be numeric, strictly positive and must not contain NAs. If `aggregate.stage` is specified, `sigma2` must obviously be constant inside `aggregate.stage`-stage clusters (otherwise the function stops and prints an error message).

The `maxit` argument sets the maximum number of iteration for the Newton-Raphson algorithm that is used to solve the calibration problem (the only exception being *unbounded linear* calibration, i.e. `calfun='linear'` and `bounds=c(-Inf, Inf)`, which is actually handled by directly solving a linear problem). The default value of `maxit` is 50.

The `epsilon` argument determines the convergence criterion for the optimization algorithm: it fixes the maximum allowed absolute value for the relative differences between the population totals and the corresponding estimates based on the calibrated weights. The default value is 10^{-7} .

The calibrated weights computed by `e.calibrate` must ensure that the calibration estimators of the auxiliary variables *exactly* match the corresponding known population totals. It is, however, possible (more likely when range constraints are imposed) that, for a specific calibration problem and for given values of `epsilon` and `maxit`, the solving algorithm does not converge. In this case, if `force = FALSE`, `e.calibrate` stops and prints an error message. If - on the contrary - `force = TRUE`, the function is forced to return the best approximation achieved for the calibrated weights, nevertheless signaling the calibration failure by a warning (see also Section 'Calibration process diagnostics').

Value

An object of class `cal.analytic`. The data frame it contains includes (in addition to the data already stored in `design`) the calibrated weights columns. The name of this column is obtained by pasting the name of the initial weights column with the string `".cal"`.

Calibration Process Diagnostics

When, dealing with a factorizable calibration problem, the user selects the partitioned solution, the global calibration problem gets split into as many *sub-problems* as the number of subpopulations defined by partition. In turn, each one of these calibration sub-problems can end without convergence on any one of the involved auxiliary variables. A calibration process with such a complex structure needs some ad hoc tool for error diagnostics. For this purpose, every call to `e.calibrate` creates, by side effect, a dedicated data structure named `ecal.status` into the `.GlobalEnv`.

`ecal.status` is a list with up to three components: the first, `"call"`, identifies the call to `e.calibrate` that generated the list, the second, `return.code`, is a matrix each element of which identifies the return code of a specific calibration sub-problem. The meaning of the return codes is as follows:

CODE	MEANING
-1.....	not yet tackled sub-problem;
0.....	solved sub-problem (convergence achieved);
1.....	unsolved sub-problem (no convergence): output forced.

Recall that the latter return code (1) may only occur if `force = TRUE`.

If any `return.code` equal to 1 exists, the `ecal.status` list gains a third component named `"fail.diagnostics"` which is itself a list; its components correspond to sub-problems for which convergence was not achieved, and store useful information about the auxiliary variables for which calibration constraints are violated. Therefore, users can exploit `ecal.status` to identify sub-problems and variables from which errors stemmed, hence taking a step forward to eliminate them.

Notice, lastly, that the `ecal.status` list will also be persistently bound to the `e.calibrate` return object, stored inside a dedicated attribute. For the inspection of such diagnostics information the [check.cal](#) function is available.

Note

The `cal.analytic` class is a specialization of the [analytic](#) class; this means that an object created by `e.calibrate` inherits from the [analytic](#) class and you can use on it all methods defined on the latter class, e.g. `print`, `summary`, [weights](#). Moreover, a calibrated design can be passed again to `e.calibrate`, thus undergoing further calibration steps.

Author(s)

Diego Zardetto

References

- Deville, J.C., Sarndal, C.E. (1992) *"Calibration Estimators in Survey Sampling"*, Journal of the American Statistical Association, Vol. 87, No. 418, pp. 376-382.
- Deville, J.C., Sarndal, C.E., Sautory, O. (1993) *"Generalized Raking Procedures in Survey Sampling"*, Journal of the American Statistical Association, Vol. 88, No. 423, pp. 1013-1020.
- Wilkinson, G.N., Rogers, C.E. (1973) *"Symbolic Description of Factorial Models for Analysis of Variance"*, Journal of the Royal Statistical Society, series C (Applied Statistics), Vol. 22, pp. 181-191.

Vanderhoeft, C. (2001) *"Generalized Calibration at Statistic Belgium"*, Statistics Belgium Working Paper n. 3.

Sarndal, C.E., Lundstrom, S. (2005) Estimation in surveys with nonresponse. John Wiley & Sons.

Scannapieco, M., Zardetto, D., Barcaroli, G. (2007) *"La Calibrazione dei Dati con R: una Sperimentazione sull'Indagine Forze di Lavoro ed un Confronto con GENESEES/SAS"*, Contributi Istat n. 4., http://www3.istat.it/dati/pubbsci/contributi/Contributi/contr_2007/2007_4.pdf.

See Also

`e.svydesign` to bind survey data and sampling design metadata, `svystatTM`, `svystatR`, `svystatS`, `svystatSR`, `svystatB`, `svystatQ` and `svystatL` for calculating estimates and standard errors, `pop.template` for constructing known totals data frames in compliance with the standard required by `e.calibrate`, `population.check` to check that the known totals data frame satisfies that standard, `pop.desc` to provide a natural language description of the template structure, `fill.template` to automatically fill the template when a sampling frame is available, `bounds.hint` to obtain a hint for range restricted calibration, `g.range` to assess the variation of weights after calibration and `check.cal` to check if calibration constraints have been fulfilled.

Examples

```
#####
# Calibration of a design object according to different calibration #
# models (the known totals data frames pop01, ..., pop05p and the #
# bounds vector are all contained in the data.examples file).      #
# For the examples relating to calibration models that can be      #
# factorized both a global and a partitioned solution are given.   #
#####

# Load household data:
data(data.examples)

# Creation of the object to be calibrated:
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
  weights=~weight)

# 1) Calibration on the total number of units in the population
# (totals in pop01):
descal01<-e.calibrate(design=des,df.population=pop01,calmodel=~1,
  calfun="logit",bounds=bounds,aggregate.stage=2)

# Printing desc01 immediately recalls that it is a
# "calibrated" object:
descal01

# Use the summary() function if you need some additional details, e.g.:
summary(descal01)

# Use the 'variables' slot to extract survey data, e.g.:
head(descal01$variables)

# Use the weights() function to extract weights, e.g.:
summary(weights(descal01))
```



```

# Checking the result (first add the new 'ones' variable
# to estimate the number of final units in the population):
descal01<-des.addvars(descal01,ones=1)
svystatTM(descal01, ~ones)

# 2) Calibration on the marginal distributions of sex and marstat
# (totals in pop02):
descal02<-e.calibrate(design=des,df.population=pop02,
                      calmodel=~sex+marstat-1,calfun="logit",bounds=bounds,
                      aggregate.stage=2)

# Checking the result:
svystatTM(descal02,~sex+marstat)

# 3) Calibration (global solution) on the joint distribution of sex
# and marstat (totals in pop03):
descal03<-e.calibrate(design=des,df.population=pop03,
                      calmodel=~marstat:sex-1,calfun="logit",bounds=bounds)

# Checking the result:
svystatTM(descal03,~sex,~marstat) # or: svystatTM(descal03,~marstat,~sex)

# which, obviously, is not respected by desc02 (notice the size of SE):
svystatTM(descal02,~sex,~marstat)

# 3.1) Again a calibration on the joint distribution of sex and marstat
# but, this time, with the partitioned solution (partition=~sex,
# totals in pop03p):
descal03p<-e.calibrate(design=des,df.population=pop03p,
                      calmodel=~marstat-1,partition=~sex,calfun="logit",
                      bounds=bounds)

# Checking the result:
svystatTM(descal03p,~sex,~marstat)

# 4) Calibration (global solution) on the totals for the quantitative
# variables x1, x2 and x3 in the subpopulations defined by the
# regcod variable (totals in pop04):
descal04<-e.calibrate(design=des,df.population=pop04,
                      calmodel=~(x1+x2+x3-1):regcod,calfun="logit",
                      bounds=bounds,aggregate.stage=2)

# Checking the result:
svystatTM(descal04,~x1+x2+x3,~regcod)

# 4.1) Same problem with the partitioned solution (partition=~regcod,
# totals in pop04p):
descal04p<-e.calibrate(design=des,df.population=pop04p,
                      calmodel=~x1+x2+x3-1,partition=~regcod,calfun="logit",
                      bounds=bounds,aggregate.stage=2)

# Checking the result:

```

```

svystatTM(descal04p,~x1+x2+x3,~regcod)

# 5) Calibration (global solution) on the total for the quantitative
#   variable x1 and on the marginal distribution of the qualitative
#   variable age5c, in the subpopulations defined by crossing sex
#   and marstat (totals in pop05):
descal05<-e.calibrate(design=des,df.population=pop05,
                      calmodel=~(age5c+x1-1):sex:marstat,calfun="logit",
                      bounds=bounds)

# Checking the result:
svystatTM(descal05,~age5c+x1,~sex:marstat)

# 5.1) Same problem with the partitioned solution (partition=~sex:marstat,
#   totals in pop05p):
descal05p<-e.calibrate(design=des,df.population=pop05p,
                      calmodel=~age5c+x1-1,partition=~sex:marstat,
                      calfun="logit",bounds=bounds)

# Checking the result:
svystatTM(descal05p,~age5c+x1,~sex:marstat)

# Notice that 3.1 and 5.1) 5.2) do not impose the aggregate.stage=2
# condition. This condition cannot, in fact, be fulfilled because
# in both cases the domains defined by partition "cut across"
# the des second stage clusters (households). To compare the results,
# the same choice was also made for 3) and 5).

# 5.2) Just a single example to inspect the ecal.status list generated
#   for diagnostics purposes.
#   Let's shrink the bounds in order to prevent perfect convergence
#   (recall that force=TRUE by default):
approx.cal<-e.calibrate(design=des,df.population=pop05p,
                      calmodel=~age5c+x1-1,partition=~sex:marstat,
                      calfun="logit",bounds=c(0.95,1.05))

# ...now use check.cal function to assess the amount of calibration
# constraints violation:
check.cal(approx.cal)

# ...or (equivalently) inspect directly ecal.status:
ecal.status

#####
# Some examples illustrating how calibration   #
# can be exploited to reduce nonresponse bias  #
# (see, e.g. [Sarndal, Lundstrom 05]).        #
#####

# Load sbs data:
data(sbs)

#####

```

```

# Full-response case. #
#####

# Create a full-response design object:
sbsdes<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,fpc=~fpc)

# Now estimate the average value added and its 95% confidence interval:
mean.VA<-svystatTM(design=sbsdes,y=~va.imp2,estimator="Mean",vartype="cvpct",
  conf.int=TRUE,conf.lev=0.95)
mean.VA

# Compare the obtained estimate with the true population parameter:
MEAN.VA<-mean(sbs.frame$va.imp2)
MEAN.VA

# We get a small overestimation of about 4%...
100*(coef(mean.VA)-MEAN.VA)/MEAN.VA

# which, anyway, doesn't indicate a significant bias for the
# full-response sample, because the 95% confidence interval
# covers the true value.

#####
# Nonresponse case: assume a response propensity #
# which increases with enterprise size.          #
#####

# Set bigger response probabilities for bigger firms,
# e.g. exploiting available information about the
# number of employees (emp.cl):
levels(sbs$emp.cl)
p.resp <- c(.4,.6,.8,.95,.99)

# Tie response probabilities to sample observations:
pr<-p.resp[unclass(sbs$emp.cl)]

# Now, randomly select a subsample of responding units from sbs:
set.seed(12345)          # (fix the RNG seed for reproducibility)
rand<-runif(1:nrow(sbs))
sbs.nr<-sbs[rand<pr,]

# This implies an overall response rate of about 73%:
nrow(sbs.nr)/nrow(sbs)

# Treat the non-response sample as it was complete: this should
# lead to biased estimates of value added, as the latter is
# positively correlated with firms size...
sbsdes.nr<-e.svydesign(data=sbs.nr,ids=~id,strata=~strata,weights=~weight)

#...indeed:
old.op <- options("RG.lonely.psu"="adjust") # (prevent lonely-PSUs troubles)
mean.VA.nr<-svystatTM(design=sbsdes.nr,y=~va.imp2,estimator="Mean",
  vartype="cvpct",conf.int=TRUE,conf.lev=0.95)
mean.VA.nr

# and, comparing with the true population average, we see a

```

```

# significant overestimation effect, with the 95% confidence
# interval not even covering the parameter:
MEAN.VA

# Nonresponse bias can be effectively reduced by calibrating
# on variables explaining the response propensity: e.g., in
# the present example, on the population distribution of emp.cl:
# Prepare the known totals template...
N.emp.cl<-pop.template(data=sbs.nr,calmodel=~emp.cl-1)
N.emp.cl

# Fill it by using the sampling frame...
N.emp.cl<-fill.template(sbs.frame,N.emp.cl)
N.emp.cl

# Lastly calibrate:
# Get a hint on the calibration bounds:
hint<-bounds.hint(sbsdes.nr,N.emp.cl)
sbscal.nr<-e.calibrate(design=sbsdes.nr,df.population=N.emp.cl,
                      bounds=hint)
sbscal.nr

# Now estimate the average value added on the calibrated design:
mean.VA.cal.nr<-svystatTM(design=sbscal.nr,y=~va.imp2,estimator="Mean",
                          vartype= "cvpct",conf.int=TRUE,conf.lev=0.95)

# options(old.op) # (reset variance estimation options)

# As expected, we see a significant bias reduction:
MEAN.VA
mean.VA.nr
mean.VA.cal.nr

# Even if the 95% confidence interval still doesn't cover the
# true value, by calibration we passed from an initial overestimation
# of about 33% to a 7% one:
100*(coef(mean.VA.nr)-MEAN.VA)/MEAN.VA
100*(coef(mean.VA.cal.nr)-MEAN.VA)/MEAN.VA

#####
# A multi-step calibration example showing that #
# a calibrated object can be calibrated again #
# (this can be sometimes useful in practice): #
# Step 1: calibrate to reduce nonresponse bias; #
# Step 2: calibrate again to gain efficiency. #
#####

# Suppose you already performed a first calibration step,
# as shown in the example above, with the aim of softening
# nonresponse bias:
sbscal.nr

# Now you may want to calibrate again in order to reduce
# estimators variance, by using further available auxiliary
# information, e.g. the total number of employees (emp.num)
# and enterprises (ent) inside the domains obtained

```

```

# by crossing nace.macro and region:

# Build the second step population totals template:
pop2<-pop.template(sbscal.nr,
  calmodel=~emp.num+ent-1,
  partition=~nace.macro:region)

# Use the fill.template function to (i) automatically compute
# the totals from the universe (sbs.frame) and (ii) safely fill
# the template:
pop2<-fill.template(universe=sbs.frame,template=pop2)

# Now perform the second calibration step:
# Get a hint on the calibration bounds:
hint2<-bounds.hint(sbscal.nr,pop2)
sbscal.nr2<-e.calibrate(design=sbscal.nr,df.population=pop2,
  bounds=hint2)

# Notice that printing sbscal.nr2 you immediately understand
# that it is a "twice-calibrated" object:
sbscal.nr2

# Notice also that, even if the second calibration step causes
# sbscal.nr2 to be no more exactly calibrated with respect to
# emp.cl (look at the cvpct values)...
old.op <- options("RG.lonely.psu"="adjust") # (prevent lonely-PSUs troubles)
svystatTM(design=sbscal.nr2,y=~emp.cl,vartype="cvpct")

# ...the nonresponse bias has not been resurrected (i.e. it gets stuck
# to its previous 7%):
mean.VA.cal.nr2<-svystatTM(design=sbscal.nr2,y=~va.imp2,estimator="Mean",
  vartype="cvpct",conf.int=TRUE,conf.lev=0.95)

options(old.op) # (reset variance estimation options)

mean.VA.cal.nr2
100*(coef(mean.VA.cal.nr2)-MEAN.VA)/MEAN.VA

#####
# Provided the auxiliary variables are chosen in a smart way #
# a single calibration step can simultaneously succeed in: #
# (i) softening nonresponse bias; #
# (ii) reducing estimators variance. #
#####

# Let's come back to the original design with nonresponse:
sbsdes.nr

# Now, let's try to calibrate simultaneously on (see examples above):
# (i) the population distribution of emp.cl;
# (ii) the total number of employees (emp.num) and enterprises (ent)
# inside the domains obtained by crossing nace.macro and region:

# Build the population totals template (notice that we are now forced
# to a global calibration, as we are assuming to ignore emp.cl counts
# inside domains obtained by crossing nace.macro and region):

```

```

pop1<-pop.template(sbs.nr,
  calmodel=~emp.cl+(emp.num+ent):nace.macro:region-1)

# Use the fill.template function to (i) automatically compute
# the totals from the universe (sbs.frame) and (ii) safely fill
# the template:
pop1<-fill.template(universe=sbs.frame,template=pop1)

# Now perform the single calibration step:
# Get a hint on the calibration bounds:
hint1<-bounds.hint(sbsdes.nr,pop1)
sbscal.nr1<-e.calibrate(design=sbsdes.nr,df.population=pop1,
  bounds=hint1)

sbscal.nr1

# Now:
# (i) verify the nonresponse bias reduction effect:
old.op <- options("RG.lonely.psu"="adjust") #(prevent lonely-PSUs troubles)
mean.VA.cal.nr1<-svystatTM(design=sbscal.nr1,y=~va.imp2,estimator="Mean",
  vartype= "cvpct",conf.int=TRUE,conf.lev=0.95)
options(old.op)

mean.VA.cal.nr1
100*(coef(mean.VA.cal.nr1)-MEAN.VA)/MEAN.VA

# thus we are back to ~7%, as for the previous 2-step calibration example.

# (ii) compare cvpct with the previous 2-step calibration example:
mean.VA.cal.nr1
mean.VA.cal.nr2

# hence, both bias reduction and efficiency are almost the same in 2-step and
# single step calibration (auxiliary information being equal): the choice
# will often depend on practical considerations (e.g. convergence, computation
# time).

#####
# Example with heteroskedastic assisting linear model: shows how to obtain #
# the ratio estimator of a total by calibration. #
#####

# Load sbs data:
data(sbs)

# Create the design object to be calibrated:
sbsdes<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,fpc=~fpc)

# Suppose you have to calibrate on the total amount of employees:
# Prepare the template:
pop<-pop.template(data=sbsdes,calmodel=~emp.num-1)
pop

# Fill it by using the sampling frame (sbs.frame)...
pop<-fill.template(sbs.frame,pop)
pop

```

```

# ... thus the total number of employees is 984394.
# Now calibrate assuming that error terms variances are proportional
# to emp.num:
sbscal<-e.calibrate(design=sbsdes,df.population=pop,sigma2=~emp.num)

# Now compute the calibration estimator of the total
# of value added (i.e. variable va.imp2)...
VA.tot.cal<-svystatTM(design=sbscal,y=~va.imp2)
VA.tot.cal

#... and observe that this is identical to the ratio estimator of the total...
TOT.emp.num <- pop[1, 1]
VA.ratio<-svystatL(design=sbsdes, expression(TOT.emp.num * (va.imp2/emp.num)))
VA.ratio

# ...as it must be.

# Recall that, for the calibration problem above, one must expect, by virtue of
# simple theoretical arguments, that the g-weights are constant and equal to the
# ratio between the known total of emp.num (984394) and its HT estimate.
# This property is exactly satisfied by our numerical results, see below:
pop[1, 1]/coef(svystatTM(sbsdes, ~emp.num))
g.range(sbscal)

# ...as it must be.

#####
# A second example of calibration with heteroskedastic assisting linear #
# model. Shows that calibrated weights associated to higher values of   #
# sigma2 tend to stay closer to their corresponding initial weights.    #
#####

# Perform a calibration process which exploits as auxiliary
# information the total number of employees (emp.num)
# and enterprises (ent) inside the domains obtained by:
# i) crossing nace2 and region;
# ii) crossing emp.cl, region and nace.macro;

# Build the population totals template:
pop<-pop.template(sbsdes,
  calmodel=~(emp.num+ent):(nace2+emp.cl:nace.macro)-1,
  partition=~region)

# Use the fill.template function to (i) automatically compute
# the totals from the universe (sbs.frame) and (ii) safely fill
# the template:
pop<-fill.template(universe=sbs.frame,template=pop)

# Now calibrate:
# 1) First, without any heteroskedasticity effect
sbscal1<-e.calibrate(sbsdes,pop,calfun="linear",bounds = c(0.01, 3),
  sigma2=NULL)

# 2) Then, with heteroskedastic effect proportional to emp.num:
sbscal2<-e.calibrate(sbsdes,pop,calfun="linear",bounds = c(0.01, 3),

```

```

sigma2=~emp.num)

# Compute the g-weights for both the calibrated objects:
g1<-weights(sbscal1)/weights(sbsdes)
g2<-weights(sbscal2)/weights(sbsdes)

# Now visually compare the absolute deviations from 1 of the g-weights
# as a function of emp.num:
plot(log10(sbs$emp.num),abs(g1-1), col="blue", pch=19, cex=0.5)
points(log10(sbs$emp.num),abs(g2-1), col="red", pch=19, cex=0.5)

#...as emp.num grows red points clearly tend to stay closer to
# the horizontal axis than blue ones, as expected.

#####
# Calibrating simultaneously on unit-level and cluster-level #
# auxiliary informations: an household survey example.      #
#####

# Load household data:
data(data.examples)

# Define the survey design:
exdes<-e.svydesign(data=example,ids=~towcod+famcod,strata=~stratum,
                  weights=~weight)

# Collapse strata to eliminate lonely PSUs:
exdes<-collapse.strata(design=exdes,block.vars=~sr:procod)

# Now add new convenience variables to the design object:
## 'houdensity': to estimate households counts
## 'ones':      to estimate individuals counts
exdes<-des.addvars(exdes,
                  houdensity=ave(famcod,famcod,FUN = function(x) 1/length(x)),
                  ones=1)

# Let's see how it's possible to calibrate *simultaneously* on:
# 1. the number of *individuals* crossclassified by sex, 5 age classes,
#    and province;
# 2. the number of *households* by region.

# First, for the purpose of running the example, let's generate some
# artificial population totals. We have only to get HT estimates for
# the auxiliary variables and perturb them randomly:
# Get HT estimates of auxiliary variables:
xx<-aux.estimates(design=exdes,calmodel=~houdensity+sex:age5c:procod-1,
                  partition=~regcod)

# Add a random uniform perturbation to these numbers:
set.seed(12345) # Fix the RNG seed for reproducibility
xx[,-1]<-round(xx[,-1]*runif(prod(dim(xx[,-1])),0.8,1.2))

# Now we have at hand our artificial population totals, and
# we can proceed with the calibration task:
excal<-e.calibrate(design=exdes,df.population=xx,calfun= "linear",
                  bounds=c(0,3),aggregate.stage=2)

```



```

# To perceive the effect of calibration, let's e.g. compare the HT and
# calibrated estimates of the average number of individuals per household
# at population level:
svystatR(exdes,~ones,~houdensity,vartype="cvpct")
svystatR(excal,~ones,~houdensity,vartype="cvpct")

#####
# Calibrating on different patterns of #
# "incomplete" auxiliary information. #
#####

# Usually calibration constraints involve "complete auxiliary information",
# i.e. totals which are known either:
#   (i) for the target population as a whole (e.g. total number of
#       employees working in italian active enterprises at a given date);
# or:
#   (ii) for each subpopulation belonging to a complete partition of
#       the target population (e.g. number of male and female people
#       residing in Italy at a given date).
#
# Anyway, it may happen sometimes that the available auxiliary information
# is actually "incomplete", i.e. one doesn't know all the totals for all the
# subpopulations in a partition, but rather only for some of them. As an
# example, suppose marital status has categories "married", "unmarried",
# and "widowed" and that one only knows the number of "unmarried" people.
#
# In what follows I show how you can use ReGenesees to handle a calibration
# task on "incomplete" auxiliary information.

#####
# A simple example. #
#####

# Load household data:
data(data.examples)

# Define the survey design:
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
  weights=~weight)

# Suppose you only know the number of "unmarried" people (let's say 398240)
# but you ignore "married" and "widowed" totals, and you want to calibrate
# on this incomplete information.

# First, add to the survey design a new numeric variable with value 1
# for unmarried people and 0 otherwise:
des<-des.addvars(des,unmarried=as.numeric(marstat=="unmarried"))

# Second, prepare a template to store the known "unmarried" people count:
pop<-pop.template(des,calmodel=~unmarried-1)

# Third, fill the template with the known total:
pop[1,1]<-398240

# Fourth, calibrate:

```

```

descal<-e.calibrate(des,pop)

# Now test that only "unmarried" estimated total has 0 percent CV:
Zapsmall(svystatTM(descal,~marstat,vartype="cvpct"))

# ...as it must be.

#####
# A more complicated example. #
#####

# Load sbs data:
data(sbs)

# Define the survey design:
sbsdes<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,fpc=~fpc)

# Suppose you want to calibrate on the following "incomplete" known totals:
# 1. enterprises counts by nace.macro
# 2. enterprises counts by dom3 ONLY inside nace.macro 'Industry'
# 3. total of y by emp.c1 ONLY inside nace.macro 'Commerce'

# First, add to the survey design new variables identifying the domains
# where "incomplete" totals 2. and 3. are known:
## 2. -> nace.macro = 'Industry'
sbsdes<-des.addvars(sbsdes,Industry=as.numeric(nace.macro=="Industry"))
## 3. -> nace.macro = 'Commerce'
sbsdes<-des.addvars(sbsdes,Commerce=as.numeric(nace.macro=="Commerce"))

# Do the same for the sampling frame:
## 2. -> nace.macro = 'Industry'
sbs.frame$Industry=as.numeric(sbs.frame$nace.macro=="Industry")
## 3. -> nace.macro = 'Commerce'
sbs.frame$Commerce=as.numeric(sbs.frame$nace.macro=="Commerce")

# Second, prepare a template to store the totals listed in 1., 2. and 3.;
# to this purpose one can e.g. compute HT estimates of the involved auxiliary
# variables:
Xht<-aux.estimates(design=sbsdes,
                   calmodel=~nace.macro+Industry:dom3+Commerce:y:emp.c1-1)
Xht

# Third, use the structure above to compute actual population totals
# from the sampling frame:
pop <- fill.template(universe=sbs.frame,template=Xht)
pop

# Fourth, calibrate:
sbscal <- e.calibrate(design=sbsdes,df.population=pop)

# Test1: nace.macro counts have 0 CVs:
test1<-svystatTM(design=sbscal,y=~nace.macro,vartype="cvpct")
test1

# Test2: only 'Industry' macrosector has 0 CVs for dom3 counts:
test2<-svystatTM(design=sbscal,y=~dom3,by=~nace.macro,vartype="cvpct")

```

```
Zapsmall(test2)

# Test3: only 'Commerce' macrosector has 0 CVs for y total by emp.cl:
test3<-svystatTM(design=sbscal,y=~y,by=~emp.cl:nace.macro,vartype="cvpct")
Zapsmall(test3)
```

e.svydesign

*Specification of a Complex Survey Design***Description**

Binds survey data and sampling design metadata.

Usage

```
e.svydesign(data, ids, strata = NULL, weights,
            fpc = NULL, self.rep.str = NULL, check.data = TRUE)

## S3 method for class 'analytic'
summary(object, ...)
```

Arguments

<code>data</code>	Data frame of survey data.
<code>ids</code>	Formula identifying clusters selected at subsequent sampling stages (PSUs, SSUs, ...).
<code>strata</code>	Formula identifying the stratification variable; NULL (the default) implies no stratification.
<code>weights</code>	Formula identifying the initial weights for the sampling units.
<code>fpc</code>	Formula identifying finite population corrections at subsequent sampling stages (see ‘Details’).
<code>self.rep.str</code>	Triggers an approximate variance estimation method for multistage designs (see ‘Details’). If not NULL (the default), must be a formula identifying self-representing strata (SR), if any.
<code>check.data</code>	Check out the correct nesting of data clusters? The default is TRUE.
<code>object</code>	An object of class <code>analytic</code> , as returned by <code>e.svydesign</code> .
<code>...</code>	Arguments for future extensions.

Details

This function has the purpose of binding in an effective and persistent way the survey data to the metadata describing the adopted sampling design. Both kinds of information are stored in a complex object of class `analytic`, which extends the `survey.design2` class from the **survey** package. The sampling design metadata are then used to enable and guide processing and analyses provided by other functions in the **ReGenesee**s package (such as [e.calibrate](#), [svystatTM](#), ...).

The `data`, `ids` and `weights` arguments are mandatory, while `strata`, `fpc`, `self.rep.str` and `check.data` arguments are optional. The data variables that are referenced by `ids`, `weights` and, if specified, by `strata`, `fpc`, `self.rep.str` must not contain any missing value (NA). Should empty levels be present in any factor variable belonging to `data`, they would be dropped.

The `ids` argument specifies the cluster identifiers. It is possible to specify a multistage sampling design by simply using a formula which involves the identifiers of clusters selected at subsequent sampling stages. For example, `ids=~id.PSU + id.SSU` declares a two-stage sampling in which the first stage units are identified by the `id.PSU` variable and second stage ones by the `id.SSU` variable.

The `strata` argument identifies the stratification variable. The data variable referenced by `strata` (if specified) must be a factor. By default the sample is assumed to be non-stratified.

The `weights` argument identifies the initial (or direct) weights for the units included in the sample. The data variable referenced by `weights` must be numeric. Direct weights must be strictly positive.

The `fpc` formula serves the purpose of specifying the finite population corrections at subsequent sampling stages. By default `fpc=NULL`, which implies with-replacement sampling.

If the survey has only one stage, then the `fpc`s can be given either as the total population size in each stratum or as the fraction of the total population that has been sampled. In either case the relevant population size must be expressed in terms of sampling units (be they elementary units or clusters). That is, sampling 100 units from a population stratum of size 500 can be specified as 500 or as $100/500=0.2$. Thus, passing to `fpc` a column of zeros, means again with-replacement sampling.

For multistage sampling the population size (or the sampling fraction) for each sampling stage should also be specified in `fpc`. For instance, when `ids=~id.PSU + id.SSU` the `fpc` formula should look like `fpc=~fpc.PSU + fpc.SSU`, with variable `fpc.PSU` giving the population sizes (or sampling fractions) in each stratum for the first stage units, while variable `fpc.SSU` gives population sizes (or sampling fractions) for the second stage units in each sampled PSU. Notice that if you choose to pass to `fpc` population totals (rather than sampling rates) at a given stage, then you must do the same for all stages (and vice versa).

If `fpc` is specified but for fewer stages than `ids`, sampling is assumed to be *complete* for subsequent stages. The function will check that `fpc`s values at each sampling stage do not vary within strata.

When dealing with a two-stage (multistage) stratified sampling design that includes *self-representing (SR) strata* (i.e. strata containing only PSUs selected with probability 1), the only (leading) contribution to the variance of SR strata arises from the second stage units ("*variance PSUs*").

When `options("RG.ultimate.cluster")` is FALSE (which is the default for **ReGenesees**), variance estimation for SR strata is correctly handled provided the survey `fpc`s have been properly specified. In particular, if `fpc=~fpc.PSU + fpc.SSU` and one specifies `fpc`s in terms of sampling fractions, then, inside SR strata, `fpc.PSU` must be always equal to one. When, on the contrary, the "*Ultimate Cluster Approximation*" holds (i.e. `options("RG.ultimate.cluster")` has been set to TRUE) the SR strata give no contribution at all to the sampling variance.

A compromise solution (adopted by former existing survey software) is the one of retaining, for both SR and not-SR strata, only the leading contribution to the sampling variance. This means that only the SSUs are relevant for SR strata, whereby only the PSUs matter in not-SR strata. This compromise solution can be achieved by using the `self.rep.str` argument. If this argument is actually specified (as a formula referencing the data variable that identifies the SR strata), a warning is generated in order to remind the user that an approximate variance estimation method will be adopted on that design. Notice that, when choosing the `self.rep.str` option, the user must ensure that the variable referenced by `self.rep.str` is logical (with value TRUE for SR strata and FALSE otherwise) or numeric (with value 1 for SR strata and 0 otherwise) or factor (with levels "1" for SR strata and "0" otherwise).

The optional argument `check.data` allows to check out the correct nesting of data clusters (PSUs, SSUs, ...). If `check.data=TRUE` the function checks that every unit selected at stage $k+1$ is associated to one and only one unit selected at stage k . For a stratified design the function checks also the correct nesting of clusters within strata.

Value

An object of class `analytic`. The `print` method for that class gives a concise description of the sampling design. The `summary` method provides further details. Objects of class `analytic` persistently store input survey data inside their `variables` component. Weights can be accessed by using the `weights` function.

PPS Sampling Designs

Probability proportional to size sampling *with replacement* does not pose any problem: one must simply specify `fpc=NULL` and pass the right weights. This holds also for multistage designs, where PSUs are selected with replacement with PPS inside strata. Moreover, when the PSUs are sampled with replacement, the only contribution to the variance arises from the estimated PSU totals, and one can simply ignore any available information about subsequent sampling stages.

For unequal probability sampling *without replacement*, on the contrary, in order to get correct variance estimates, one should know the second-order inclusion probabilities under the sampling design at hand. Unluckily, these probabilities cannot generally be computed, thus one has to resort to some viable approximation. The easier one rests on pretending that PSUs were sampled with replacement, even if this is not actually the case. It is worth stressing that this approach will result in conservative estimates. Moreover, the variance overestimation is expected to be negligible as long as the actual sampling fractions of PSUs are close to zero. Notice that this "with replacement" approximation can be achieved by either not specifying `fpc`, or by passing to the PSUs term of `fpc` a column of zeros.

Note

The `analytic` class is a specialization of the `survey.design2` class from the **survey** package; this means that an object created by `e.svydesign` inherits from the `survey.design2` class and you can use on it every method defined on the latter class.

Author(s)

Diego Zardetto.

References

Sarndal, C.E., Swensson, B., Wretman, J. (1992) *"Model Assisted Survey Sampling"*, Springer Verlag.

Lumley, T. (2006) *"survey: analysis of complex survey samples"*, <http://cran.at.r-project.org/web/packages/survey/index.html>.

See Also

`svyestatTM`, `svyestatR`, `svyestatS`, `svyestatSR`, `svyestatB`, `svyestatQ`, `svyestatL` for calculating estimates and standard errors, `e.calibrate` for calibrating weights, `ReGenesees.options` for setting/changing variance estimation options, `collapse.strata` for the suggested way of handling lonely PSUs, `weights` to extract weights.

Examples

```
#####
# The following examples illustrate how to create objects  #
# (of class 'analytic') defining different sampling designs. #
```

```

# Note: sometimes the same survey data will be used to      #
# define more than one design: this serves only the purpose #
# of illustrating e.svydesign syntax.                        #
#####

data(data.examples)
# Two-stage stratified cluster sampling design (notice that
# the design contains lonely PSUs):
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~stratum,
               weights=~weight)
des

# Use the summary() function if you need some additional details, e.g.:
summary(des)

# Use the 'variables' slot to extract survey data, e.g.:
head(des$variables)

# Use the weights() function to extract weights, e.g.:
summary(weights(des))

# Again the same design, but using collapsed strata (SUPERSTRATUM variable)
# to remove lonely PSUs:
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
               weights=~weight)
des

# Two stage cluster sampling (no stratification):
des<-e.svydesign(data=example,ids=~towcod+famcod,weights=~weight)
des

# Stratified unit sampling design:
des<-e.svydesign(data=example,ids=~key,strata=~SUPERSTRATUM,
               weights=~weight)
des

data(sbs)
# One-stage stratified unit sampling without replacement
# (notice the presence of the fpc argument):
des<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,
               fpc=~fpc)
des

# Same design as above but ignoring the finite population corrections:
des<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight)
des

data(fpcdat)
# Two-stage stratified cluster sampling without replacement
# (notice that the fpcs are specified for both stages):
des<-e.svydesign(data=fpcdat,ids=~psu+ssu,strata=~stratum,weights=~w,
               fpc=~fpc1+fpc2)
des

# Same design as above but assuming complete sampling for the

```

```
# second stage units (notice fpcs have been passed only for the
# first stage):
des<-e.svydesign(data=fpcdat,ids=~psu+ssu,strata=~stratum,weights=~w,
  fpc=~fpc1)
des

# Again a two-stage stratified cluster sampling without replacement but
# specified in such a way as to retain, in the estimation phase, only
# the leading contribution to the sampling variance (i.e. the one arising
# from SSUs in SR strata and PSUs in not-SR strata). Notice that the
# self.rep.str argument is used:
des<-e.svydesign(data=fpcdat,ids=~psu+ssu,strata=~stratum,weights=~w,
  fpc=~fpc1+fpc2, self.rep.str=~sr)
des
```

estimator.kind

Which Estimator Did Generate these Survey Statistics?

Description

Identifies what kind of estimator has been used to compute a (set of) survey static(s).

Usage

```
estimator.kind(stat, design)
```

Arguments

stat	An object containing survey statistics.
design	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.

Details

Given a survey statistic object `stat` and a survey design object `design` from which `stat` is supposed to have been derived, this function returns the “precise kind” of the corresponding estimator, as a textual description.

Argument `stat` can be any object which have been returned by calling a survey statistics function (e.g. `svyestatTM`, `svyestatR`, `svyestatS`, `svyestatSR`, `svyestatB`, `svyestatQ`, `svyestatL`) on survey design object `design`. It can also be a collection of survey statistics as generated by protean function `svyestat`, provided that function is invoked with `forGVF = FALSE`.

Should `stat` be a survey statistic derived from a design object *other than* `design`, the function would raise an error.

Note that function `estimator.kind` is smart enough to recognize that estimates of totals/means of *dummy variables* are actually estimates of absolute/relative frequencies, despite such variables are of class `numeric` (see Section ‘Examples’).

Value

A character string describing the estimator kind.

Currently, possible return values (i.e. estimator kinds) are the following:

- (1) 'Total'
- (2) 'Absolute Frequency'
- (3) 'Mix of Totals and Absolute Frequencies'
- (4) 'Mean'
- (5) 'Relative Frequency'
- (6) 'Mix of Means and Relative Frequencies'
- (7) 'Ratio'
- (8) 'Share'
- (9) 'Share Ratio'
- (10) 'Regression Coefficient'
- (11) 'Quantile'
- (12) 'Complex Estimator'

Author(s)

Diego Zardetto

See Also

[gvf.input](#) and [svystat](#) to prepare the input for GVF model fitting, [fit.gvf](#) to fit GVF models, and [GVF.db](#) to manage **ReGenesees** archive of registered GVF models.

Examples

```
# Create a design object:
data(sbs)
des<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,
  fpc=~fpc)

# Compute some statistics and ask the corresponding estimator kind:
stat<-svystatTM(des,~emp.num)
stat
estimator.kind(stat,des)

stat<-svystatTM(des,~emp.num,estimator="Mean")
stat
estimator.kind(stat,des)

stat<-svystatTM(des,~emp.num+emp.c1)
stat
estimator.kind(stat,des)

stat<-svystatR(des,num=~va.imp2,den=~emp.num,by=~region)
stat
estimator.kind(stat,des)

stat<-svystatQ(des,y=~va.imp2,ties="rounded")
stat
estimator.kind(stat,des)
```



```

# Using protean function svystat to get many statistics in a single shot:
## ungrouped summary statistics:
stat<-svystat(des,kind="R",num=~va.imp2,den=~emp.num,by=~emp.cl:nace.macro,
             combo=2,forGVF=FALSE)
stat
estimator.kind(stat,des)

## grouped summary statistics:
stat<-svystat(des,kind="R",num=~va.imp2,den=~emp.num,by=~emp.cl:nace.macro,
             group=~region,forGVF=FALSE)
stat
estimator.kind(stat,des)

# Behaviour with dummy variables:
## 1. convenience variable 'ent' (whose values are always 1, so that its
#   estimated total actually estimates how many enterprises are there in the
#   target population)
class(des$variables$ent)
range(des$variables$ent)
# The estimated total is correctly recognized as a count
stat<-svystatTM(des,~ent)
stat
estimator.kind(stat,des)

## 2. an actual dummy variable (built on the fly) which indicates if the
#   enterprise has more than 29 employees or not:
des<-des.addvars(des,emp.gt.29=as.numeric(emp.num > 29))
class(des$variables$emp.gt.29)
range(des$variables$emp.gt.29)
# The estimated total is correctly recognized as an absolute frequency
stat<-svystatTM(des,~emp.gt.29)
stat
estimator.kind(stat,des)
# The estimated mean is correctly recognized as a relative frequency
stat<-svystatTM(des,~emp.gt.29,estimator="Mean")
stat
estimator.kind(stat,des)

```

ext.calibrated

Make ReGenesees Digest Externally Calibrated Weights

Description

Enables **ReGenesees** to provide correct variance estimates of (functions of) calibration estimators, even if the survey weights have not been calibrated by **ReGenesees**.

Usage

```

ext.calibrated(data, ids, strata = NULL, weights,
              fpc = NULL, self.rep.str = NULL, check.data = TRUE,
              weights.cal, calmodel, partition = FALSE, sigma2 = NULL)

```

Arguments

data	The same as in function e.svydesign .
ids	The same as in function e.svydesign .
strata	The same as in function e.svydesign .
weights	The same as in function e.svydesign .
fpc	The same as in function e.svydesign .
self.rep.str	The same as in function e.svydesign .
check.data	The same as in function e.svydesign .
weights.cal	Formula identifying the externally calibrated weights.
calmodel	The same as in function e.calibrate .
partition	The same as in function e.calibrate .
sigma2	The same as in function e.calibrate .

Details

Owing to **ReGenesees**'s ability to provide proper variance estimates for (complex functions of) calibration estimators, some users may be tempted to exploit **ReGenesees** in the estimation phase *even if* they did *not* use **ReGenesees** for calibration.

This result *cannot* be achieved naively, by simply passing to **ReGenesees** function [e.svydesign](#) the survey data and supplying the externally calibrated weights through its weights argument.

Indeed, variance estimation methods of **ReGenesees**'s summary statistics functions ([svystatTM](#), [svystatR](#), [svystatS](#), [svystatSR](#), [svystatB](#), [svystatQ](#), [svystatL](#) and [svystat](#)) are dispatched according to the class of the input design object:

1. If the design object is un-calibrated (i.e. its class is 'analytic'), variance formulas are appropriate to Horvitz-Thompson estimators (and functions of them).
2. If the design object is calibrated (i.e. its class is 'cal.analytic'), variance formulas are appropriate to Calibration estimators (and functions of them).

Therefore, the naive approach of passing the externally calibrated weights `weights.cal` to [e.svydesign](#) as if they were initial or design weights cannot succeed, since it would result in HT-like variance estimates, leading generally to *variance overestimation* (with bigger upward bias for variables that are better explained by the calibration model).

Function `ext.calibrated` has been designed exactly to avoid the aforementioned pitfalls and to allow **ReGenesees** provide correct variance estimates of (functions of) calibration estimators, even if the survey weights have been calibrated externally by other software.

Argument `weights.cal` identifies the externally calibrated weights of the units included in the sample. The data variable referenced by `weights.cal` must be numeric. Currently, only *positive* externally calibrated weights can be handled (see the dedicated section below).

Other arguments to `ext.calibrated` derive either from function [e.svydesign](#) or from function [e.calibrate](#). The former serve the purpose of passing the survey data and the corresponding sampling design metadata, the latter are meant to tell `ext.calibrated` how the externally calibrated weights have been obtained.

Value

An object of class `cal.analytic`, storing the original survey data *plus* all the sampling design and calibration metadata needed for proper variance estimation.

What if externally calibrated weights happen to be negative?

From a methodological perspective, negative calibration weights are legitimate. However, owing to software implementation details whose modification would not be trivial, function `ext.calibrated` is *not* yet able to cope with this case. Note that the problem is actually due to the *external* origin of the negative calibration weights. In fact, **ReGenesees** calibration and estimation facilities are entirely able to cope with possibly negative calibration weights, provided they were computed *internally*.

Note

Exactly as **ReGenesees**'s base functions `e.svydesign` and `e.calibrate` would do, `ext.calibrated` too will wrap inside its return value a local copy of data. As usual, this copy will be stored inside the variables slot of the output list. As usual, again, the calibrated weights will be accessible by using the `weights` function.

Author(s)

Diego Zardetto.

See Also

`e.svydesign` to bind survey data and sampling design metadata, and `e.calibrate` for calibrating survey weights within **ReGenesees**.

Examples

```
# Load data sbs data
data(sbs)

#####
# Simulate an external calibration procedure and compute some benchmark #
# estimates and errors to test function ext.calibrated                  #
#####
# Define a survey design
sbsdes <- e.svydesign(data= sbs, ids= ~id, strata= ~strata, weights= ~weight,
                    fpc= ~fpc)

# Build a template for population totals
pop <- pop.template(data= sbsdes, calmodel= ~y:nace.macro + emp.cl + emp.num - 1,
                   partition= ~dom3)

# Have a look at the template structure
pop.desc(pop)

# Fill the template
pop <- fill.template(universe= sbs.frame, template= pop)

# Calibrate
sbscal <- e.calibrate(design= sbsdes, df.population= pop, calfun= "logit",
                    bounds= c(0.8, 1.3), sigma2= ~ emp.num)

# Compute benchmark estimates and errors (average value added per employee by
# region) to be later compared with those obtained by using ext.calibrated
benchmark <- svystatR(design= sbscal, num= ~va.imp2, den= ~emp.num, by= ~region)
```

benchmark

```
# Extract the 'externally' calibrated weights...
w <- weights(sbscal)

#...and add these 'externally' calibrated weights to the original survey data
sbs.ext <- data.frame(sbs, w.ext = w)

# NOTE: Now sbs.ext is just a data frame, without any knowledge of the
#       calibration metadata formerly stored inside sbscal (i.e. the object
#       calibrated by ReGenesees)

#####
# Let ReGenesees digest the 'externally' calibrated weights, #
# then re-compute benchmark estimates and errors for testing #
#####
# Simply pass survey data along with sampling design and calibration model
# metadata
sbscal.ext <- ext.calibrated(data= sbs.ext, ids= ~id, strata= ~strata,
                             weights= ~weight, fpc = ~fpc,
                             weights.cal= ~w.ext,
                             calmodel= ~y:nace.macro + emp.cl + emp.num - 1,
                             partition= ~dom3, sigma2= ~emp.num)

# Have a look at the output
sbscal.ext

# Now re-compute benchmark estimates and errors by means of new object
# ext.sbscal
test <- svyestatR(design= sbscal.ext, num= ~va.imp2, den= ~emp.num, by= ~region)
test

#####
# Compare benchmark estimates and errors to those derived from #
# ext.calibrated return object                                     #
#####
benchmark
test

# ...and they are identical, as it must be.

# NOTE: All utility tools yield exactly the same results, e.g.
identical(weights(sbscal), weights(sbscal.ext))
identical(g.range(sbscal), g.range(sbscal.ext))

#####
# Show that the naive idea of directly passing the externally calibrated #
# weights to e.svydesign does NOT work properly for variance estimation #
#####
naive <- e.svydesign(data= sbs.ext, ids= ~id, strata= ~strata,
                    weights= ~w.ext, fpc = ~fpc)

# Estimated sampling errors derived by this naive design object...
svyestatR(design= naive, num= ~va.imp2, den= ~emp.num, by= ~region)
```

```
#...do NOT match benchmark values, overestimating them:
benchmark
```

 extractors

Extractor Functions for Variability Statistics

Description

These functions extract standard errors (SE), variances (VAR), coefficients of variation (cv) and design effects (deff) from an object which has been returned by a survey statistic function (e.g. [svystatTM](#), [svystatR](#), [svystatS](#), [svystatSR](#), [svystatB](#), [svystatQ](#), [svystatL](#), [svystat](#), ...).

Usage

```
SE(object, ...)
VAR(object, ...)
cv(object, ...)
deff(object, ...)
```

Arguments

<code>object</code>	An object containing survey statistics.
<code>...</code>	Arguments for future expansion.

Details

With the exception of `deff`, all extractor functions can be used on any object returned by a survey statistic function: the correct answer will be obtained whatever the call that generated the object. For getting the design effect, object must have been built with option `deff = TRUE`.

Value

A data structure (typically inheriting from classes `matrix` or `data.frame`) storing the requested informations.

Note

Package **ReGenesees** provides extensions of methods [coef](#) and [confint](#) (originally from package **stats**) that can be used to extract estimates and confidence intervals respectively.

Author(s)

Diego Zardetto

See Also

Function [coef](#) to extract estimates and function [confint](#) to extract confidence intervals. Estimators of Totals and Means [svystatTM](#), Ratios between Totals [svystatR](#), Shares [svystatS](#), Ratios between Shares [svystatSR](#), Multiple Regression Coefficients [svystatB](#), Quantiles [svystatQ](#), Complex Analytic Functions of Totals and/or Means [svystatL](#), and all of the above [svystat](#).

Examples

```
# Creation of a design object:
data(sbs)
des<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,
  fpc=~fpc)

# Estimation of the average value added at the
# nation level (by default one gets the SE):
VA.avg <- svystatTM(des,~va.imp2,estimator="Mean")
VA.avg

# Extractions of some variance statistics from the
# object above:
## 1) SE
SE(VA.avg)
## 2) CV
cv(VA.avg)
## 3) VAR
VAR(VA.avg)

# Design effects have to be requested in advance,
# i.e. the following invocation produces an error:
## Not run:
deff(VA.avg)

## End(Not run)
# ...while the following works:
VA.avg <- svystatTM(des,~va.imp2,estimator="Mean",deff=TRUE)
deff(VA.avg)

# Further examples:
## extract the statistic:
coef(VA.avg)
## extract the confidence interval at 90%
## confidence level (the default would be 95%):
confint(VA.avg, conf.lev=0.9)
```

fill.template

Fill the Known Totals Template for a Calibration Task

Description

Given a template prepared to store the totals of the auxiliary variables for a specific calibration task, computes the actual values of such totals from a sampling frame.

Usage

```
fill.template(universe, template, mem.frac = 10)
```

Arguments

universe	Data frame containing the complete list of the units belonging to the target population, along with the corresponding values of the auxiliary variables (the sampling frame).
----------	---

template	The template for the calibration task, an object of class <code>pop.totals</code> .
mem.frac	A numeric and non-negative value (the default is 10). It triggers a memory-efficient algorithm when universe is really huge (see ‘Details’ and ‘Performance’).

Details

Recall that a `template` object returned by function `pop.template` has a structure that complies with the standard required by `e.calibrate`, but is *empty*, in the sense that all the known totals it must be able to store are missing (NA). Whenever these totals are available to the user as such, that is in the form of already computed aggregated values (e.g. because they come from an external source, like a Population Census), the **ReGenesees** package cannot automatically fill the template. Stated more explicitly: the user himself has to bear the responsibility of putting the *right values* in the *right slots* of the prepared template data frame. To this end, function `pop.desc` could be very helpful.

A lucky alternative arises when a “*sampling frame*” (that is a data frame containing the complete list of the units belonging to the target population, along with the corresponding values of the auxiliary variables) is available. In such cases, indeed, the `fill.template` function is able to: (i) automatically compute the totals of the auxiliary variables from the universe data frame, (ii) safely arrange and format these values according to the template structure.

Notice that `fill.template` will perform a complete coherence check between universe and template. If this check fails, the program stops and prints an error message: the meaning of the message should help the user diagnose the cause of the problem. Should empty levels be present in any factor variable belonging to universe, they would be dropped.

Argument `mem.frac` (whose value must be numeric and non-negative) triggers a memory-efficient algorithm when universe is *really huge*. The *only* sound reason to ever change the value of this argument from its default (`mem.frac=10`) is that an invocation of `fill.template` caused a memory-failure (i.e. a messages beginning cannot allocate vector of size ...) on your machine. In such a case, *increasing* the value of `mem.frac` (e.g. `mem.frac=20`) will provide a better chance of succeeding (for more details, see ‘Performance’ section below).

Value

An object of class `pop.totals` storing the *actual* values of the population totals for the specified calibration task, ready to be safely passed to `e.calibrate`.

Performance

Real-world calibration tasks (e.g. in the field of Official Statistics) can simultaneously involve hundreds of auxiliary variables and refer to target populations of several million units. In such circumstances, the naive aggregation of the calibration model `matrix` of universe may turn out to be too memory-demanding (at least in ordinary PC environments) and determine a memory-failure error.

The alternative implemented in `fill.template` is to: (i) split universe in chunks, (ii) compute partial sums of auxiliary variables chunk-by-chunk, (iii) update template by adding progressively such partial sums. This alternative is triggered by parameter `mem.frac`, which also implicitly controls the number of chunks. The function estimates the memory that would be used to store the *full* model `matrix` of universe and compares it to the maximum memory allocable on the machine (as returned by `memory.limit`): if the resulting ratio is bigger than $1/\text{mem.frac}$, the memory-efficient algorithm starts; the number of chunks in which universe will then be split is determined in such a way that the memory needed to store the model `matrix` of *each* chunk does not exceed a fraction $1/\text{mem.frac}$ of the maximum allocable memory.

Whenever `fill.template` switches to the memory-efficient "chunking" algorithm, a warning message will signal it and will specify as well the number of chunks that are being processed.

Author(s)

Diego Zardetto

See Also

[e.calibrate](#) for calibrating weights, [pop.template](#) for the definition of the class `pop.totals` and to build a "template" data frame for known population totals, [pop.desc](#) to provide a natural language description of the template structure, and [%into%](#) for the compression operator for nested factors.

Examples

```
# Load sbs data:
data(sbs)

# Build a design object:
sbsdes<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,fpc=~fpc)

#####
# A simple example first. #
#####

# Suppose you want to calibrate on the enterprise counts inside areas
# 1) Build the population totals template:
pop<-pop.template(sbsdes, calmodel=~area-1)

# Note: given the dimension of the obtained template...
dim(pop)

# ...the number of known totals to be stored is 24 (one for each area).

# 2) Use the fill.template function to (i) automatically compute
#     such 24 totals from the universe (sbs.frame) and (ii) safely fill
#     the template:
pop<-fill.template(universe=sbs.frame,template=pop)
pop

# 3) Lastly calibrate, e.g. with the unbounded linear distance and
#     heteroskedastic effects proportional to emp.num:
sbscal<-e.calibrate(sbsdes,pop,sigma2=~emp.num,bounds=c(-Inf,Inf))

#####
# A more involved (two-sided) example. #
#####

# Now suppose you have to perform a calibration process which
# exploits as auxiliary information the total number of employees (emp.num)
# and enterprises (ent) inside the domains obtained by:
# i) crossing nace2 and region;
# ii) crossing emp.cl, region and nace.macro;
```



```

# Due to the fact that nace2 is nested into nace.macro,
# the calibration model can be efficiently factorized as follows:
## 1) Add to the design object and universe the new compressed
#   factor variable involving nested factors, namely:
sbsdes<-des.addvars(sbsdes,nace2.in.nace.macro=nace2 %into% nace.macro)
sbs.frame$nace2.in.nace.macro<-sbs.frame$nace2 %into% sbs.frame$nace.macro

# 2) Build the template exploiting the new variable:
pop<-pop.template(sbsdes,
  calmodel=~(emp.num+ent):(nace2.in.nace.macro + emp.cl)-1,
  partition=~nace.macro:region)

# Note: given the dimension of the obtained template...
dim(pop)

# ...the number of known totals to be stored is 792.

# 3) Use the fill.template function to (i) automatically compute
#   such 792 totals from the universe (sbs.frame) and (ii) safely fill
#   the template:
pop<-fill.template(universe=sbs.frame,template=pop)

# Note: out of the 792 known totals in pop, only non-zero entries are actually
# relevant

# 4) Lastly calibrate, e.g. with the unbounded linear distance and
#   heteroskedastic effects proportional to emp.num:
sbscal<-e.calibrate(sbsdes,pop,sigma2=~emp.num,bounds=c(-Inf,Inf))

# Note: a global calibration task would have led to identical calibrated
# weights, but in a more memory-hungry and time-consuming way, as you can
# verify:
# 1) Build template:
pop.g<-pop.template(sbsdes,
  calmodel=~(emp.num+ent):(nace2:region + emp.cl:nace.macro:region)-1)
dim(pop.g)

# 2) Fill template:
pop.g <- fill.template(sbs.frame,pop.g)

# 3) Calibrate globally:
## Not run:
sbscal.g<-e.calibrate(sbsdes,pop.g,sigma2=~emp.num,bounds=c(-1E6,1E6))

# 4) Compare calibrated weights (factorized vs. global solution):
range(weights(sbscal)/weights(sbscal.g))

# ... they are equal.

## End(Not run)

#####
# Just a single example of the memory-efficient algorithm #
# triggered by argument 'mem.frac'.                        #
#####
## Not run:

```

```
# First artificially increase the size of the sampling frame (e.g.
# up to 5 million rows):
sbs.frame.HUGE<-sbs.frame[sample(1:nrow(sbs.frame),5000000,rep=TRUE),]
dim(sbs.frame.HUGE)

# Build the template:
pop<-pop.template(sbsdes,
  calmodel=~(emp.num+ent):(nace2.in.nace.macro + emp.cl)-1,
  partition=~nace.macro:region)
dim(pop)

# Fill the template by using the HUGE universe:
pop<-fill.template(universe=sbs.frame.HUGE,template=pop)

## End(Not run)
```

find.lon.strata

Find Strata with Lonely PSUs

Description

Checks whether a stratified design object contains lonely PSUs: if this is the case, returns the lonely strata levels.

Usage

```
find.lon.strata(design)
```

Arguments

design	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
--------	--

Details

Lonely PSUs (i.e. PSUs which are alone inside a not self-representing stratum) are a concern from the viewpoint of variance estimation. The suggested **ReGenesees** facility to handle the lonely PSUs problem is the strata aggregation technique provided in function `collapse.strata` (for further alternatives, see also `ReGenesees.options`).

Function `find.lon.strata` (originally a private function intended to be called only by `collapse.strata`) is a simple diagnostic tool whose purpose is to identify the levels of the strata containing lonely PSUs (lonely strata for short).

Value

The lonely strata levels, if design actually contains lonely PSUs; `invisible(NULL)` otherwise.

Author(s)

Diego Zardetto

See Also

[collapse.strata](#) for the suggested way of handling lonely PSUs, [ReGenesees.options](#) for a different way to face the same problem (namely by setting variance estimation options), and [fpcdat](#) for useful data examples.

Examples

```
# Load sbs data:
data(fpcdat)

# A negative example first:

# Build a design object:
fpcdes<-e.svydesign(data=fpcdat,ids=~psu+ssu,strata=~stratum,weights=~w,
  fpc=~fpc1+fpc2)
fpcdes

# Find lonely strata:
find.lon.strata(fpcdes)

# Recall that the difference between certainty PSUs (those sampled with
# probability 1, contained inside self-representing strata) and lonely PSUs
# rests on the fpc information passed to e.svydesign, e.g.:

# Build a new design object with the same data, now IGNORING fpcs:
fpcdes.nofpc<-e.svydesign(data=fpcdat,ids=~psu+ssu,strata=~stratum,
  weights=~w)
fpcdes.nofpc

# Find lonely strata:
find.lon.strata(fpcdes.nofpc)

# A trivial check: collapsing strata eliminates lonely PSUs

# Apply the collapse strata technique:
fpcdes.nofpc.clps<-collapse.strata(fpcdes.nofpc)
fpcdes.nofpc.clps
clps.strata.status

# Find lonely strata:
find.lon.strata(fpcdes.nofpc.clps)

# ...as it must be.
```

Description

This function fits one or more GVF models to a set of survey statistics.

Usage

```
fit.gvf(gvf.input, model = NULL, weights = NULL)

## S3 method for class 'gvf.fit'
print(x, digits = max(3L, getOption("digits") - 3L), ...)
## S3 method for class 'gvf.fits'
print(x, digits = max(3L, getOption("digits") - 3L), ...)
## S3 method for class 'gvf.fit.gr'
print(x, digits = max(3L, getOption("digits") - 3L), ...)
## S3 method for class 'gvf.fits.gr'
print(x, digits = max(3L, getOption("digits") - 3L), ...)

## S3 method for class 'gvf.fits'
x[...]
## S3 method for class 'gvf.fits'
x[[...]]

## S3 method for class 'gvf.fit'
summary(object, correlation = FALSE, symbolic.cor = FALSE, ...)
## S3 method for class 'gvf.fits'
summary(object, correlation = FALSE, symbolic.cor = FALSE, ...)
## S3 method for class 'gvf.fit.gr'
summary(object, correlation = FALSE, symbolic.cor = FALSE, ...)
## S3 method for class 'gvf.fits.gr'
summary(object, correlation = FALSE, symbolic.cor = FALSE, ...)
```

Arguments

<code>gvf.input</code>	An object of class <code>gvf.input</code> (or <code>gvf.input.gr</code>), containing the data to fit.
<code>model</code>	The GVF model(s) to be fitted (see ‘Details’). <code>NULL</code> (the default) requires to fit <i>all</i> the registered GVF models currently available in GVF.db .
<code>weights</code>	Formula specifying the weights to be used for fitting (via weighted least squares), if any. <code>NULL</code> (the default) means that ordinary least squares will be used. See also ‘Details’.
<code>x</code>	An object of class <code>gvf.fits</code> , storing fitted GVF models.
<code>digits</code>	Minimal number of significant digits, see print.default .
<code>object</code>	Any output of <code>fit.gvf</code> , storing one (more than one) fitted GVF model(s).
<code>correlation</code>	Should the correlation matrix of the estimated parameters be returned and printed? Logical, with default <code>FALSE</code> .
<code>symbolic.cor</code>	Should the correlations be printed in symbolic form (see symnum) rather than as numbers. Logical, with default <code>FALSE</code> .
<code>...</code>	Further arguments passed to or from other methods.

Details

Function `fit.gvf` fits one or more GVF models to a set of survey statistics. The rationale for fitting multiple models to the same data is primarily for comparison purposes: the user is expected to eventually choose his preferred model, in order to obtain sampling errors predictions.

Argument `gvf.input` specifies the set of (pre computed) estimates and errors to which GVF models are to be fitted, as prepared by functions [gvf.input](#) and/or [svystat](#).

One or more GVF models can be fitted *simultaneously* to the same data, depending on the way argument `model` is passed.

Argument `model` can be either:

- (1) NULL (the default) meaning *all* the registered models currently available in [GVF.db](#);
- (2) any sub-vector of `GVF.db$Model.id`, i.e. an integer vector identifying an arbitrary selection of registered models;
- (3) an arbitrary (single) formula, i.e. any custom, user-defined GVF model.

When `model` is passed via options (1) or (2), function `fit.gvf` can take advantage of any additional information available inside `GVF.db`, e.g. to warn the user in case a GVF model is not deemed to be appropriate for the kind of estimates contained into `gvf.input` (see ‘Examples’).

Argument `weights` enables fitting the specified GVF model(s) via weighted least squares. By default `weights = NULL` and ordinary least squares are used. The weights must be passed by a formula referencing variables belonging to `gvf.input`. For instance, to weight observations according to reciprocals of squared CVs, one can use `weights = ~I(CV^-2)`.

Value

An object containing one or more fitted GVF models, depending on the way argument `model` was passed.

Let’s first focus on input objects of class `gvf.input`.

If `model` specifies a single GVF model, the output object will be of class `gvf.fit` and inherit from class [lm](#).

If `model` specifies many GVF models, the output object will be of class `gvf.fits` and inherit from class [list](#). Hence, it will be possible to subset `gvf.fits` objects via methods `[]` and `[[`. Note, moreover, that each component (in the sense of class [list](#)) of a `gvf.fits` object will be of class `gvf.fit`.

When, instead, the input object has class `gvf.input.gr`, i.e. it stores “grouped” estimates and errors, model fitting is performed *separately* for different groups. Therefore, applying `fit.gvf` *always* results in *many* fitted GVF models.

If `model` specifies a single GVF model, the output object will be of class `gvf.fit.gr` and inherit from class [list](#). Each slot of the list will contain the same GVF model fitted to a specific group.

If `model` specifies many GVF models, the output object will be of class `gvf.fits.gr` and again inherit from class [list](#). Each slot of the list will now contain *a second list* storing different GVF models fitted to a specific group.

Author(s)

Diego Zardetto

See Also

[estimator.kind](#) to assess what kind of estimates are stored inside a survey statistic object, [GVF.db](#) to manage **ReGenesees** archive of registered GVF models, [gvf.input](#) and [svystat](#) to prepare the input for GVF model fitting, [fit.gvf](#) to fit GVF models, [plot.gvf.fit](#) to get diagnostic plots for fitted GVF models, [drop.gvf.points](#) to drop alleged outliers from a fitted GVF model and simultaneously refit it, and [predictCV](#) to predict CV values via fitted GVF models.

Examples

```
# Load example data:
data(AF.gvf)

# Now we have at our disposal a set of estimates and errors
# of Absolute Frequencies:
str(ee.AF)

# And the available registered GVF models are listed below:
GVF.db

#####
# How to specify the GVF model(s) to fit? #
#####

## (A) How to specify a *single* GVF model ##

#### (A.1) Select one registered model using its 'Model.id' as reported in
####       the GVF.db archive
# Let's fit, for instance, the GVF model with Model.id = 1:
m <- fit.gvf(ee.AF, model = 1)

# Inspect the result:
class(m)
m
summary(m)

# Now let's fit GVF model with Model.id = 4
m <- fit.gvf(ee.AF, model = 4)
# Beware of the NOTE reported when printing or summarizing this fitted model:
m
summary(m)

#### (A.2) Specify the GVF model to fit by providing its formula directly, e.g.
####       because it is not available in GVF.db (yet):
m <- fit.gvf(ee.AF, model = CV ~ I(1/Y^2) + I(1/Y) + Y + I(Y^2))
m
summary(m)

## (B) How to specify a *many* GVF models simultaneously ##

#### (B.1) Use a subset of column 'Model.id' of GVF.db
# Let's, for instance, fit all the available GVF models which are appropriate
# to Frequencies, as reported in column 'Estimator.kind' of GVF.db
mm <- fit.gvf(ee.AF, model = 1:3)

# Inspect the result:
class(mm)
length(mm)
mm
summary(mm)

# Note that you can subset the output fitted models as a list:
```

```

mm.31 <- mm[c(3,1)]
class(mm.31)
mm.31

# and:
mm.2 <- mm[[2]]
class(mm.2)
mm.2

#### (B.2) Not specifying any GVF model, or specifying model = NULL, causes
####      *all* the available models in GVF.db to be fitted simultaneously:
mm <- fit.gvf(ee.AF)

# Inspect the result:
class(mm)
length(mm)
mm
summary(mm)

#####
# How to fit GVF model(s) via *weighted* least squares? #
#####
# Weights can be specified by a formula. Of course, the 'weights' formula must
# reference variables belonging to gvf.input.

# Let's use the built-in GVF model with Model.id = 1 and weight observations
# according to reciprocals of squared CVs:
mw <- fit.gvf(ee.AF, model = 1, weights = ~I(CV^-2))
mw

# Compute ordinary least squares fit:
m <- fit.gvf(ee.AF, model = 1)
m

# Compare the results:
summary(mw)
summary(m)

#####
# Fitting GVF model(s) to "grouped" estimates and errors: a quick ride. #
#####
# Recall we have at our disposal the following survey design object
# defined on household data:
exdes

# Now use function svystat to prepare "grouped" estimates and errors
# of counts to be fitted separately (here groups are regions):
ee.g <- svystat(exdes, y=~ind, by=~age5c:marstat:sex, combo=3, group=~regcod)
class(ee.g)
ee.g

## Fit a *single* registered GVF model separately inside groups ##
m.g <- fit.gvf(ee.g, model = 1)

```

```

# Inspect the result:
class(m.g)
length(m.g)
m.g
summary(m.g)

# Can subset the result as a list, e.g. to get the fitted model of region '7':
m.g7 <- m.g[["7"]]
class(m.g7)
summary(m.g7)

## Fit *many* registered GVF models separately inside groups ##
mm.g <- fit.gvf(ee.g, model = 1:3)

# Inspect the result:
class(mm.g)
length(mm.g)
mm.g
summary(mm.g)

# Still can subset the result as a list, but now each component is a list
# itself. To get the fitted models of region '7', simply:
mm.g7 <- mm.g[["7"]]
class(mm.g7)
summary(mm.g7)

# And to isolate GVF fitted model number 2 for region '7', simply:
mm.g7.2 <- mm.g7[[2]]
class(mm.g7.2)
summary(mm.g7.2)

```

fpcdat

A Small But Not Trivial Artificial Sample Data Set

Description

A small dataset mimicking sample data selected with a 2-stage, stratified, cluster sampling without replacement. Allows to run R code contained in the ‘Examples’ section of the **ReGenesees** package help pages.

Usage

```
data(fpcdat)
```

Format

A data frame with 28 observations on the following 12 variables.

psu Identifier of the primary sampling units, numeric

ssu Identifier of the second stage sampling units, numeric

stratum Stratification Variable, a factor with 5 levels: S.1, S.2, S.3, S.4, S.5

sr Strata type, integer with values 0 (NSR strata) and 1 (SR strata)
 fpc1 First stage finite population corrections, given as population sizes (in terms of psu clusters) inside strata, numeric
 fpc2 Second stage finite population corrections, given as population sizes (in terms of ssu clusters) inside the corresponding sampled psu, numeric
 x A numeric variable
 y A numeric variable
 dom1 A variable defining unplanned estimation domains, factor with 3 levels: A, B, C
 dom2 A variable defining unplanned estimation domains, factor with 6 levels: a, b, c, d, e, f
 w Direct weights, numeric
 z A numeric variable
 pl.domain A variable defining planned estimation domains, factor with 3 levels: pd.1, pd.2, pd.3

Details

Though very small, the fpcdat dataset concentrates a lot of interesting features. The sampling design is a complex one, with both self-representing (SR) and not-self-representing (NSR) strata. Sampling fractions are deliberately not negligible, in order to stress the effects of finite population corrections on variance estimation. Moreover, being the observations so few, performing computations on the fpcdat dataset allows to check and understand easily all the effects of setting/changing the global variance estimation options of the **ReGenesees** package (see e.g. [ReGenesees.options](#)).

See Also

[ReGenesees.options](#) for setting/changing variance estimation options.

Examples

```
data(fpcdat)
head(fpcdat)
str(fpcdat)
```

g.range

Range of g-Weights

Description

Computes the range of the ratios between calibrated weights and initial weights (*g-weights*).

Usage

```
g.range(cal.design)
```

Arguments

cal.design Object of class cal.analytic.

Details

This function computes the smallest interval which contains the ratios between calibrated weights and initial weights.

Value

A numeric vector of length 2.

Note

If `cal.design` has undergone k subsequent calibration steps (with $k \geq 2$), the function will return the range of the ratios between the output weights of calibration steps k and $k - 1$.

Author(s)

Diego Zardetto

See Also

[weights](#) to extract the weights from a design object, [e.calibrate](#) for calibrating weights and [bounds.hint](#) to obtain a hint for calibration problems where range restrictions are imposed on the *g-weights*.

Examples

```
# Creation of the object to be calibrated:
data(data.examples)
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
  weights=~weight)

# Calibration (partitioned solution) on the marginal distribution
# of age in 5 classes (age5c) inside provinces (procod)
# (totals in pop06p) with bounds=c(0.5, 1.5):
descal06p<-e.calibrate(design=des,df.population=pop06p,
  calmodel=~age5c-1,partition=~procod,calfun="logit",
  bounds=c(0.5, 1.5),aggregate.stage=2)

# Now let's verify the actual range of the obtained g-weights:
g.range(descal06p)

# which indeed is covered by c(0.5, 1.5), as required.

# Now calibrate once again, this time on the joint distribution of sex
# and marstat (totals in pop03) with the global solution:
descal2<-e.calibrate(design=descal06p,df.population=pop03,
  calmodel=~marstat:sex-1,calfun="linear",bounds=bounds)

# Notice that the print method correctly takes the calibration chain
# into account:
descal2

# The range of the g-weights for the twice calibrated object is:
g.range(descal2)

#... which is equal to:
range(weights(descal2)/weights(descal06p))
```

```
#... and must not be confused with:
range(weights(descal2)/weights(des))
```

get.residuals

Calibration Residuals of Interest Variables

Description

Computes (scaled) residuals of a set of interest variables w.r.t. the calibration model adopted to build a calibrated object.

Usage

```
get.residuals(cal.design, y, scale = c("no", "w", "d", "g"))
```

Arguments

cal.design	Object of class <code>cal.analytic</code> .
y	Formula defining the variables of interest.
scale	character specifying how to scale the residuals, can be one of: 'no' (the default), 'w', 'd', 'g' (see 'Details').

Details

This function has been designed mainly for programmers willing to build upon **ReGenesees**: typical users are not expected to feel much need of it.

The residuals of an interest variable w.r.t. the linear model defined by the auxiliary variables used for calibration play a central role in estimating the variance of Calibration Estimators. Notice that if object `cal.design` has been generated by running a *partitioned* calibration task (see [e.calibrate](#)), the residuals will be correctly computed using the different estimated regression coefficients pertaining to the different domains belonging to the partition.

The mandatory argument `y` behaves exactly the same way as it does in function [svstatTM](#).

The `scale` argument allows to scale the computed residuals by multiplying them by different factors. By default `scale="no"`, that is *unscaled* residuals are returned. Value `"w"` returns the residuals times the calibrated weights; value `"d"` returns the residuals times the initial weights; finally, value `"g"` returns the residuals times the *g-weights* (i.e. the ratios between calibrated and initial weights). Notice that the semantics of argument `scale` are slightly modified when the input object `cal.design` as been obtained by a multi-step calibration procedure (see Section 'Note' below).

Value

A matrix of residuals.

Note

If `cal.design` has undergone k subsequent calibration steps (with $k \geq 1$), the function will return the residuals computed w.r.t. the linear assisting model underlying the *last* (i.e. k -th) calibration step. If $k \geq 2$, the scale parameter will be interpreted as follows:

SCALE	MEANING
"no".....	no scale;
"w".....	last calibration weight (i.e. at step k);
"d".....	second to last calibration weight (i.e. at step $k - 1$);
"g".....	ratio between last and second to last calibration weights.

Author(s)

Diego Zardetto

See Also

[weights](#) to extract the weights from a design object, [e.calibrate](#) for calibrating weights and [g.range](#) to get the range of the *g-weights*.

Examples

```
#####
# Just some checks on the consistency of the numerical results #
# obtained by ReGenesees with well known theoretical properties. #
#####

# Load sbs data:
data(sbs)

# Create a design object to be calibrated:
sbsdes<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,fpc=~fpc)

#####
## Property 1 ##
#####
## If the calibration model has (implicitly or explicitly) an intercept
## the weighted sum of residuals must be zero.

# Suppose you calibrate on enterprise counts inside areas, i.e. a calibration
# model WITH intercept (though implicitly):
# calmodel= ~ area - 1

# First, build and fill the known totals template:
pop<-pop.template(sbsdes, calmodel= ~ area - 1)
pop<-fill.template(pop, universe=sbs.frame)

# Then, calibrate:
sbscal<-e.calibrate(sbsdes, pop)

# Now, get the residuals of any variable (e.g. y and emp.num) scaled with the
# direct weights:
de <- get.residuals(sbscal, ~ y + emp.num, scale="d")

# Lastly, compute the column sums...
```

```

colSums(de)

#...which is (numerically) zero, as it must be.

#####
## Property 2 ##
#####
## If the calibration model does not have (implicitly or explicitly) an
## intercept term the weighted sum of residuals is generally different from zero.

# Suppose you calibrate on employees counts inside areas, i.e. a calibration
# model WITH intercept (though implicitly):
# calmodel= ~ emp.num:area - 1

# First, build and fill the known totals template:
pop<-pop.template(sbsdes, calmodel= ~ emp.num:area - 1)
pop<-fill.template(pop, universe=sbs.frame)

# Then, calibrate:
sbscal<-e.calibrate(sbsdes, pop)

# Now, get the residuals of any variable (e.g. y and region) scaled with the
# direct weights:
de <- get.residuals(sbscal, ~ y + region, scale="d")

# Lastly, compute the column sums...
colSums(de)

#...which is far from zero, as expected.

#####
## Property 3 ##
#####
## In the Taylor linearization approach, estimating the variance of a
## Calibration Estimator amounts to estimating the variance of the HT total
## of its linearized variable (i.e. the g-scaled residual), under the sampling
## design at hand.

# Suppose you calibrate on the total number of employees and enterprises
# inside the domains obtained by:
# i) crossing nace.macro and region;
# ii) crossing emp.cl and region;

# First, build and fill the population totals template:
pop<-pop.template(sbsdes,
  calmodel=~(emp.num+ent):(nace.macro+emp.cl)-1,
  partition=~region)
pop<-fill.template(universe=sbs.frame,template=pop)

# Then, calibrate:
sbscal<-e.calibrate(sbsdes,pop)

# Now, compute the linearized variable of the Calibration Estimator of the
# total of any variable (e.g. va.imp2):
z_va.imp2 <- get.residuals(sbscal, ~ va.imp2, scale="g")

```

```

# Now, treat z_va.imp2 as an ordinary variable and compute the standard error
# of its HT total:
sbsdes<-des.addvars(sbsdes, z_va.imp2 = z_va.imp2)
SE(svystatTM(sbsdes, ~z_va.imp2))

# Lastly, compute directly the standard error of the Calibration Estimator...
SE(svystatTM(sbscal, ~va.imp2))

#...and they are identical, as it must be.

# Obviously the same result would hold for domain estimates (e.g. the total
# of va.imp2 for the "Agriculture" nace.macro).

# Compute the linearized variable of the Calibration Estimator of the domain
# total:
z_va.imp2.Agr <- get.residuals(sbscal, ~ I(va.imp2*(nace.macro=="Agriculture")),
                             scale="g")

# Now, treat z_va.imp2.Agr as an ordinary variable and compute the standard
# error of its HT total:
sbsdes<-des.addvars(sbsdes, z_va.imp2.Agr = z_va.imp2.Agr)
SE(svystatTM(sbsdes, ~z_va.imp2.Agr))

# Lastly, compute directly the standard error of the Calibration Estimator
# by domain...
SE(svystatTM(sbscal, ~va.imp2, ~nace.macro))

#...and the "Agriculture" SEs are identical, as it must be.

```

getBest

Identify the Best Fit GVF Model

Description

Given a set of competing fitted GVF models, this function selects the best model according to a given criterion.

Usage

```

getBest(object,
        criterion = c("R2", "adj.R2", "AIC", "BIC"), ...)

```

Arguments

object	Typically, an object containing <i>many</i> fitted GVF models (i.e. of class <code>gvf.fits</code> or <code>gvf.fits.gr</code>).
criterion	The quality criterion to be used for model selection. Default is R^2 .
...	Further arguments passed to or from other methods.

Details

Given a set of competing fitted GVF models, this function selects the best model according to a given criterion.

Four goodness-of-fit criteria are available: R^2 , adjusted R^2 , AIC, and BIC (see [getR2](#)).

If object is a *set* of GVF models fitted to *grouped* data (i.e. of class `gvf.fits.gr`), the function will return the fitted GVF model with best *average score* in the given criterion *over the groups*.

Value

A single GVF fitted model.

Methodological Warning

Each one of the available criteria has its own specificities and limitations (e.g. it is senseless to use AIC to compare two GVF models with different response variables). It is up to the user to select the measure which is appropriate to his goals.

Author(s)

Diego Zardetto

See Also

[GVF.db](#) to manage **ReGenesees** archive of registered GVF models, [gvf.input](#) and [svystat](#) to prepare the input for GVF model fitting, [fit.gvf](#) to fit GVF models, [plot.gvf.fit](#) to get diagnostic plots for fitted GVF models, [drop.gvf.points](#) to drop alleged outliers from a fitted GVF model and simultaneously refit it, and [predictCV](#) to predict CV values via fitted GVF models.

Examples

```
# Load example data:
data(AF.gvf)

# Inspect available estimates and errors of counts:
str(ee.AF)

# List available registered GVF models:
GVF.db

## (A) A *a set* of GVF models fitted to the same data ##
# Fit example data to all registered GVF models:
mm <- fit.gvf(ee.AF)
summary(mm)

# Get the best model according to adjusted R^2:
mm.best <- getBest(mm, criterion = "adj.R2")
mm.best

# NOTE: The *first* model has been selected. A thorough model comparison
#       by means of diagnostic plots would have led to the same result:
plot(mm, 1:3)
```

```
## (B) a *set of* GVF models fitted to *grouped* data ##
# We have at our disposal the following survey design object on household data:
exdes

# Use function svystat to prepare *grouped* estimates and errors of counts
# to be fitted separately (here groups are regions):
ee.g <- svystat(exdes, y=~ind, by=~age5c:marstat:sex, combo=3, group=~regcod)
str(ee.g)

# Fit all registered GVF model number separately inside groups:
mm.g <- fit.gvf(ee.g)
summary(mm.g)

# Get the best model according to R^2:
mm.g.best <- getBest(mm.g)
mm.g.best

# NOTE: Again, the *first* model has been selected. A thorough model comparison
#       by means of diagnostic plots would have led to the same result:
plot(mm.g, 1:3)
```

getR2

Quality Measures on Fitted GVF Models

Description

These functions extract goodness-of-fit measures from fitted GVF models.

Usage

```
getR2(object, adjusted = FALSE, ...)
```

```
## S3 method for class 'gvf.fits'
```

```
AIC(object, ...)
```

```
## S3 method for class 'gvf.fits'
```

```
BIC(object, ...)
```

Arguments

object	An object containing one or more fitted GVF models.
adjusted	Should the <i>adjusted</i> R ² be computed? The default is FALSE
...	Further arguments passed to or from other methods.

Details

These functions compute three goodness-of-fit measures on fitted GVF models: R², [AIC](#), and [BIC](#). Such measures can help compare the relative quality of competing GVF models, hence facilitating model selection (see also function [getBest](#)).

Though object can also be a *single* fitted GVF model, these functions are principally meant to compare *different* GVF models fitted to the same data (i.e. the same estimates and errors).

To request the *adjusted* R², use function getR2 and specify adjusted = TRUE.

Value

If object is a single GVF model (class `gvf.fit`), the requested quality measure.

If object is a set of GVF models fitted to the same data (class `gvf.fits`), a vector whose elements store the requested quality measure for each GVF model.

If object is a single GVF model fitted to "grouped" data (class `gvf.fit.gr`), a list whose components store the requested quality measure for the corresponding groups.

If object is a set of GVF models fitted to "grouped" data (class `gvf.fits.gr`), a list whose components store vectors whose elements report the requested quality measure for each GVF model of each group.

Methodological Warning

Each one of the provided quality measures has its own specificities and limitations (e.g. it is senseless to use AIC to compare two GVF models with different response variables). It is up to the user to select the measure which is appropriate to his goals.

Author(s)

Diego Zardetto

See Also

[GVF.db](#) to manage **ReGenesees** archive of registered GVF models, [gvf.input](#) and [svystat](#) to prepare the input for GVF model fitting, [fit.gvf](#) to fit GVF models, [plot.gvf.fit](#) to get diagnostic plots for fitted GVF models, [drop.gvf.points](#) to drop alleged outliers from a fitted GVF model and simultaneously refit it, and [predictCV](#) to predict CV values via fitted GVF models.

Examples

```
# Load example data:
data(AF.gvf)

# Inspect available estimates and errors of counts:
str(ee.AF)

# List available registered GVF models:
GVF.db

## (A) A *single* fitted GVF model ##
# Fit example data to registered GVF model number one:
m <- fit.gvf(ee.AF, 1)

# Compute some goodness-of-fit measures:
getR2(m)
AIC(m)

## (B) A *a set* of GVF models fitted to the same data ##
# Fit example data to all registered GVF models:
mm <- fit.gvf(ee.AF)

# Compute some goodness-of-fit measures:
getR2(mm, adjusted = TRUE)
BIC(mm)
```

```
## (C) a *single* GVF model fitted to *grouped* data ##
# We have at our disposal the following survey design object on household data:
exdes

# Use function svstat to prepare *grouped* estimates and errors of counts
# to be fitted separately (here groups are regions):
ee.g <- svstat(exdes, y=~ind, by=~age5c:marstat:sex, combo=3, group=~regcod)
str(ee.g)

# Fit registered GVF model number one separately inside groups:
m.g <- fit.gvf(ee.g, 1)

# Compute some goodness-of-fit measures:
getR2(mm)
AIC(mm)

## (D) a *set of* GVF models fitted to *grouped* data ##
# Fit all registered GVF model number separately inside groups:
mm.g <- fit.gvf(ee.g)

# Compute some goodness-of-fit measures:
getR2(mm.g, adjusted = TRUE)
BIC(mm.g)
```

GVF.db

Archive of Registered GVF Models

Description

GVF.db is the archive of *registered* (i.e. built-in and/or user-defined) Generalized Variance Functions models supported by **ReGenesees**. Special accessor functions allow to customize, maintain, extend, update, save and reset such archive.

Usage

GVF.db

GVF.db\$insert(GVF.model, Estimator.kind = NA, Resp.to.CV = NA, verbose = TRUE)

GVF.db\$delete(Model.id, verbose = TRUE)

GVF.db\$get(verbose = TRUE)

GVF.db\$assign(value, verbose = TRUE)

GVF.db\$reset(verbose = TRUE)

Arguments

GVF.model	A GVF model, expressed as a formula object or as a character string (see ‘Details’).
-----------	--

<code>Estimator.kind</code>	Character string identifying the kind of estimators for which the GVF model is deemed to be appropriate (see ‘Details’).
<code>Resp.to.CV</code>	Character string representing the function which maps the response of the GVF model (namely: variable ‘resp’) to the coefficient of variation (namely: variable ‘CV’), see ‘Details’.
<code>Model.id</code>	Unique integer key identifying the GVF model.
<code>value</code>	An exported copy of <code>GVF.db</code> , as returned by <code>GVF.db\$get()</code> .
<code>verbose</code>	Enables printing of a summary description of the result (the default is <code>TRUE</code>).

Format

Each row of the `GVF.db` data frame represents a registered GVF model, with relevant information on the following 4 variables:

`Model.id` A unique integer key identifying the GVF model, integer.

`GVF.model` A character string specifying the GVF model formula, character. See also ‘Details’.

`Estimator.kind` A character string identifying the kind of estimators for which the GVF model is deemed to be appropriate, character. See also ‘Details’.

`Resp.to.CV` A character string which represents the function mapping the response of the GVF model (namely: variable ‘resp’) to the coefficient of variation (namely: variable ‘CV’), character. See also ‘Details’.

Details

`GVF.db` stores information about Generalized Variance Functions models supported by **ReGenesees**. When starting a new work session with **ReGenesees**, `GVF.db` contains few built-in GVF models (currently 5, see sections ‘Source’ and ‘Examples’). The content of `GVF.db` can be customized by means of special accessor functions:

ACCESSOR FUNCTION	PURPOSE
<code>GVF.db\$insert</code>	Register a new GVF model by adding a new row to the <code>GVF.db</code> archive
<code>GVF.db\$delete</code>	Unregister a GVF model by deleting the corresponding row from <code>GVF.db</code>
<code>GVF.db\$get</code>	Get the current version of <code>GVF.db</code> (e.g. to copy/save a customized archive for later usage)
<code>GVF.db\$assign</code>	Overwrite the current version of <code>GVF.db</code> (e.g. to use a customized archive which was exported in a previous ReGenesees session)
<code>GVF.db\$reset</code>	Reset <code>GVF.db</code> to its default version (i.e. the one with built-in GVF models only)

Information about registered GVF models stored inside `GVF.db` will be accessed and used by **ReGenesees** Generalized Variance Functions facilities, e.g. functions `fit.gvf` or `predictCV`.

`GVF.db$insert()`

Function `GVF.db$insert` has just a single mandatory argument: `GVF.model`. This can be either a two-sided formula or a character string which would be transformed into a (well formed) two-sided formula by function `as.formula`.

The `GVF.model` formula to be inserted into `GVF.db` must be *new* (i.e. not already present into the archive) and can involve only variables contained inside `gvf.input` objects, namely:

- (1) 'Y'
- (2) 'SE'
- (3) 'CV'
- (4) 'VAR'
- (5) 'DEFF'

Moreover, since GVF models are intended to model variances in terms of estimates, the response term of `GVF.model` must involve some of 'SE', 'CV', 'VAR', and the linear predictor must involve 'Y'.

Optional argument `Estimator.kind` can be used to specify the kind of estimators for which the `GVF.model` is deemed to be appropriate. There are currently only 11 valid values for `Estimator.kind`, namely:

- (1) 'Total'
- (2) 'Mean'
- (3) 'Frequency'
- (4) 'Absolute Frequency'
- (5) 'Relative Frequency'
- (6) 'Ratio'
- (7) 'Share'
- (8) 'Share Ratio'
- (9) 'Regression Coefficient'
- (10) 'Quantile'
- (11) 'Complex Estimator'

Note that category 'Frequency' has to be understood as an aggregation of categories 'Absolute Frequency' and 'Relative Frequency', thus being appropriate for GVF models which are deemed to work well for estimators of *both* kind of frequencies.

One of the primary motivations for building and fitting a GVF model is to exploit the fitted model to *predict* the sampling error associated to a given estimate, instead of having to *compute* directly an estimate of such sampling error. Optional argument `Resp.to.CV` is relevant to that scope.

Indeed, different GVF models can actually specify as response term (call it 'resp' for definiteness) different functions of variables 'SE', 'CV', and 'VAR', but **ReGenesees** will always adopt variable 'CV' as a *pivot*. Thus, when registering a new GVF model, the user can provide via argument `Resp.to.CV` the function which transforms the response of the model, 'resp', into the pivot measure of variability, 'CV'. A look to the default content of `GVF.db` should make the latter statement clear (see 'Examples').

Note that while `Resp.to.CV` is passed as a character string, that string is expected to represent a well-formed mathematical expression (otherwise function `predictCV` would not work). Moreover, only variables 'resp' and 'Y' are allowed to appear inside `Resp.to.CV` (which is enough, since 'VAR' and 'SE' can be expressed in terms of 'CV' and 'Y').

If the user does not specify `Resp.to.CV` when registering a new GVF model, he will be not able to use function `predictCV` for predicting CV values based on the fitted GVF model.

Lastly, note that the `Model.id` of a newly inserted GVF model will automatically be set, by adding 1 to the previous maximum of `Model.id`.

GVF.db\$delete()

Function `GVF.db$delete` has just a single mandatory argument: `Model.id`. It must match the integer key of the (already existing) GVF model you want to drop from `GVF.db`.

Note that, after deleting a GVF model from `GVF.db`, values of column `Model.id` will be automatically renumbered, so as to range always from 1 to `nrow(GVF.db)`.

GVF.db\$get()

Function `GVF.db$get` has no mandatory arguments. When invoked, the function returns the *current* content of `GVF.db`, so that it can be assigned and saved/exported for later usage (see ‘Examples’). Should the *current* content of `GVF.db` happen to be empty, the function would inform the user and return `NULL`. The return value of `GVF.db$get` has class `"GVF.db_exported"`, and inherits from class `"data.frame"`.

GVF.db\$assign()

Function `GVF.db$assign` has just a single mandatory argument: `value`. The object passed to argument `value` can only be a previously exported copy of `GVF.db`, i.e. an object of class `GVF.db_exported`. The function overwrites the *current* version of `GVF.db` with `value`. As a result, after invoking `GVF.db$assign`, the content of `GVF.db` is `value`.

GVF.db\$reset()

Function `GVF.db$reset` has no mandatory arguments and simply restores the default version of `GVF.db` (i.e. the one containing built-in GVF models only).

Author(s)

Diego Zardetto

Source

Built-in GVF models for frequencies (i.e. those with `Model.id` 1, 2, and 3) are discussed in Chapter 7 of [Wolter 07], along with their theoretical justification. Built-in GVF models for totals (i.e. those with `Model.id` 4, and 5) lack a rigorous justification, but have sometimes been used successfully on a purely empirical basis. For instance, Istat surveys on structural business statistics adopted models of that kind to summarize standard errors in publications and to allow their approximate evaluation on a custom basis.

References

Wolter, K.M. (2007) *"Introduction to Variance Estimation"*, Second Edition, Springer-Verlag, New York.

See Also

[estimator.kind](#) to assess what kind of estimates are stored inside a survey statistic object, [gvf.input](#) and [svyestat](#) to prepare the input for GVF model fitting, [fit.gvf](#) to fit GVF models, [plot.gvf.fit](#) to get diagnostic plots for fitted GVF models, [drop.gvf.points](#) to drop alleged outliers from a fitted GVF model and simultaneously refit it, and [predictCV](#) to predict CV values via fitted GVF models.

Examples

```
# Print the current content of GVF.db (invoking
# print(GVF.db) would do the same):
GVF.db

# Inspect the structure of the GVF.db data frame:
data.class(GVF.db)
str(GVF.db)
dim(GVF.db)
nrow(GVF.db)

#####
# Accessor functions #
#####

# Delete the 3rd model:
GVF.db$delete(3)
# Print GVF.db (note that Model.id has been renumbered,
# so as to range always from 1 to nrow(GVF.db))
GVF.db

# Now delete the 1st model:
GVF.db$delete(1)
GVF.db

# Reset GVF.db to its default values:
GVF.db$reset()
GVF.db

# Insert a new tentative GVF model for Totals:
GVF.db$insert(CV ~ I(1/Y^2) + I(1/Y) + Y + I(Y^2), "Total", "resp")
GVF.db
# (notice that invoking GVF.db$insert() with first argument of type character,
# i.e. GVF.model="CV~I(1/Y^2)+I(1/Y)+Y+I(Y^2)", would have obtained exactly the
# same result)

# Now suppose you have somehow validated your newly added model,
# and you want to save your current, enhanced GVF.db in order to
# be able to use it later in a subsequent ReGenesees session.
### This can be achieved as follows:
### START
# 1. You must first get a copy of it, by using accessor function
#   GVF.db$get:
myGVF.db <- GVF.db$get()
myGVF.db
data.class(myGVF.db)

# 2. Then, you must save the copy to a .RData workspace, in order
#   to be able to load it later when needed, e.g.:
## Not run:
save(myGVF.db, file="custom.GVF.Archive.RData")

## End(Not run)

# 3. Starting a new ReGenesees session will set the default GVF.db,
```

```

#   which we can simulate in this example as follows:
GVF.db$reset()
GVF.db

# 4. Now you can load your previously saved customized GVF.db...
## Not run:
load("custom.GVF.Archive.RData")

## End(Not run)
# ...so that myGVF.db is back into your .GlobalEnv:
myGVF.db

# 5. Lastly, you must overwrite GVF.db with your custom
#   GVF archive myGVF.db via function GVF.db$assign:
GVF.db$assign(myGVF.db)
GVF.db

### Now your custom GVF archive is ready to be used by ReGenesees.
### STOP

# Illustrate some GVF.db$insert checks by trying crazy models
# or ill-specified attributes

# Examples start: reset GVF.db to its default values
GVF.db$reset()
GVF.db

# GVF model must be "syntactically new"...
## Not run:
GVF.db$insert(log(CV^2) ~ log(Y))

## End(Not run)
# ...if this is the case, it can even be "equivalent" to old ones: e.g.
# the following is identical to model number 5 and will produces identical
# estimates and predictions (as you may want to check):
GVF.db$insert(I(sqrt(VAR)/Y) ~ I(1/Y) + Y, "Total", Resp.to.CV = "resp")
GVF.db

# GVF model must have a response term
## Not run:
GVF.db$insert(~ log(Y))

## End(Not run)

# GVF model response must involve some of 'SE', 'CV', 'VAR'
## Not run:
GVF.db$insert(DEFF ~ log(Y))

## End(Not run)

# GVF model predictor must involve 'Y'
## Not run:
GVF.db$insert(VAR ~ SE)

## End(Not run)

# If passed, Resp.to.CV can only involve 'resp' and 'Y'

```

```
## Not run:
GVF.db$insert(I(sqrt(VAR)/Y) ~ I(1/Y) + Y + I(Y^2), Resp.to.CV = "sqrt(VAR)/Y")

## End(Not run)

# Examples end: reset GVF.db to its default values:
GVF.db$reset()
```

gvf.input

Prepare Input Data to Fit GVF Models

Description

Transforms a set of computed survey statistics into a suitable (data.frame-like) data structure, in order to fit a Generalized Variance Function model.

Usage

```
gvf.input(design, ..., stats = list(...))

## S3 method for class 'gvf.input'
plot(x, ...)
```

Arguments

design	The design object (of class <code>analytic</code> or inheriting from it) from which the input survey statics are supposed to have been derived.
...	For function <code>gvf.input</code> , objects containing survey statistics. For <code>plot</code> , further arguments passed to or from other methods.
stats	A list storing survey statistic objects (see ‘Details’).
x	The object of class <code>gvf.input</code> to plot.

Details

Given a set of survey statistic objects (via arguments ‘...’ or `stats`) and a design object (`design`) from which those statics are supposed to have been derived, function `gvf.input` builds a data structure that can be fed to **ReGenesees** GVF model fitting function `fit.gvf`.

Argument ‘...’ can be bound to an arbitrary number of objects. These objects must be output of survey statistics functions, i.e. `svystatTM`, `svystatR`, `svystatS`, `svystatSR`, `svystatB`, `svystatQ`, and `svystatL`.

All input objects passed to ‘...’ must derive from estimators of the *same* kind (as returned by function `estimator.kind`). For the same reason, objects of *mixed* kind (see `estimator.kind`) are not allowed. Since function `svystatL` can actually handle estimators of *different* kinds, objects of kind ‘Complex Estimator’ are the only exception to the rule.

Argument `stats` can be used as an alternative to argument ‘...’: one has only to store the survey statistic objects into a list and bind such list to `stats`. Note that, if both are passed, argument `stats` will prevail on ‘...’ (see ‘Examples’).

Should *any* input object be a survey statistic derived from a design object *other than* `design`, the function would raise an error.

The `plot` method for `gvf.input` objects produces a matrix of scatterplots with polynomial smoothers.

Value

An object of class `gvf.input`, inheriting from class `data.frame`: basically a data frame supplied with appropriate attributes.

Each row of the data frame contains an *estimate* along with its estimated sampling error, expressed in terms of *standard error*, *coefficient of variation*, *variance*, and - whenever available - *design effect*.

The data frame has the following structure:

`name` The name of the original estimate, factor.

`Y` The value of the original estimate, numeric.

`SE` The standard error of the original estimate, numeric.

`CV` The coefficient of variation of the original estimate, numeric.

`VAR` The variance of the original estimate, numeric.

`DEFF` The design effect of the original estimate (if available), numeric.

Note that by inspecting the *attributes* of a `gvf.input` object, one can always identify which design object and which kind of estimator generated that object (see ‘Examples’).

Author(s)

Diego Zardetto

See Also

[estimator.kind](#) to assess what kind of estimates are stored inside a survey statistic object, [svystat](#) as a useful alternative to prepare the input for GVF model fitting, [GVF.db](#) to manage **ReGenesees** archive of registered GVF models, [fit.gvf](#) to fit GVF models, [plot.gvf.fit](#) to get diagnostic plots for fitted GVF models, [drop.gvf.points](#) to drop alleged outliers from a fitted GVF model and simultaneously refit it, and [predictCV](#) to predict CV values via fitted GVF models.

Examples

```
# Load sbs data:
data(sbs)

# Create a design object...
sbsdes<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,fpc=~fpc)

# ...and use it to compute some survey statistics:
va<-svystatTM(sbsdes,~va.imp2)
va.reg<-svystatTM(sbsdes,~va.imp2,~region)
va.area<-svystatTM(sbsdes,~va.imp2,~area)

# Now suppose you want to fit a GVF model on the estimates and errors computed
# above: you must prepare your input as follows:
ee<-gvf.input(sbsdes,va,va.reg,va.area)

# Inspect the obtained data structure:
ee
str(ee)  # Note the "design" and "stats.kind" attributes
plot(ee)

# Note that, instead of argument '...', you could have used argument 'stats'
# as follows:
```

```

va.list<-list(va,va.reg,va.area)
ee2<-gvf.input(sbsdes,stats=va.list)

# ...obtaining exactly the same result:
identical(ee,ee2)

# Note also that, if both are passed, argument 'stats' prevails on '...':
# indeed, while:
gvf.input(sbsdes,va.reg)
# we would get again:
gvf.input(sbsdes,va.reg,stats=va.list)

```

gvf.misc

Miscellanea: Methods for Fitted GVF Models

Description

These methods extract information from fitted GVF model(s).

Usage

```

## S3 method for class 'gvf.fit'
coef(object, ...)
## S3 method for class 'gvf.fits'
coef(object, ...)
## S3 method for class 'gvf.fit.gr'
coef(object, ...)
## S3 method for class 'gvf.fits.gr'
coef(object, ...)

## S3 method for class 'gvf.fit'
residuals(object, ...)
## S3 method for class 'gvf.fits'
residuals(object, ...)
## S3 method for class 'gvf.fit.gr'
residuals(object, ...)
## S3 method for class 'gvf.fits.gr'
residuals(object, ...)

## S3 method for class 'gvf.fit'
fitted(object, ...)
## S3 method for class 'gvf.fits'
fitted(object, ...)
## S3 method for class 'gvf.fit.gr'
fitted(object, ...)
## S3 method for class 'gvf.fits.gr'
fitted(object, ...)

## S3 method for class 'gvf.fit'
predict(object, ...)
## S3 method for class 'gvf.fits'

```

```
predict(object, ...)
## S3 method for class 'gvf.fit.gr'
predict(object, ...)
## S3 method for class 'gvf.fits.gr'
predict(object, ...)

## S3 method for class 'gvf.fit'
effects(object, ...)
## S3 method for class 'gvf.fits'
effects(object, ...)
## S3 method for class 'gvf.fit.gr'
effects(object, ...)
## S3 method for class 'gvf.fits.gr'
effects(object, ...)

## S3 method for class 'gvf.fit'
rstandard(model, ...)
## S3 method for class 'gvf.fits'
rstandard(model, ...)
## S3 method for class 'gvf.fit.gr'
rstandard(model, ...)
## S3 method for class 'gvf.fits.gr'
rstandard(model, ...)

## S3 method for class 'gvf.fit'
rstudent(model, ...)
## S3 method for class 'gvf.fits'
rstudent(model, ...)
## S3 method for class 'gvf.fit.gr'
rstudent(model, ...)
## S3 method for class 'gvf.fits.gr'
rstudent(model, ...)

## S3 method for class 'gvf.fit'
anova(object, ...)
## S3 method for class 'gvf.fits'
anova(object, ...)
## S3 method for class 'gvf.fit.gr'
anova(object, ...)
## S3 method for class 'gvf.fits.gr'
anova(object, ...)

## S3 method for class 'gvf.fit'
vcov(object, ...)
## S3 method for class 'gvf.fits'
vcov(object, ...)
## S3 method for class 'gvf.fit.gr'
vcov(object, ...)
## S3 method for class 'gvf.fits.gr'
vcov(object, ...)
```

Arguments

<code>object</code>	An object containing one or more fitted GVF models (see ‘Usage’ for the allowed classes).
<code>model</code>	An object containing one or more fitted GVF models (see ‘Usage’ for the allowed classes).
<code>...</code>	Further arguments passed to or from other methods (see corresponding <code>.lm</code> methods).

Details

These methods can be used to extract information from fitted GVF model(s).

For more details on their usage, please read the help pages of the methods with same name defined on class `.lm` by package **stats** (e.g. `coef`, `fitted`, etc.).

Value

The requested information, wrapped into an R object whose structure depends on the class of the input fitted GVF model(s) (i.e. arguments `object` and/or `model`).

Author(s)

Diego Zardetto

See Also

[GVF.db](#) to manage **ReGenesees** archive of registered GVF models, [gvf.input](#) and [svystat](#) to prepare the input for GVF model fitting, [fit.gvf](#) to fit GVF models, [plot.gvf.fit](#) to get diagnostic plots for fitted GVF models, [drop.gvf.points](#) to drop alleged outliers from a fitted GVF model and simultaneously refit it, and [predictCV](#) to predict CV values via fitted GVF models.

Examples

```
# Load example data:
data(AF.gvf)

# Inspect available estimates and errors of counts:
head(ee.AF)
summary(ee.AF)

# List available registered GVF models:
GVF.db

## (A) A *single* fitted GVF model ##
# Fit example data to registered GVF model number one:
m <- fit.gvf(ee.AF, 1)

# Extract some information:
coef(m)
fitted(m)

## (B) A *a set* of GVF models fitted to the same data ##
# Fit example data to registered GVF models for frequencies (i.e. number 1:3):
mm <- fit.gvf(ee.AF, 1:3)
```

```

# Extract some information:
r.mod <- residuals(mm)
lapply(r.mod, head)

r.sta <- rstandard(mm)
lapply(r.sta, head)

r.stu <- rstudent(mm)
lapply(r.stu, head)

## (C) a *single* GVF model fitted to *grouped* data ##
# We have at our disposal the following survey design object on household data:
exdes

# Use function svystat to prepare *grouped* estimates and errors of counts
# to be fitted separately (here groups are regions):
ee.g <- svystat(exdes, y=~ind, by=~age5c:marstat:sex, combo=3, group=~regcod)
str(ee.g)

# Fit registered GVF model number one separately inside groups:
m.g <- fit.gvf(ee.g, 1)

# Extract some information:
coef(m.g)
fitted(m.g)

## (D) a *set of* GVF models fitted to *grouped* data ##
# Fit all registered GVF models for frequencies (i.e. number 1:3) separately
# inside groups:
mm.g <- fit.gvf(ee.g, 1:3)
# Extract some information:
coef(mm.g)
fitted(mm.g)

```

plot.gvf.fit

Diagnostic Plots for Fitted GVF Models

Description

This function provides basic diagnostic plots for fitted GVF model(s).

Usage

```

## S3 method for class 'gvf.fit'
plot(x, which.more = 1:3, id.n = 3, labels.id = names(residuals(x)),
     cex.id = 0.75, label.pos = c(4, 2), cex.caption = 1, Main = NULL, ...)

## S3 method for class 'gvf.fits'
plot(x, which.more = NULL, id.n = 3, labels.id = names(residuals(x)),
     cex.id = 0.75, label.pos = c(4, 2), cex.caption = 1, Main = NULL, ...)

```

```
## S3 method for class 'gvf.fit.gr'
plot(x, which.more = 1:3, id.n = 3, labels.id = NULL,
      cex.id = 0.75, label.pos = c(4, 2), cex.caption = 1, ...)

## S3 method for class 'gvf.fits.gr'
plot(x, which.more = NULL, id.n = 3, labels.id = NULL,
      cex.id = 0.75, label.pos = c(4, 2), cex.caption = 1, ...)
```

Arguments

<code>x</code>	An object containing one or more fitted GVF models (see ‘Usage’ for the allowed classes).
<code>which.more</code>	Select additional plots beyond the default one (‘Observed vs Fitted’). Can be any subset of vector 1:6 with up to three elements.
<code>id.n</code>	Number of points to be initially labelled in each plot, starting with the most extreme.
<code>labels.id</code>	Vector of labels, from which the labels for extreme points will be chosen. NULL uses observation numbers.
<code>cex.id</code>	Magnification of point labels.
<code>label.pos</code>	Positioning of labels, for the left half and right half of the graph(s) respectively.
<code>cex.caption</code>	Controls the size of caption.
<code>Main</code>	Optional string to be added to automatic plot titles.
<code>...</code>	Other parameters to be passed through to plotting functions.

Details

Diagnostic plots can be useful both for assessing the goodness of a GVF model fit qualitatively, and for selecting the “best” GVF model among different alternatives.

This function can provide any of the following 7 plots:

- (0) 'Observed vs Fitted'
- (1) 'Residuals vs Fitted'
- (2) 'Normal Q-Q'
- (3) 'Scale-Location'
- (4) 'Cook's distance'
- (5) 'Residuals vs Leverage'
- (6) 'Cook's distances vs Leverage/(1-Leverage)'

The ‘*Residuals vs Fitted*’ plot is special in that it will be always provided: this explains its zero-th order in the list above. The rest of the list, namely plots 1:6, exactly matches the numbering convention of function [plot.lm](#).

Additional plots - beyond ‘*Residuals vs Fitted*’ - can be requested through argument `which.more`. Any subset of 1:6 is allowed, provided its length does not exceed 3. Therefore, at most 4 plots will be generated simultaneously.

Note that the *default* behaviour of this function do depend on whether input object `x` stores *one* or *more than one* fitted GVF models. In the first case, plots 0:3 will be returned in a multiple plot with a 2x2 layout. In the second case, only the default plot number 0 will be returned, opening a new graphics frame for each different GVF model.

Argument `id.n` specifies how many points have to be labelled, starting with the most extreme in terms of residuals: this applies to all plots.

Argument `Main` is expected to be seldom (if ever) useful: its main purpose is programming consistency at a deeper level.

All the other arguments have the same meaning as in function `plot.lm`.

Author(s)

Diego Zardetto

References

See `plot.lm` and references therein.

See Also

`GVF.db` to manage **ReGenesees** archive of registered GVF models, `gvf.input` and `svystat` to prepare the input for GVF model fitting, `fit.gvf` to fit GVF models, `drop.gvf.points` to drop alleged outliers from a fitted GVF model and simultaneously refit it, and `predictCV` to predict CV values via fitted GVF models.

Examples

```
# Load example data:
data(AF.gvf)

# Inspect available estimates and errors of counts:
str(ee.AF)

# List available registered GVF models:
GVF.db

#####
# Diagnostic plots for fitted GVF model(s) #
#####

## (A) Plots of a *single* fitted GVF model ##
# Fit example data to registered GVF model number one:
m <- fit.gvf(ee.AF, 1)

## Default call yields 4 plots:
plot(m)

# Play with argument 'which.more':
## which.more = NULL yields the "Observed vs Fitted" plot only:
plot(m, which.more = NULL)

## which.more = 1 adds the "Residuals vs Fitted" plot:
plot(m, which.more = 1)

## subsets of 1:6 with length <= 3 are allowed:
plot(m, which.more = c(1:2,4))

# Just for illustration, play with other parameters:
```

```

plot(m, id.n = 6, col = "blue", pch = 20)

## (B) Plots of *many* fitted GVF models ##
# Fit example data to registered GVF models for frequencies (i.e. number 1:3):
mm <- fit.gvf(ee.AF, 1:3)

## Default call yields the "Observed vs Fitted" plot reported separately for
## each model in subsequent graphics frames:
plot(mm)

# Play with argument 'which.more':
## which.more = 1:3 yields subsequent 2x2 plots:
plot(mm, which.more = 1:3)

## again, subsets of 1:6 are allowed:
plot(mm, which.more = 1)

#####
# Diagnostic plots for "grouped" fitted GVF model(s) #
#####
# We have at our disposal the following survey design object on household data:
exdes

# Use function svstat to prepare "grouped" estimates and errors of counts
# to be fitted separately (here groups are regions):
ee <- svstat(exdes, y=~ind, by=~age5c:marstat:sex, combo=3, group=~regcod)
lapply(ee, head)

## (C) Plots of a *single* GVF model fitted to different groups ##
# Fit registered GVF model number one separately inside groups:
m.g <- fit.gvf(ee, 1)

## Default call yields 4 plots reported separately for each group
## in subsequent graphics frames:
plot(m.g)

## Play with argument 'which.more' to select different plots:
plot(m.g, which.more = c(1:2,4))

## (D) Plots of *many* GVF model fitted to different groups ##
# Fit all registered GVF models for frequencies separately inside groups:
mm.g <- fit.gvf(ee, 1:3)

## Default call yields the "Residuals vs Fitted" plot reported separately
## for each group in subsequent graphics frames:
plot(mm.g)

## Play with argument 'which.more' to add more plots:
plot(mm.g, which.more = 1:3, id.n = 6, col = "blue", pch = 20)

```


Description

Provides a natural language description of a known totals data frame to be used for a calibration task.

Usage

```
pop.desc(pop.totals)
```

Arguments

pop.totals	An object of class pop.totals, be it a template or the actual known totals data frame for the calibration task.
------------	---

Details

Function [pop.template](#) generates a *template* (i.e. *empty*) data frame of class pop.totals, which is appropriate to store the known totals of a given calibration task. Afterwards, the template data frame must be filled with actual figures.

When the sampling frame of the survey is available and the actual population totals can be calculated from this source, function [fill.template](#) (i) automatically computes the totals of the auxiliary variables from the sampling frame, (ii) safely arranges and formats these values according to the template structure. Therefore, function [fill.template](#) avoids any need for the user to understand, comply with, or even be aware of, the structure of the template that is being filled.

On the contrary, when the population totals are available to the user as such, that is in the form of already computed aggregated values (e.g. because they come from an external source, like a Population Census), it is up to the user to correctly fill the template, that is to put the *right values* in the *right slots* of the prepared template.

Function pop.desc has been designed for users who cannot take advantage of function [fill.template](#), to help them understand the structure of the known totals template, in order to safely fill it with actual figures.

Invoking pop.desc will print on screen a detailed natural language description of the structure of the input pop.totals object. Such description will clarify how known totals are organized inside the template slots.

Value

The main purpose of the function is to print on screen, anyway it returns invisibly the input pop.totals object (as print would do).

Author(s)

Diego Zardetto

See Also

[e.calibrate](#) for calibrating weights, [pop.template](#) for the definition of the class pop.totals and to build a template data frame for known population totals, [fill.template](#) to automatically fill the template when a sampling frame is available.

Examples

```
## First prepare some design objects to work with:

# Load household data:
data(data.examples)
# Build a design object:
exdes<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
                  weights=~weight)

# Load sbs data:
data(sbs)
# Build a design object:
sbsdes<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,fpc=~fpc)

## Now build some known totals templates that (after having been filled by
## actual figures) could be used to calibrate the design objects above,
## and explore the corresponding natural language description:

#####
## Some simple and small examples ##
#####
expop<-pop.template(exdes,calmodel=~1)
expop
pop.desc(expop)

expop<-pop.template(exdes,calmodel=~sex)
expop
pop.desc(expop)

# equivalent to the one above
expop<-pop.template(exdes,calmodel=~sex-1)
expop
pop.desc(expop)

expop<-pop.template(exdes,calmodel=~x1+x2+x3,partition=~procod)
expop
pop.desc(expop)

expop<-pop.template(exdes,calmodel=~sex:marstat-1)
expop
pop.desc(expop)

# equivalent to the one above
expop<-pop.template(exdes,calmodel=~sex*marstat-1)
expop
pop.desc(expop)

# equivalent to the one above
expop<-pop.template(exdes,calmodel=~1,partition=~sex:marstat)
expop
pop.desc(expop)

expop<-pop.template(exdes,calmodel=~x1+age5c:marstat-1,partition=~regcod:sex)
expop
pop.desc(expop)
```

```
#####
## Some more involved and bigger examples ##
#####
expop<-pop.template(exdes,calmodel=~sex:age10c:regcod + sex:age5c:procod - 1)
expop
pop.desc(expop)

# equivalent to the one above (because procod is nested into regcod and
# age10c is nested into age5c)
expop<-pop.template(exdes,calmodel=~age10c+procod-1,
  partition=~regcod:sex:age5c)
expop
pop.desc(expop)
# NOTE: Most of the entries of the template above will be structural zeros,
#       as can be seen in what follows:
expop.HT<-aux.estimate(exdes, template=expop)
expop.HT
sum(expop.HT==0)

# Switch to sbs data
sbspop<-pop.template(sbsdes,
  calmodel=~(emp.num + ent):(nace.macro + emp.cl) - 1, partition=~region)

# Can fill the template using the sampling frame...
sbspop<-fill.template(universe=sbs.frame,template=sbspop)
sbspop

# ...and invoke function pop.desc on the filled known totals dataframe:
pop.desc(sbspop)

sbspop <- pop.template(data=sbsdes,
  calmodel=~((emp.num + ent):(nace2 + emp.cl:nace.macro))-1,
  partition=~region:public)

sbspop
pop.desc(sbspop)
```

pop.template

Template Data Frame for Known Population Totals

Description

Constructs a *"template"* data frame to store known population totals for a calibration problem.

Usage

```
pop.template(data, calmodel, partition = FALSE)
```

Arguments

data	Data frame of survey data (or an object inheriting from class <i>analytic</i>).
calmodel	Formula defining the linear structure of the calibration model.

partition Formula specifying the variables that define the "calibration domains" for the model. FALSE (the default) implies no calibration domains.

Details

This function creates an object of class `pop.totals`. A `pop.totals` object is made up by the union of a data frame (whose structure conforms to the standard required by `e.calibrate` for the known totals) and the metadata describing the calibration problem.

The mandatory argument `data` must identify the survey data frame on which the calibration problem is defined (or, as an alternative, an analytic object built upon that data frame). Should empty levels be present in any factor variable belonging to `data`, they would be dropped.

The mandatory argument `calmodel` symbolically defines the calibration model you intend using: it identifies the auxiliary variables and the constraints for the calibration problem. The data variables referenced by `calmodel` must be numeric or factor and must not contain any missing value (NA).

The optional argument `partition` specifies the variables that define the calibration domains for the model. The default value (FALSE) means either that there are not calibration domains or that you want to solve the problem globally (even though it could be factorized). If a formula is passed through the `partition` argument the program checks that `calmodel` actually describes a "reduced model", that is it does not reference any of the partition variables; if this is not the case, the program stops and prints an error message. Notice that a formula like `by=~D1+D2` will be automatically translated into the factor-crossing formula `by=~D1:D2`. The data variables referenced by `partition` (if any) must be factor and must not contain any missing value (NA).

Value

An object of class `pop.totals`. The data frame it contains is a "*template*" in the sense that all the known totals it must be able to store are missing (NA). However, this data frame has a structure that complies with the standard required by `e.calibrate` (provided the latter is invoked with the same `calmodel` and `partition` values used to create the template).

The operation of filling the template's NAs with the actual values of the corresponding population totals has, obviously, to be done by the user. If the user has access to a "*sampling frame*" (that is a data frame containing the complete list of the units belonging to the target population along with the corresponding values of the auxiliary variables), then he can exploit the function [fill.template](#) to automatically fill the template.

The `pop.totals` class is a specialization of the `data.frame` class; this means that an object built by `pop.template` inherits from the `data.frame` class and you can use on it every method defined on that class.

Author(s)

Diego Zardetto

See Also

[e.calibrate](#) for calibrating weights, [population.check](#) to check that the known totals data frame satisfies the standard required by `e.calibrate`, [pop.desc](#) to provide a natural language description of the template structure, and [fill.template](#) to automatically fill the template when a sampling frame is available.

Examples

```

# Creation of population totals template data frames for different
# calibration problems (if the calibration models can be factorized
# both a global and a partitioned solution are given):

data(data.examples)

# 1) Calibration on the total number of units in the population:
pop.template(data=example,calmodel=~1)

# 2) Calibration on the total number of units in the population
# and on the marginal distribution of marstat (notice that the
# total for the first level "married" of the marstat factor
# variable is missing because it can be deduced from
# the remaining totals):
pop.template(data=example,calmodel=~marstat)

# 3) Calibration on the marginal distribution of marstat (you
# must explicitly remove the intercept term in the
# calibration model adding -1 to the calmodel formula):
pop.template(data=example,calmodel=~marstat-1)

# 4) Calibration (global solution) on the joint distribution of sex
# and marstat:
pop.template(data=example,calmodel=~sex:marstat-1)

# 4.1) Calibration (partitioned solution) on the joint distribution
# of sex and marstat:
# 4.1.1) Using sex to define calibration domains:
pop.template(data=example,calmodel=~marstat-1,partition=~sex)

# 4.1.2) Using marstat to define calibration domains:
pop.template(data=example,calmodel=~sex-1,partition=~marstat)

# 4.1.3) Using sex and marstat to define calibration domains:
pop.template(data=example,calmodel=~1,partition=~sex:marstat)

# 5) Calibration (global solution) on the total for the quantitative
# variable x1 and on the marginal distribution of the qualitative
# variable age5c, in the subpopulations defined by crossing sex
# and marstat:
pop.template(data=example,calmodel=~(age5c+x1-1):sex:marstat)

# 5.1) The same problem with partitioned solutions:
# 5.1.1) Using sex to define calibration domains:
pop.template(data=example,calmodel=~(age5c+x1-1):marstat,partition=~sex)

# 5.1.2) Using marstat to define calibration domains:
pop.template(data=example,calmodel=~(age5c+x1-1):sex,partition=~marstat)

# 5.1.3) Using sex and marstat to define calibration domains:
pop.template(data=example,calmodel=~age5c+x1-1,partition=~sex:marstat)

```

population.check

Compliance Test for Known Totals Data Frames

Description

Checks whether a known population totals data frame conforms to the standard required by `e.calibrate` for a specific calibration problem.

Usage

```
population.check(df.population, data, calmodel, partition = FALSE)
```

Arguments

<code>df.population</code>	Data frame of known population totals.
<code>data</code>	Data frame of survey data (or an object inheriting from class <code>analytic</code>).
<code>calmodel</code>	Formula defining the linear structure of the calibration model.
<code>partition</code>	Formula specifying the variables that define the "calibration domains" for the model. <code>FALSE</code> (the default) implies no calibration domains.

Details

The behaviour of this function depends on the outcome of the test. If `df.population` is found to conform to the standard, the function first converts it into an object of class `pop.totals` and then invisibly returns it. Failing this, the function stops and prints an error message: the meaning of the message should help the user diagnose the cause of the problem.

The mandatory argument `df.population` identifies the known totals data frame for which compliance with the standard is to be checked.

The mandatory argument `data` identifies the survey data frame on which the calibration problem is defined (or, as an alternative, an `analytic` object built upon that data frame).

The mandatory argument `calmodel` symbolically defines the calibration model you intend using: it identifies the auxiliary variables and the constraints for the calibration problem. The data variables referenced by `calmodel` must be numeric or factor and must not contain any missing value (NA).

The optional argument `partition` specifies the variables that define the calibration domains for the model. The default value (`FALSE`) means either that there are not calibration domains or that you want to solve the problem globally (even though it could be factorized). If a formula is passed through the `partition` argument the program checks that `calmodel` actually describes a "reduced model", that is it does not reference any of the partition variables; if this is not the case, the program stops and prints an error message. Notice that a formula like `by=~D1+D2` will be automatically translated into the factor-crossing formula `by=~D1:D2`. The data variables referenced by `partition` (if any) must be factor and must not contain any missing value (NA).

Value

An invisible object of class `pop.totals`. The `pop.totals` class is a specialization of the `data.frame` class; this means that an object built by `pop.template` inherits from the `data.frame` class and you can use on it every method defined on that class.

Note

The `population.check` function can be used to convert a known totals data frame that conforms to the standard required by `e.calibrate` into an object of class `pop.totals`. The usefulness of this conversion lies in the fact that, once you have known totals with this "certified format", you can invoke `e.calibrate` without specifying the values for the `calmodel` and `partition` arguments (this means that the function is able to extract them directly from the attributes of the `pop.totals` object).

Author(s)

Diego Zardetto

See Also

[e.calibrate](#) for calibrating weights, [pop.template](#) for the definition of the class `pop.totals` and to build a "template" data frame for known population totals, [fill.template](#) to automatically fill the template when a sampling frame is available.

Examples

```
data(data.examples)

# Suppose you have to calibrate the example survey data frame
# on the totals of x1 by sex and you want the partitioned solution.
# Start creating a design object:
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
  weights=~weight)

# Then build a template data frame for the known totals:
pop<-pop.template(data=example,calmodel=~x1-1,partition=~sex)
pop
class(pop)

# Now fill NAs with the actual values for the population
# totals (suppose 123 for sex="f" and 456 for sex="m"):
pop[, "x1"]<-c(123,456)
pop
class(pop)

# Finally check if pop complies with the e.calibrate standard:
population.check(df.population=pop,data=example,calmodel=~x1-1,
  partition=~sex)

# If, despite keeping the content unchanged, we altered the
# structure of the data frame (for example, by changing the
# order of its rows)...
pop.mod<-pop ; pop.mod[1,]<-pop[2,] ; pop.mod[2,]<-pop[1,]
pop
pop.mod

# ...we would obtain an error:
## Not run:
population.check(df.population=pop.mod,data=example,calmodel=~x1-1,
  partition=~sex)
```

```
## End(Not run)

# Remember that, if the known totals have been converted
# into the pop.totals "format" by means of population.check,
# it is possible to invoke e.calibrate without specifying
# calmodel and partition:

class(pop04p)
pop04p
descal04p<-e.calibrate(design=des,df.population=pop04p,
                      calfun="logit",bounds=bounds,aggregate.stage=2)

# ...this option is not allowed if the known totals
# are not of class 'pop.totals' even if they conform to the
# standard:

pop04p.mod=data.frame(pop04p)
class(pop04p.mod)
pop04p.mod
## Not run:
e.calibrate(design=des,df.population=pop04p.mod,calfun="logit",
            bounds=bounds,aggregate.stage=2)

## End(Not run)
```

predictCV

Predict CV Values via Fitted GVF Models

Description

This function predicts the CV values associated to given estimates, based on fitted GVF model(s).

Usage

```
predictCV(object, new.Y = NULL, scale = NULL, df = Inf,
          interval = c("none", "confidence", "prediction"), level = 0.95,
          na.action = na.pass, pred.var = NULL, weights = 1)
```

Arguments

object	An object containing one or more fitted GVF models.
new.Y	A data frame storing new estimates whose CVs have to be predicted. If omitted or NULL, CVs arising from the fitted GVF model(s) will be returned.
scale	Scale parameter for standard error calculation. See also predict.lm .
df	Degrees of freedom for scale. See also predict.lm .
interval	Type of interval calculation. Can be abbreviated. See also predict.lm .
level	Confidence (or tolerance) level for intervals. See also predict.lm .
na.action	Function determining what should be done with missing values in new.Y. The default is to predict NA. See also predict.lm .

pred.var	The variance(s) for future observations to be assumed for prediction intervals. See also predict.lm .
weights	Variance weights for prediction. This can be a numeric vector or a one-sided model formula. In the latter case, it is interpreted as an expression evaluated in new.Y. See also predict.lm .

Details

The main motivation for building and fitting a GVF model is to exploit the fitted model to *predict* the sampling error associated to a given estimate, instead of having to *compute* directly an estimate of such sampling error. Function predictCV is relevant to that scope.

Despite different GVF models can specify as response term (call it 'resp') different functions of variables 'SE', 'CV', and 'VAR' (see e.g. [Wolter 07]), function predictCV adopts variable 'CV' as a universal *pivot*. This means that predictCV can handle *only* fitted GVF models which are *registered* (that is already stored inside [GVF.db](#)), and for which variable Resp.to.CV is *not* NA. Indeed, it is variable Resp.to.CV of data frame GVF.db which tells predictCV how to transform the response of an arbitrary GVF model ('resp') into the pivot measure of variability ('CV').

By default new.Y = NULL and CVs (and intervals, if any) obtained by transforming fitted response values will be returned. If passed, argument new.Y must be a data frame storing new estimates for which CVs have to be predicted. Such input estimates have to be stored in column Y of data frame new.Y. Moreover, if object stores GVF model(s) fitted to *grouped* data (namely, it has class gvf.fit.gr or gvf.fits.gr), then new.Y should also have columns identifying the *groups* to which input estimates are referred (see 'Examples'). The *only exception* is the following: if the new.Y data frame has just the Y column, then CVs will be predicted for *all groups* (see 'Examples'). The function will check for consistency between groups available in object and in new.Y (see 'Examples').

If interval = "none" (the default), the function will return predicted CVs only. Otherwise, lower and upper bounds of confidence (or prediction) intervals around predicted CVs will be also provided. Use argument level to specify the desired confidence (or tolerance) level for those intervals.

All the other arguments have the same meaning as in function [predict.lm](#).

Value

If object is a single GVF model (classes gvf.fit and gvf.fit.gr), a data frame.

If object is a set of GVF models fitted to the same data (classes gvf.fits and gvf.fits.gr), a list of data frames, one for each input GVF model.

The output data frame(s) will store input estimates new.Y plus additional columns:

CV.fit Predicted CV value, numeric.

CV.lwr Lower bound of requested interval (if any), numeric.

CV.upr Upper bound of requested interval (if any), numeric.

Of course, lower and upper bounds for CVs will be reported only when interval != "none".

Note

Please read the 'Note' section of [predict.lm](#).

Author(s)

Diego Zardetto

References

Wolter, K.M. (2007) *"Introduction to Variance Estimation"*, Second Edition, Springer-Verlag, New York.

See Also

[GVF.db](#) to manage **ReGenesee**s archive of registered GVF models, [gvf.input](#) and [svystat](#) to prepare the input for GVF model fitting, [fit.gvf](#) to fit GVF models, [plot.gvf.fit](#) to get diagnostic plots for fitted GVF models, and [drop.gvf.points](#) to drop alleged outliers from a fitted GVF model and simultaneously refit it.

Examples

```
#####
# Simple examples to illustrate the syntax #
#####
# Load example data:
data(AF.gvf)

# Inspect available estimates and errors of counts:
head(ee.AF)
summary(ee.AF)

# List available registered GVF models:
GVF.db

## (A) A *single* fitted GVF model ##
# Fit example data to registered GVF model number one:
m <- fit.gvf(ee.AF, 1)

# Not passing 'new.Y' yield CVs from fitted response values:
p <- predictCV(m)

# Take a look:
head(p)
with(p, plot(CV, CV.fit, col = "blue", pch = 20))

# Now let's predict CV values for new estimates of counts
# e.g. Y = c(1000, 5000, 10000, 50000, 100000)
# First, put these values into a data frame:
new.Y <- data.frame(Y = c(1000, 5000, 10000, 50000, 100000))
new.Y

# Then, compute predicted values and confidence intervals:
p <- predictCV(m, new.Y, interval = "confidence")
p

# NOTE: Should we ever need it, we could also use function predict
#       to predict *response* values instead of CVs:
predict(m, new.Y, interval = "confidence")

## (B) A *a set* of GVF models fitted to the same data ##
# Fit example data to registered GVF models for frequencies (i.e. number 1:3):
mm <- fit.gvf(ee.AF, 1:3)
```

```

# Let's predict CV values for the same new estimates of counts used above,
# i.e. Y = c(1000, 5000, 10000, 50000, 100000).

# Separate predictions will be obtained from the three fitted GVF models
pp <- predictCV(mm, new.Y, interval = "confidence")
pp

# NOTE: The WARNING above arises from the third fitted GVF model and explains
#       the appearance of NaN at the lower bound of the CV confidence interval
#       for input Y = 100000. Indeed, the response of the third model is the
#       squared CV (which ought to be *positive*), but the prediction for the
#       lower endpoint of the confidence interval happens to be *negative*:
predict(mm, new.Y, interval = "confidence")

## (C) a *single* GVF model fitted to *grouped* data ##
# We have at our disposal the following survey design object on household data:
exdes

# Use function svystat to prepare *grouped* estimates and errors of counts
# to be fitted separately (here groups are regions):
ee.g <- svystat(exdes, y=~ind, by=~age5c:marstat:sex, combo=3, group=~regcod)

# Inspect these grouped estimates and errors of counts:
lapply(ee.g, head)
lapply(ee.g, summary)

# Fit registered GVF model number one, separately inside regions '6', '7',
# and '10':
m.g <- fit.gvf(ee.g, 1)

# Suppose we want to predict CV values for the same new estimates of counts used
# above, i.e. Y = c(1000, 5000, 10000, 50000, 100000).
# Obviously, we need tell to what groups (i.e. regions) should these Y values
# be referred. Therefore, input data frame new.Y should have columns identifying
# the groups (i.e. regions).

# Case 1: all known regions (i.e. regions '6', '7', and '10')
#       Here we can exploit the exception described in section 'Details' and
#       avoid building group variables explicitly:

# Predict:
p.g <- predictCV(m.g, new.Y, interval = "confidence")
p.g

# Case 2: a subset of known regions (e.g. region '7' only)
#       Here we must build group variables explicitly:
new.Y.g <- data.frame(Y = c(1000, 5000, 10000, 50000, 100000),
                      regcod = 7)
new.Y.g

# Predict:
p.g <- predictCV(m.g, new.Y.g, interval = "confidence")
p.g

```

```

# Case 3: a subset of known regions (e.g. region '7') *plus* some *unknown*
#         region (e.g. region '11').
#         Unknown groups will be tacitly *discarded*:
new.Y.g <- data.frame(Y = c(1000, 5000, 10000, 50000, 100000),
                      regcod = rep(c(7, 11), each = 5))
new.Y.g

# Predict:
p.g <- predictCV(m.g, new.Y.g, interval = "confidence")
p.g

# Case 4: only *unknown* regions (e.g. regions '11' and '12').
#         This will raise an *error*:
new.Y.g <- data.frame(Y = c(1000, 5000, 10000, 50000, 100000),
                      regcod = rep(c(11, 12), each = 5))
new.Y.g

## Not run:
# Predict:
p.g <- predictCV(m.g, new.Y.g, interval = "confidence")

## End(Not run)

# Case 5: *unknown* group variables (e.g. 'region' instead of 'regcod').
#         This will raise an *error*:
new.Y.g <- data.frame(Y = c(1000, 5000, 10000, 50000, 100000),
                      region = rep(c(11, 12), each = 5))
new.Y.g

## Not run:
# Predict:
p.g <- predictCV(m.g, new.Y.g, interval = "confidence")

## End(Not run)

## (D) a *set of* GVF models fitted to *grouped* data ##
# Fit all registered GVF models for frequencies (i.e. number 1:3) separately
# inside groups:
mm.g <- fit.gvf(ee.g, 1:3)

# Predict CV values for the same new estimates of counts used above,
# i.e. Y = c(1000, 5000, 10000, 50000, 100000), for all the regions:
# Again, here we can exploit the exception described in section 'Details'
# and avoid building group variables explicitly:

# Predict:
pp.g <- predictCV(mm.g, new.Y)
pp.g

# NOTE: The WARNING above explains the appearance of NaN for some predicted
#       CV values stemming from the third GVF model. The reason causing this
#       behaviour is exactly the same as discussed in previous example (B).

```

```
#####
# Estimating CVs: Prediction vs Direct Calculation #
#####
# Load example data:
data(AF.gvf)

# Fit available registered GVF models for frequencies:
mm <- fit.gvf(ee.AF, model=1:3)

# Get the best fitted model:
mbest <- getBest(mm, criterion="adj.R2")
mbest
# Note: adjusted R^2 used as a 'quick and dirty' criterion, as a thorough model
#       comparison via diagnostic plots would have given the same result.

# Compute directly the estimates and errors of a set of absolute frequencies
# which did not belong to the previously fitted data ee.AF, e.g. the joint
# distribution of marstat and regcod:
marstat.regcod <- svystatTM(exdes, ~I(marstat:regcod))
marstat.regcod

# Predict CVs of the joint distribution of marstat and regcod
# by means of the selected GVF model:
# First, prepare data with which to predict:
newdata <- gvf.input(exdes, marstat.regcod)
# Then, compute CV predictions:
p.marstat.regcod <- predictCV(mbest, new.Y = newdata, interval="prediction")

# Inspect the results:
p.marstat.regcod

# Plot of computed and predicted CVs with prediction error bars:
# plot starts #
plot(p.marstat.regcod$Y, p.marstat.regcod$CV.fit, pch=19, col="red",
     ylim=range(p.marstat.regcod$CV.lwr, p.marstat.regcod$CV.upr, p.marstat.regcod$CV),
     xlab="Absolute Frequency Estimate", ylab="Coefficient of Variation",
     main="Estimated and GVF Predicted CVs\n(joint distribution of marstat and regcod)")
segments(x0=p.marstat.regcod$Y, y0=p.marstat.regcod$CV.lwr, y1=p.marstat.regcod$CV.upr,
         col="red")
points(p.marstat.regcod$Y, p.marstat.regcod$CV, pch=0)
legend("topright", title="CV Estimation Method",
      legend=c("Direct Estimate", "GVF Predicted Value", "GVF Prediction Interval"),
      pch=c(0,19,124), col=c("black", "red", "red"), inset=rep(0.05, 2))
# plot ends #
```

Description

This help page documents the options that control the behaviour of the **ReGenesees** package with respect to standard error estimation.

Details

The **ReGenesees** package provides four options for variance estimations which can be freely set and modified by the user:

- RG.ultimate.cluster
- RG.lonely.psu
- RG.adjust.domain.lonely
- RG.warn.domain.lonely

When `options("RG.ultimate.cluster")` is TRUE, the **ReGenesees** package adopts the so called "*Ultimate Cluster Approximation*" [Kalton 79]. Under this approximation, the overall sampling variance for a multistage sampling design is estimated by taking into account only the contribution arising from the estimated PSU totals (thus simply ignoring any available information about subsequent sampling stages). For without replacement sampling designs, this approach is known to underestimate the true multistage variance, while - at the same time - overestimating its true first-stage component. Anyway, the underestimation error becomes negligible if the PSUs' sampling fractions across strata are very small. When sampling with replacement, the Ultimate Cluster approach is no longer an approximation, but rather an exact result. Hence, `options("RG.ultimate.cluster")` TRUE or FALSE, if one does not specify first-stage finite population corrections, **ReGenesees** will produce exactly the same variance estimates.

When `options("RG.ultimate.cluster")` is FALSE, each sampling stage contributes and variances get estimated by means of a recursive algorithm [Bellhouse, 85] inherited and adapted from package **survey** [Lumley 06]. Notice that the results obtained by choosing this option can differ from the one that would be obtained under the "Ultimate Cluster Approximation" *only if* first-stage finite population corrections are specified.

Lonely PSUs (i.e. PSUs which are alone inside a not self-representing stratum) are a concern from the viewpoint of variance estimation. The suggested **ReGenesees** facility to handle the lonely PSUs problem is the strata aggregation technique (see e.g. [Wolter 07] and [Rust, Kalton 87]) provided in function `collapse.strata`. As a possible alternative, you can get rid of lonely PSUs also by setting proper variance estimation options via `options("RG.lonely.psu")`. The default setting is "fail", which raises an error if a lonely PSU is met. Option "remove" simply causes the software to ignore lonely PSUs for variance computation purposes. Option "adjust" means that deviations from the *population mean* will be used in variance estimation formulae, instead of deviations from the stratum mean (a conservative choice). Finally, option "average" causes the software to replace the variance contribution of the stratum by the average variance contribution across strata (this can be appropriate e.g. when one believes that lonely PSU strata occur at random due to uniform nonresponse among strata).

The variance formulae for domain estimation give well-defined, positive results when a stratum contains only a single PSU with observations falling in the domain, but are not unbiased. If `options("RG.adjust.domain.lonely")` is TRUE and `options("RG.lonely.psu")` is "average" or "adjust" the same adjustment for lonely PSUs will be used within a domain. Note that this adjustment is not available for calibrated designs.

If `options("RG.warn.domain.lonely")` is set to TRUE, a warning message is raised whenever an estimation domain happens to contain just a single PSU belonging to a stratum. The default is FALSE.

References

- Kalton, G. (1979). "*Ultimate cluster sampling*", Journal of the Royal Statistical Society, Series A, 142, pp. 210-222.

Bellhouse, D. R. (1985). "Computing Methods for Variance Estimation in Complex Surveys". Journal of Official Statistics, Vol. 1, No. 3, pp. 323-329.

Lumley, T. (2006) "survey: analysis of complex survey samples", <http://cran.at.r-project.org/web/packages/survey/index.html>.

Wolter, K.M. (2007) "Introduction to Variance Estimation", Second Edition, Springer-Verlag, New York.

Rust, K., Kalton, G. (1987) "Strategies for Collapsing Strata for Variance Estimation", Journal of Official Statistics, Vol. 3, No. 1, pp. 69-81.

See Also

[e.svydesign](#) and its `self.rep.str` argument for a "compromise solution" that can be adopted when the sampling design involves self-representing (SR) strata, [collapse.strata](#) for the suggested way of handling lonely PSUs, and [fpcdat](#) for useful data examples.

Examples

```
# Define a two-stage stratified cluster sampling without
# replacement:
data(fpcdat)
des<-e.svydesign(data=fpcdat,ids=~psu+ssu,strata=~stratum,weights=~w,
  fpc=~fpc1+fpc2)

# Now compare SE (or CV%) sizes under different settings:

## 1) Default setting, i.e. Ultimate Cluster Approximation is off
svystatTM(des,~x+y+z,vartype=c("se","cvpct"))

## 2) Turn on the Ultimate Cluster Approximation, thus missing
##     the variance contribution from the second stage
##     (hence SR strata give no contribution at all):
old.op <- options("RG.ultimate.cluster"=TRUE)
svystatTM(des,~x+y+z,vartype=c("se","cvpct"))
options(old.op)

## 3) The "compromise solution" (see ?e.svydesign) i.e. retaining
##     only the leading contribution to the sampling variance (namely
##     the one arising from SSUs in SR strata and PSUs in not-SR strata):
des2<-e.svydesign(data=fpcdat,ids=~psu+ssu,strata=~stratum,weights=~w,
  fpc=~fpc1+fpc2, self.rep.str=~sr)
svystatTM(des2,~x+y+z,vartype=c("se","cvpct"))

# Therefore, sampling variances come out in the expected
# hierarchy: 1) > 3) > 2).

# Under default settings lonely PSUs produce errors in standard
# errors estimation (notice we didn't pass the fpcs):
data(fpcdat)
des.lpsu<-e.svydesign(data=fpcdat,ids=~psu+ssu,strata=~stratum,
  weights=~w)
## Not run:
svystatTM(des.lpsu,~x+y+z,vartype=c("se","cvpct"))

## End(Not run)
```

```
# This can be circumvented in different ways, namely:
old.op <- options("RG.lonely.psu"="adjust")
svystatTM(des.lpsu,~x+y+z,vartype=c("se","cvpct"))
options(old.op)

# or:
old.op <- options("RG.lonely.psu"="average")
svystatTM(des.lpsu,~x+y+z,vartype=c("se","cvpct"))
options(old.op)

# or otherwise by collapsing strata inside planned
# estimation domains:
des.clps<-collapse.strata(design=des.lpsu,block.vars=~pl.domain)
svystatTM(des.clps,~x+y+z,vartype=c("se","cvpct"))
```

sbs

Artificial Structural Business Statistics Data

Description

The sbs data frame stores artificial sbs-like sampling data, while `sbs.frame` is the artificial sampling frame from which the sbs units have been drawn. They allow to run R code contained in the 'Examples' section of the **ReGenesees** package help pages.

Usage

```
data(sbs)
```

Format

The sbs data frame mimics data observed in a Structural Business Statistics survey, under a one-stage stratified unit sampling design. The sample is made up of 6909 units, for which the following 22 variables were observed:

```
id Identifier of the sampling units (enterprises), numeric
public Does the enterprise belong to the Public Sector? factor with levels 0 (No) and 1 (Yes)
emp.num Number of employees, numeric
emp.c1 Number of employees classified into 5 categories, factor with levels [6,9] (9,19] (19,49]
      (49,99] (99,Inf] (notice that small enterprises with less than 6 employees fell outside the
      scope of the survey)
nace5 Economic Activity code with 5 digits, factor with 596 levels
nace2 Economic Activity code with 2 digits, factor with 57 levels
area Territorial Division, factor with 24 levels
cens Flag identifying statistical units to be censused (hence defining take-all strata), factor with
      levels 0 (No) and 1 (Yes)
region Macroregion, factor with levels North Center South
va.c1 Class of Value Added, factor with 27 levels
va Value Added, numeric (contains NAs)
```


dom1 A planned estimation domain, factor with 261 levels (dom1 crosses nace2 and emp.cl)

nace.macro Economic Activity Macrosector, factor with levels Agriculture Industry Commerce Services

dom2 A planned estimation domain, factor with 12 levels (dom2 crosses nace.macro and region)

strata Stratification Variable, a factor with 664 levels (obtained by crossing variables region, nace2, emp.cl and cens)

va.imp1 Value Added Imputed1, numeric (NAs were replaced with average values computed inside imputation strata obtained by crossing region, nace.macro, emp.cl)

va.imp2 Value Added Imputed2, numeric (NAs were replaced with median values computed inside imputation strata obtained by crossing region, nace.macro, emp.cl)

y A numeric variable correlated with va

weight Direct weights, numeric

fpc Finite Population Corrections (given as sampling fractions inside strata), numeric

ent Convenience numeric variable identically equal to 1 (sometimes useful, e.g. to estimate the total number of enterprises)

dom3 An unplanned estimation domain, factor with 4 levels

The sbs.frame sampling frame (from which sbs units have been drawn) contains 17318 units.

Examples

```
data(sbs)
head(sbs)
str(sbs)
str(sbs.frame)
```

svystat

Compute Many Estimates and Errors in Just a Single Shot

Description

Computes many estimates and errors (e.g. for disparate estimation domains) in just a single shot, primarily to use them in fitting GVF models. Can handle estimators of all kinds.

Usage

```
svystat(design, kind = c("TM", "R", "S", "SR", "B", "Q", "L"),
        by = NULL, group = NULL, forGVF = TRUE,
        combo = -1, ...)

## S3 method for class 'gvf.input.gr'
plot(x, ...)

## S3 method for class 'svystat.gr'
coef(object, ...)
## S3 method for class 'svystat.gr'
SE(object, ...)
## S3 method for class 'svystat.gr'
VAR(object, ...)
```

```
## S3 method for class 'svystat.gr'
cv(object, ...)
## S3 method for class 'svystat.gr'
deff(object, ...)
## S3 method for class 'svystat.gr'
confint(object, ...)
```

Arguments

design	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
kind	character specifying the summary statistics function to call: it may be 'TM' (i.e. <code>svystatTM</code> , the default), 'R' (i.e. <code>svystatR</code>), 'S' (i.e. <code>svystatS</code>), 'SR' (i.e. <code>svystatSR</code>), 'B' (i.e. <code>svystatB</code>), 'Q' (i.e. <code>svystatQ</code>), and 'L' (i.e. <code>svystatL</code>).
by	Formula specifying the variables that define the "estimation domains". If <code>NULL</code> (the default option) estimates refer to the whole population.
group	Formula specifying a partition of the population into "groups": the output will be returned separately for each group. If <code>NULL</code> (the default option) the output is returned as a whole.
forGVF	Select <code>TRUE</code> (the default) if you want to use the output to fit a GVF model. Otherwise, the output will be simply a set of summary statistics objects.
combo	An integer which is only meaningful if <code>by</code> is passed. Requests to compute outputs for all the domains determined by crossing the <code>by</code> variables <i>up to</i> a given order (see 'Details').
...	For function <code>svystat</code> , additional arguments to the summary statistic function implied by <code>kind</code> . Otherwise, further arguments passed to or from other methods.
x	The object of class <code>gvf.input.gr</code> to plot.
object	An object of class <code>svystat.gr</code> containing survey statistics.

Details

This function can compute *all* the summary statistics provided by **ReGenesees**, and is principally meant to return a lot of them in just a single shot.

If `forGVF = TRUE` the output will be ready to feed **ReGenesees** GVF fitting infrastructure, otherwise it will consist simply of a set of summary statistic objects.

Use argument `kind` to specify the summary statistic you need. The default value 'TM' selects function `svystatTM`, which yields Totals and Means. All the arguments needed by the summary statistic function implied by `kind` (e.g. argument `y` for `svystatTM` when `kind = 'TM'`) will be passed on through argument '...'.

As usual in summary statistics, argument `by` can be used to request domain estimates.

The group formula (if any) specifies a way of partitioning the population into groups: the output will be reported separately for each group. In the GVF context, a "*grouped*" output will permit to fit *separate* GVF models inside different groups (and hence to compute separate variance predictions for different groups).

Note that `group` and `by` share identical syntax and semantics as model formulae, despite they have different purposes in function `svystat` (as explained above).

Parameter `combo` is *only* meaningful if `by` is passed. Its purpose is to allow computing estimates and errors simultaneously for many estimation domains.

If the by formula involves n variables, specifying `combo = m` requests to compute outputs for all the domains determined by all the interactions of by variables *up to* order m (with $-1 \leq m \leq n$), as follows:

COMBO	MEANING
<code>m = -1.....</code>	'no combo', i.e. treat 'by' formula as usual (the default);
<code>m = 0.....</code>	'order zero' combination, i.e. just a single domain: the whole population;
<code>m = 1.....</code>	'order zero' plus 'order one' combinations, the latter being all the marginal domains defined by 'by' variables;
<code>m = n.....</code>	combinations of any order, the maximum being the one with all 'by' variables interacting simultaneously.

The plot method can be used *only* when `forGVF = TRUE` and produces a matrix (or many matrices, if group is passed) of scatterplots with polynomial smoothers.

Methods `coef`, `SE`, `VAR`, `cv`, `deff`, and `confint` can be used *only* when `forGVF = FALSE`, to extract estimates and variability statistics.

Value

An object storing estimates and errors, whose detailed structure depends on input parameters' values.

If `forGVF = FALSE`, a set of summary statistics possibly stored into a list (with class `svystat.gr` in the most general case).

If `forGVF = TRUE` and argument `group` is *not* passed, an object of class `gvf.input`.

If `forGVF = TRUE` and argument `group` is passed, an object of class `gvf.input.gr`. This is a list of objects of class `gvf.input`, each one pertaining to a different population group.

Author(s)

Diego Zardetto

See Also

`estimator.kind` to assess what kind of estimates are stored inside a survey statistic object, `gvf.input` as an alternative to prepare the input for GVF model fitting, `GVF.db` to manage **ReGenesees** archive of registered GVF models, `fit.gvf` to fit GVF models, `plot.gvf.fit` to get diagnostic plots for fitted GVF models, `drop.gvf.points` to drop alleged outliers from a fitted GVF model and simultaneously refit it, and `predictCV` to predict CV values via fitted GVF models.

Examples

```
# Load sbs data:
data(sbs)

# Create a design object:
sbsdes<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,fpc=~fpc)

#####
# svystat as an alternative way to compute 'ordinary' summary statistics #
#####
## Total number of employees
```

```

svystat(sbsdes,y=~emp.num,forGVF=FALSE)
# equivalent to:
svystatTM(sbsdes,y=~emp.num)

## Average number of employees per enterprise
svystat(sbsdes,y=~emp.num,estimator="Mean",forGVF=FALSE)
# equivalent to:
svystatTM(sbsdes,y=~emp.num,estimator="Mean")

## Average value added per employee by economic activity macro-sector
## (nace.macro):
svystat(sbsdes,kind="R",num=~va.imp2,den=~emp.num,by=~nace.macro,forGVF=FALSE)
# equivalent to:
svystatR(sbsdes,num=~va.imp2,den=~emp.num,by=~nace.macro)

## Counts of employees by classes of number of employees (emp.cl) crossed
## with economic activity macro-sector (nace.macro):
svystat(sbsdes,y=~emp.num,by=~emp.cl:nace.macro,forGVF=FALSE)
# equivalent to:
svystatTM(sbsdes,y=~emp.num,by=~emp.cl:nace.macro)

## Provided forGVF = FALSE, you can use estimator.kind on svystat output:
stat<-svystat(sbsdes,kind="R",num=~va.imp2,den=~emp.num,by=~emp.cl:nace.macro,
             group=~region,forGVF=FALSE)
stat
estimator.kind(stat,sbsdes)

#####
# Understanding syntax and semantics of argument 'combo' #
#####
# Load household data:
data(data.examples)

# Create a design object:
houdes<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
                  weights=~weight)

# Add convenience variable 'ones' to estimate counts:
houdes<-des.addvars(houdes,ones=1)

## To facilitate understanding, let's for the moment keep forGVF = FALSE.
## Let's use estimates and errors of counts of individuals by sex and
## five age classes (age5c):
svystat(houdes,y=~ones,by=~age5c:sex,forGVF=FALSE)

## Now let's play with argument 'combo':
# combo = -1
# -> 'no combo', i.e. treat 'by' formula as usual
svystat(houdes,y=~ones,by=~age5c:sex,forGVF=FALSE,combo=-1)

# combo = 0
# -> 'order zero' combination, i.e. just a single domain: the whole population
svystat(houdes,y=~ones,by=~age5c:sex,forGVF=FALSE,combo=0)

# combo = 1
# -> 'order zero' plus 'order one' combinations, the latter being all the

```

```

#   marginal domains defined by 'by' variables
svystat(houdes,y=~ones,by=~age5c:sex,forGVF=FALSE,combo=1)

# combo = 2
# -> since 'by' has 2 variables, this means combinations of any order up to
#   the maximum
svystat(houdes,y=~ones,by=~age5c:sex,forGVF=FALSE,combo=2)

# combo = 3
# -> yields an error, as 'combo' cannot exceed the number of 'by' variables
#   (2 in this example)
## Not run:
svystat(houdes,y=~ones,by=~age5c:sex,forGVF=FALSE,combo=3)

## End(Not run)

#####
# svystat as an alternative way to prepare input data for GVF models #
#####
## The same estimates and errors of the last example above, now with
## forGVF = TRUE: note the different output data format
svystat(houdes,y=~ones,by=~age5c:sex,combo=2)

## Note that the agile command above is indeed equivalent to the following
## lengthier, cumbersome statement:
gvf.input(houdes,
          svystatTM(houdes,y=~ones),
          svystatTM(houdes,y=~ones,by=~age5c),
          svystatTM(houdes,y=~ones,by=~sex),
          svystatTM(houdes,y=~ones,by=~age5c:sex)
          )

#####
# Using argument 'group' to prepare input data #
# for separate GVF models #
#####
## The same estimates and errors of the last example above, now prepared
## separately for different regions (regcod):
svystat(houdes,y=~ones,by=~age5c:sex,combo=2,group=~regcod)

## Again the same estimates and errors, prepared separately for groups
## defined crossing marital status (marstat) and region:
svystat(houdes,y=~ones,by=~age5c:sex,combo=2,group=~marstat:regcod)

## NOTE: Output has class "gvf.input.gr". This will tell ReGenesees' GVF
##       fitting facilities to handle estimates and errors pertaining to
##       different groups independently of each other.

## NOTE: Parameter combo allows svystat to gather a huge amount of estimates and
##       errors in just a single slot, as the number of estimation domains grows
##       exponentially with the number of by variables.
##       See, for instance, the following example:
out <- svystat(houdes,y=~ones,by=~age5c:marstat:sex:regcod,combo=4)
dim(out)

```

```

head(out)
plot(out)

#####
# Minor details: accessor functions and plotting #
#####
## Accessor functions work only when forGVF = FALSE
# Average value added per employee by nace.macro:
out <- svystat(sbsdes,kind="R",num=~va.imp2,den=~emp.num,by=~nace.macro,forGVF=FALSE)
out
# Access CV values and confidence intervals:
cv(out)
confint(out)

# The same as above, separately for regions:
out <- svystat(sbsdes,kind="R",num=~va.imp2,den=~emp.num,by=~nace.macro,group=~region,forGVF=FALSE)
out
# Access CV values and confidence intervals:
cv(out)
confint(out)

## Plot function works only when forGVF = TRUE
# Counts of individuals by sex, marstat and age5c, and all their interactions:
out <- svystat(houdes,y=~ones,by=~age5c:marstat:sex,combo=3)
# Plot GVF input:
plot(out)

# The same as above, grouped by region:
out <- svystat(houdes,y=~ones,by=~age5c:marstat:sex,combo=3,group=~regcod)
# Plot GVF inputs, separately by groups (regions):
plot(out)

```

svystatB

Estimation of Population Regression Coefficients

Description

Computes estimates, standard errors and confidence intervals for Multiple Regression Coefficients.

Usage

```

svystatB(design, model,
         vartype = c("se", "cv", "cvpct", "var"),
         conf.int = FALSE, conf.lev = 0.95, deff = FALSE,
         na.rm = FALSE)

## S3 method for class 'svystatB'
coef(object, ...)
## S3 method for class 'svystatB'
SE(object, ...)
## S3 method for class 'svystatB'
VAR(object, ...)

```

```
## S3 method for class 'svyestatB'
cv(object, ...)
## S3 method for class 'svyestatB'
deff(object, ...)
## S3 method for class 'svyestatB'
confint(object, ...)
## S3 method for class 'svyestatB'
summary(object, ...)
```

Arguments

<code>design</code>	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
<code>model</code>	Formula specifying the linear model whose coefficients have to be estimated.
<code>vartype</code>	character vector specifying the desired variability estimators. It is possible to choose one or more of: standard error ('se', the default), coefficient of variation ('cv'), percent coefficient of variation ('cvpct'), or variance ('var').
<code>conf.int</code>	Compute confidence intervals for the estimates? The default is FALSE.
<code>conf.lev</code>	Probability specifying the desired confidence level: the default value is 0.95.
<code>deff</code>	Should the design effect be computed? The default is FALSE (see 'Details').
<code>na.rm</code>	Should missing values (if any) be removed from the variables of interest? The default is FALSE (see 'Details').
<code>object</code>	An object of class <code>svyestatB</code> .
<code>...</code>	Additional arguments to <code>coef</code> , <code>...</code> , <code>confint</code> methods (if any).

Details

This function computes weighted estimates for Multiple Regression Coefficients using suitable weights depending on the class of `design`: calibrated weights for class `cal.analytic` and direct weights otherwise. Standard errors are calculated using the Taylor linearization technique.

The mandatory argument `model` identifies the regression model whose population coefficients have to be estimated (for details on model specification, see e.g. [lm](#)). The design variables referenced by `model` should be numeric or factor (variables of other types - e.g. character - will be coerced).

The `conf.int` argument allows to request the confidence intervals for the estimates. By default `conf.int=FALSE`, that is the confidence intervals are not provided.

Whenever confidence intervals are requested (i.e. `conf.int=TRUE`), the desired confidence level can be specified by means of the `conf.lev` argument. The `conf.lev` value must represent a probability ($0 \leq \text{conf.lev} \leq 1$) and its default is chosen to be 0.95.

The optional argument `deff` allows to request the design effect [Kish 1995] for the estimates. By default `deff=FALSE`, that is the design effect is not provided. The design effect of an estimator is defined as the ratio between the variance of the estimator under the actual sampling design and the variance that would be obtained for an 'equivalent' estimator under a hypothetical simple random sampling without replacement of the same size. To obtain an estimate of the design effect comparing to simple random sampling "*with replacement*", one must use `deff="replace"`.

For nonlinear estimators, the design effect is estimated on the linearized version of the estimator (that is for the estimator of the total of the linearized variable, aka "Woodruff transform").

When dealing with domain estimation, the design effects referring to a given subpopulation are currently computed by taking the ratios between the actual variance estimates and those that would have been obtained if a simple random sampling were carried out *within* that subpopulation. This is the same as the `srssubpop` option for Stata's function `estat`.

Missing values (NA) in model variables should be avoided. If `na.rm=FALSE` (the default) they generate an error. If `na.rm=TRUE`, observations containing NAs in model variables are dropped, and estimates gets computed on non missing values only. This implicitly assumes that missing values hit interest variables *completely at random*: should this be not the case, computed estimates would be *biased*.

The summary method invoked on regression coefficients (say `b`) estimated via `svystatB`, gives p-values and significance codes for the component-wise test $b = 0$. Such values are computed assuming that the distribution of the regression coefficients estimators is normal (which is asymptotically true for large scale surveys). This assumption has the advantage of overcoming the problem of choosing the "right" statistic and assessing its "right" number of degrees of freedom when using data from a complex survey (see e.g. [Korn, Graubard 1990]).

Value

An object inheriting from the `data.frame` class, whose detailed structure depends on input parameters' values.

Author(s)

Diego Zardetto

References

- Sarndal, C.E., Swensson, B., Wretman, J. (1992) *"Model Assisted Survey Sampling"*, Springer Verlag.
- Kish, L. (1995). *"Methods for design effects"*. Journal of Official Statistics, Vol. 11, pp. 55-77.
- Korn, E.L., Graubard, B.I. (1990) *"Simultaneous testing of regression coefficients with complex survey data: Use of Bonferroni t statistics"*. The American Statistician, 44, 270-276.

See Also

Estimators of Totals and Means [svystatTM](#), Ratios between Totals [svystatR](#), Shares [svystatS](#), Ratios between Shares [svystatSR](#), Quantiles [svystatQ](#), Complex Analytic Functions of Totals and/or Means [svystatL](#), and all of the above [svystat](#).

Examples

```
#####
# A simple regression model with a single predictor. #
# Let's compare the estimated regression coefficient #
# to its true value computed on the sampling frame. #
#####

# Load sbs data:
data(sbs)

# Create a design object:
sbsdes<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,
                    fpc=~fpc)

# The population scatterplot of y vs emp.num reveals a linear
# behaviour:
plot(sbs.frame$emp.num,sbs.frame$y,
      col=rgb(50,205,50,100,maxColorValue=255),pch=16)
```



```

# Compute the population fit of the linear regression
# model y~emp.num-1 (no intercept):
pop.fit<-lm(y~emp.num-1,data=sbs.frame)
abline(pop.fit,col="red",lwd=2,lty=2)

# The obtained population R-squared is quite significant
# (greater than 0.7):
pop.R2<-summary(pop.fit)$r.squared
pop.R2

# The population regression coefficient is:
B<-coef(pop.fit)
B

# Now let's estimate B on the basis of the sbs sample and
# let's build a 95% confidence interval for the obtained estimate:
svystatB(sbsdes,y~emp.num-1,conf.int=TRUE)

# Thus, the confidence interval covers the true value of B.

# Notice that using ReGenesee's Complex Estimators function
# svystatL, you would have obtained exactly the same results:
sbsdes<-des.addvars(sbsdes,y4emp.num=y*emp.num,
                    emp.num.sq=emp.num^2)
svystatL(sbsdes,expression(y4emp.num/emp.num.sq),
          conf.int=TRUE)

#####
# A multiple regression example. #
#####

# Let's estimate the coefficients of a model describing
# value added (variable va.imp2) as a linear function
# of number of employees by region and of nace.macro:
b <- svystatB(sbsdes,va.imp2~emp.num:region+nace.macro,vartype="cvpct")
b

# To obtain p-values and significance codes for the
# component-wise test  $t=0$ , you can exploit the
# summary method:
summary(b)

# Notice that estimators normality is assumed.

#####
# Obtaining domain means via regression. #
#####

# The domain mean of a numeric variable can be thought
# as a regression coefficient. Suppose you need the
# average number of employees by macro-sector, you can
# do as follows:
svystatB(sbsdes,emp.num~nace.macro-1)

```

```

# ...which, indeed, gives exactly the same results of:
svystatTM(sbsdes,y=~emp.num,by=~nace.macro,estimator="Mean")

#####
# Handling collinearity. #
#####

# Function svystatB overcomes problems arising from exact
# collinearity between model variables via 'aliasing'.
# To understand how aliasing works, let's build a manifestly
# redundant linear model:
svystatB(sbsdes,y~emp.num+I(2*emp.num)+I(3*va.imp2)+va.imp2-1)

# The obtained warning message shows that order definitely matters
# in aliasing, indeed:
svystatB(sbsdes,y~emp.num+I(2*emp.num)+va.imp2+I(3*va.imp2)-1)

# Notice also that aliasing gives exact estimates and standard errors
# for non-aliased regression coefficients (i.e. the same results that
# would be obtained with a reduced - no collinearity - model):
svystatB(sbsdes,y~emp.num+va.imp2-1)

#####
# Handling missing values in model variables. #
#####

# Load fpcdat:
data(fpcdat)

# Now, let's introduce some NAs in survey data:
fpcdat$y[c(1,3)]<-NA
fpcdat$x[c(3,5)]<-NA

# Create a design object:
fpcdes<-e.svydesign(data=fpcdat,ids=~psu+ssu,strata=~stratum,weights=~w,
  fpc=~fpc1+fpc2)

# Let's estimate regression coefficients of model z~y+x
# na.rm=FALSE (the default) leads to an error:
## Not run:
svystatB(fpcdes,z~y+x)

## End(Not run)

# whereas na.rm=TRUE simply drops all the cases
# with missing data in model variables:
svystatB(fpcdes,z~y+x,na.rm=TRUE)

#####
# Handling non positive weights. #
#####

# Non positive direct weights are not allowed, anyway some
# calibrated weights can sometimes turn out to be <= 0. The

```

```
# corresponding observations would be dropped by svystatB.

# Prepare a template for population totals:
pop<-pop.template(fpcdes,~z+pl.domain-1)

# Fill it with silly values in order to obtain some negative g-weights:
pop[1,]<-c(20000,90,10,90)

# Calibrate:
fpccal<-e.calibrate(fpcdes,pop)

# We got 2 negative calibrated weights:
g.range(fpccal)
sum(weights(fpccal)<=0)

# Now, let's estimate regression coefficients of model z~y+x
# and pay attention to the warnings:
svystatB(fpccal,z~y+x,na.rm=TRUE)
```

svystatL

Estimation of Complex Estimators in Subpopulations

Description

Computes estimates, standard errors and confidence intervals for Complex Estimators in subpopulations. A Complex Estimator can be any analytic function of (Horvitz-Thompson or Calibration) estimators of Totals and Means.

Usage

```
svystatL(design, expr, by = NULL,
         vartype = c("se", "cv", "cvpct", "var"),
         conf.int = FALSE, conf.lev = 0.95, deff = FALSE,
         na.rm = FALSE)
```

```
## S3 method for class 'svystatL'
coef(object, ...)
## S3 method for class 'svystatL'
SE(object, ...)
## S3 method for class 'svystatL'
VAR(object, ...)
## S3 method for class 'svystatL'
cv(object, ...)
## S3 method for class 'svystatL'
deff(object, ...)
## S3 method for class 'svystatL'
confint(object, ...)
```

Arguments

design	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
--------	--

<code>expr</code>	R expression defining the Complex Estimator (see ‘Details’).
<code>by</code>	Formula specifying the variables that define the "estimation domains". If NULL (the default option) estimates refer to the whole population.
<code>vartype</code>	character vector specifying the desired variability estimators. It is possible to choose one or more of: standard error (<code>'se'</code> , the default), coefficient of variation (<code>'cv'</code>), percent coefficient of variation (<code>'cvpct'</code>), or variance (<code>'var'</code>).
<code>conf.int</code>	Compute confidence intervals for the estimates? The default is FALSE.
<code>conf.lev</code>	Probability specifying the desired confidence level: the default value is 0.95.
<code>deff</code>	Should the design effect be computed? The default is FALSE (see ‘Details’).
<code>na.rm</code>	Should missing values (if any) be removed from the variables of interest? The default is FALSE (see ‘Details’).
<code>object</code>	An object of class <code>svystatL</code> .
<code>...</code>	Additional arguments to <code>coef</code> , ..., <code>confint</code> methods (if any).

Details

This function computes weighted estimates for Complex Estimators using suitable weights depending on the class of design: calibrated weights for class `cal.analytic` and direct weights otherwise. Standard errors are calculated using the Taylor linearization technique.

The mandatory argument `expr`, which identifies the Complex Estimator, must be an object of class `expression`. It can be specified just a single Complex Estimator at a time, i.e. `length(expr)` must be equal to 1. Any analytic function of estimators of Totals and Means is allowed.

Inside `expr` the estimator of the Total of a variable is simply represented by the *name* of the variable itself. To represent the estimator of the Mean of a variable `y`, the expression `y/ones` has to be used (ones being the convenience name of an artificial variable whose value is 1 for each sampling unit, so that its Total estimator actually estimates the population total). Variables referenced inside `expr` have obviously to belong to design and must be `numeric`.

At a minimal level, `svystatL` can be used to estimate Totals, Means and Ratios, thus reproducing the same results achieved by using the corresponding dedicated functions `svystatTM` and `svystatR`. For instance, calling `svystatL(design, expression(y/x))` is equivalent to invoking `svystatR(design, ~y, ~x)`, while using `svystatL(design, expression(y/ones))` or `svystatTM(design, ~y, estimator = "Mean")` achieves an identical result.

The mathematical expression of a Complex Estimator, as specified by argument `expr`, can involve ‘parameters’, that is *symbols* representing given, non-random, scalar, numeric *values*. For each parameter appearing in `expr`, the value corresponding to its symbol will be searched following R standard scoping rules, see e.g. the first example in Section ‘Examples’ for a practical illustration.

The optional argument `by` specifies the variables that define the "estimation domains", that is the subpopulations for which the estimates are to be calculated. If `by=NULL` (the default option), the estimates produced by `svystatL` refer to the whole population. Estimation domains must be defined by a formula: for example the statement `by=~B1:B2` selects as estimation domains the subpopulations determined by crossing the modalities of variables `B1` and `B2`. Notice that a formula like `by=~B1+B2` will be automatically translated into the factor-crossing formula `by=~B1:B2`: if you need to compute estimates for domains `B1` and `B2` *separately*, you have to call `svystatL` twice. The design variables referenced by `by` (if any) should be of type `factor`, otherwise they will be coerced.

The `conf.int` argument allows to request the confidence intervals for the estimates. By default `conf.int=FALSE`, that is the confidence intervals are not provided.

Whenever confidence intervals are requested (i.e. `conf.int=TRUE`), the desired confidence level can be specified by means of the `conf.lev` argument. The `conf.lev` value must represent a probability ($0 \leq \text{conf.lev} \leq 1$) and its default is chosen to be 0.95.

The optional argument `deff` allows to request the design effect [Kish 1995] for the estimates. By default `deff=FALSE`, that is the design effect is not provided. The design effect of an estimator is defined as the ratio between the variance of the estimator under the actual sampling design and the variance that would be obtained for an 'equivalent' estimator under a hypothetical simple random sampling without replacement of the same size. To obtain an estimate of the design effect comparing to simple random sampling "*with replacement*", one must use `deff="replace"`.

For nonlinear estimators, the design effect is estimated on the linearized version of the estimator (that is for the estimator of the total of the linearized variable, aka "Woodruff transform").

When dealing with domain estimation, the design effects referring to a given subpopulation are currently computed by taking the ratios between the actual variance estimates and those that would have been obtained if a simple random sampling were carried out *within* that subpopulation. This is the same as the `srssubpop` option for Stata's function `estat`.

Missing values (NA) in interest variables should be avoided. If `na.rm=FALSE` (the default) they generate NAs in estimates (or even an error, if design is calibrated). If `na.rm=TRUE`, observations containing NAs are dropped, and estimates gets computed on non missing values only. This implicitly assumes that missing values hit interest variables *completely at random*: should this be not the case, computed estimates would be *biased*.

Value

An object inheriting from the `data.frame` class, whose detailed structure depends on input parameters' values.

Warning

When the linearized variable corresponding to a Complex Estimator is ill defined (because the estimator gradient is singular at the Taylor series expansion point), SE estimates returned by `svystatL` are NaN.

Author(s)

Diego Zardetto

References

Sarndal, C.E., Swensson, B., Wretman, J. (1992) "*Model Assisted Survey Sampling*", Springer Verlag.

Kish, L. (1995). "*Methods for design effects*". Journal of Official Statistics, Vol. 11, pp. 55-77.

See Also

Estimators of Totals and Means [svystatTM](#), Ratios between Totals [svystatR](#), Shares [svystatS](#), Ratios between Shares [svystatSR](#), Multiple Regression Coefficients [svystatB](#), Quantiles [svystatQ](#), and all of the above [svystat](#).

Examples

```
#####
# A first example: the Ratio Estimator of a Total. #
#####

# Creation of a design object:
data(data.examples)
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
```

```

weights=~weight)

# Recall that ratio estimators of Totals rely on auxiliary
# information. Thus, suppose you want to estimate the total
# of income and suppose you know from an external source that
# the population size is, say, 1E6:
pop <- 1E6

# To obtain the ratio estimator of total income, you can do as follows:
## A) Directly plug the numeric value of pop into expr
svystatL(des, expression(1E6 * (income/ones)), vartype = "cvpct")

## B) Treat pop as a parameter and let R find its actual value (1E6) inside
## the calling environment of svystatL (the .GlobalEnv)
svystatL(des, expression(pop * (income/ones)), vartype = "cvpct")

# NOTE: Method B) can be very useful for simulation purposes, as it avoids
# having to directly type in numbers when invoking svystatL (something
# that only a human in an interactive R session could do).

# By comparing the latter result with the ordinary estimator of the mean...
svystatTM(des, ~income, vartype="cvpct")

# ...one can appreciate the variance reduction stemming from the correlation
# between numerator and denominator:
Corr(des, expression(income), expression(ones))

#####
# A complex example: estimation of the Population Standard #
# Deviation of a variable. #
#####

# Creation of another design object:
data(sbs)
sbsdes<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,
fpc=~fpc)

# Suppose you want to estimate the standard deviation of the
# population distribution of value added (va.imp2):
sbsdes<-des.addvars(sbsdes,va.imp2.sq=va.imp2^2)
svystatL(sbsdes,expression( sqrt( (ones/(ones-1))*
( (va.imp2.sq/ones)-(va.imp2/ones)^2 )
)
), conf.int=TRUE)

# The estimate above and the associated confidence interval (which
# involves the estimate of the sampling variance of the complex
# estimator) turn out to be very sound: indeed the TRUE value of the
# parameter is:
sd(sbs.frame$va.imp2)

#####
# Estimation of Geometric and Harmonic Means. #
#####

```

```

## 1. Harmonic Mean
# Recall that the the harmonic mean of a positive variable,
# say z, can be computed as 1/mean(1/z). Thus, for instance,
# to get a survey estimate of the harmonic mean of emp.num,
# you can do as follows:
sbsdes<-des.addvars(sbsdes,emp.num.m1=1/emp.num)
h<-svystatL(sbsdes,expression( ones/emp.num.m1 ),
            conf.int=TRUE)
h

# You can easily verify that the obtained estimate is close
# to the true value (as computed from the sampling frame) and
# covered by the 95% confidence interval:
1/mean(1/sbs.frame$emp.num)

## 2. Geometric Mean
# Recall that the the geometric mean of a non negative variable,
# say z, can be computed as exp(mean(log(z))). Thus, for instance,
# to get a survey estimate of the geometric mean of emp.num,
# you can do as follows:
sbsdes<-des.addvars(sbsdes,log.emp.num=log(emp.num))
g<-svystatL(sbsdes,expression( exp(log.emp.num/ones) ),
            conf.int=TRUE)
g

# You can easily verify that the obtained estimate is close
# to the true value (as computed from the sampling frame) and
# covered by the 95% confidence interval:
exp(mean(log(sbs.frame$emp.num)))

## 3. Comparison with the arithmetic mean
# If you compute the arithmetic mean estimate:
a<-svystatTM(sbsdes,~emp.num,estimator="Mean")
a

#...you easily verify the expected hierachy,
# i.e. harmonic <= geometric <= arithmetic:
H<-coef(h)
G<-coef(g)
A<-coef(a)
stopifnot(H <= G && G <= A)

#####
# Further complex examples: estimation of Population Regression #
# Coefficients (for a model with a single predictor).          #
#####

# Suppose you want to estimate of the slope of the population
# regression y vs. emp.num. You can do as follows:

## 1. No intercept model: y ~ emp.num - 1
# Get survey estimate:
sbsdes<-des.addvars(sbsdes,y4emp.num=y*emp.num,
                    emp.num.sq=emp.num^2)
svystatL(sbsdes,expression(y4emp.num/emp.num.sq),
        conf.int=TRUE)

```

```

# Compare with the actual slope from the population fit:
pop.fit<-lm(y~emp.num-1,data=sbs.frame)
coef(pop.fit)

# ...a very good agreement.

## 2. The model with intercept: y ~ emp.num
# Get survey estimate:
svystatL(sbsdes,expression( (ones*y4emp.num - y*emp.num)/
                             (ones*emp.num.sq - emp.num^2)
                             ),
          conf.int=TRUE)

# Compare with the actual slope from the population fit:
pop.fit<-lm(y~emp.num,data=sbs.frame)
coef(pop.fit)

# ...again a very good agreement.

# Notice that both results above could be obtained also
# by using ReGenesees specialized function svystatB:

## 1.
svystatB(sbsdes,y~emp.num-1,conf.int=TRUE)

## 2.
svystatB(sbsdes,y~emp.num,conf.int=TRUE)

# Notice also - incidentally - that the estimate of the intercept
# turns out to be less accurate than the one we obtained for the slope,
# with about a 6% overestimation.

```

svystatQ

Estimation of Quantiles in Subpopulations

Description

Calculates estimates, standard errors and confidence intervals for Quantiles of numeric variables in subpopulations.

Usage

```

svystatQ(design, y, probs = c(0.25, 0.5, 0.75), by = NULL,
          vartype = c("se", "cv", "cvpct", "var"),
          conf.lev = 0.95, na.rm = FALSE,
          ties=c("discrete", "rounded"))

## S3 method for class 'svystatQ'
coef(object, ...)
## S3 method for class 'svystatQ'
SE(object, ...)
## S3 method for class 'svystatQ'
VAR(object, ...)

```



```
## S3 method for class 'svystatQ'
cv(object, ...)
## S3 method for class 'svystatQ'
confint(object, ...)
```

Arguments

<code>design</code>	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
<code>y</code>	Formula defining the interest variable.
<code>probs</code>	Vector of probability values to be used to calculate the quantiles estimates. The default value selects estimates of quartiles.
<code>by</code>	Formula specifying the variables that define the "estimation domains". If <code>NULL</code> (the default option) estimates refer to the whole population.
<code>vartype</code>	character vector specifying the desired variability estimators. It is possible to choose one or more of: standard error (<code>'se'</code> , the default), coefficient of variation (<code>'cv'</code>), percent coefficient of variation (<code>'cvpct'</code>), or variance (<code>'var'</code>).
<code>conf.lev</code>	Probability specifying the desired confidence level: the default value is 0.95.
<code>na.rm</code>	Should missing values (if any) be removed from the variable of interest? The default is <code>FALSE</code> (see 'Details').
<code>ties</code>	How should duplicated observed values be treated? Select <code>'discrete'</code> for a genuinely discrete interest variable and <code>'rounded'</code> for a continuous one.
<code>object</code>	An object of class <code>svystatQ</code> .
<code>...</code>	Additional arguments to <code>coef</code> , ..., <code>confint</code> methods (if any).

Details

This function calculates weighted estimates for the Quantiles of a quantitative variable using suitable weights depending on the class of design: calibrated weights for class `cal.analytic` and direct weights otherwise.

Standard errors are calculated using the so-called "Woodruff method" [Woodruff 52][Sarndal, Swensson, Wretman 92]: (i) first a confidence interval (at a given confidence level $1-\alpha$) is constructed for the relative frequency of units with values below the estimated quantile, (ii) then the inverse of the estimated cumulative relative frequency distribution (ECDF) is used to map this interval to a confidence interval for the quantile, (iii) lastly the desired standard error is estimated by dividing the length of the obtained confidence interval by the value $2 \cdot qnorm(1-\alpha/2)$. Notice that the procedure above builds, in general, asymmetric confidence intervals around the estimated quantiles.

The mandatory argument `y` identifies the variable of interest, that is the variable for which estimates of quantiles have to be calculated. The design variable referenced by `y` must be numeric.

The optional argument `probs` specifies the probability values ($0.001 \leq probs[i] \leq 0.999$) corresponding to the quantiles one wants to estimate; the default option selects quartiles.

The optional argument `by` specifies the variables that define the "estimation domains", that is the subpopulations for which the estimates are to be calculated. If `by=NULL` (the default option), the estimates produced by `svystatTM` refer to the whole population. Estimation domains must be defined by a formula: for example the statement `by=~B1:B2` selects as estimation domains the subpopulations determined by crossing the modalities of variables `B1` and `B2`. Notice that a formula like `by=~B1+B2` will be automatically translated into the factor-crossing formula `by=~B1:B2`: if you need to compute estimates for domains `B1` and `B2` *separately*, you have to call `svystatQ` twice.

The design variables referenced by `by` (if any) should be of type factor, otherwise they will be coerced.

The `conf.int` argument allows to request the confidence intervals for the estimates. By default `conf.int=FALSE`, that is the confidence intervals are not provided.

Whenever confidence intervals are requested (i.e. `conf.int=TRUE`), the desired confidence level can be specified by means of the `conf.lev` argument. The `conf.lev` value must represent a probability ($0 \leq \text{conf.lev} \leq 1$) and its default is chosen to be 0.95.

Missing values (NA) in interest variables should be avoided. If `na.rm=FALSE` (the default) they generate NAs in estimates (or even an error, if design is calibrated). If `na.rm=TRUE`, observations containing NAs are dropped, and estimates gets computed on non missing values only. This implicitly assumes that missing values hit interest variables *completely at random*: should this be not the case, computed estimates would be *biased*.

Argument `ties` addresses the problem of how to treat duplicated observed values (if any) when computing the ECDF. Option 'discrete' (the default) is appropriate when the variable of interest is genuinely discrete, while 'rounded' is a better choice for a continuous variable, i.e. when duplicates stem from rounding. In the first case the ECDF will show a vertical step corresponding to a duplicated value, in the second a smoother shape will be achieved by linear interpolation.

Value

An object inheriting from the `data.frame` class, whose detailed structure depends on input parameters' values.

Author(s)

Diego Zardetto

References

Woodruff, R.S. (1952) *"Confidence Intervals for Medians and Other Position Measures"*, Journal of the American Statistical Association, Vol. 47, No. 260, pp. 635-646.

Sarndal, C.E., Swensson, B., Wretman, J. (1992) *"Model Assisted Survey Sampling"*, Springer Verlag.

See Also

Estimators of Totals and Means [svystatTM](#), Ratios between Totals [svystatR](#), Shares [svystatS](#), Ratios between Shares [svystatSR](#), Multiple Regression Coefficients [svystatB](#), Complex Analytic Functions of Totals and/or Means [svystatL](#), and all of the above [svystat](#).

Examples

```
# Creation of a design object:
data(data.examples)
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
  weights=~weight)

# Estimate of the deciles of the income variable for
# the whole population:
svystatQ(des,~income,probs=seq(0.1,0.9,0.1),ties="rounded")

# Another design object:
```

```

data(sbs)
des<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,
  fpc=~fpc)

# Estimation of the median value added
# for economic activity macro-sectors:
svystatQ(des,~va.imp2,probs=0.5,by=~nace.macro,
  ties="rounded",vartype="cvpct")

# Estimation of the Interquartile Range (IQR) of the number
# of employees for economic activity macro-sectors:
apply(svystatQ(des,~emp.num,probs=c(0.25,0.75),by=~nace.macro)[,2:3],1,diff)

```

svystatR

*Estimation of Ratios in Subpopulations***Description**

Calculates estimates, standard errors and confidence intervals for Ratios between Totals in subpopulations.

Usage

```

svystatR(design, num, den, by = NULL, cross = FALSE,
  vartype = c("se", "cv", "cvpct", "var"),
  conf.int = FALSE, conf.lev = 0.95, deff = FALSE,
  na.rm = FALSE)

```

```

## S3 method for class 'svystatR'
coef(object, ...)
## S3 method for class 'svystatR'
SE(object, ...)
## S3 method for class 'svystatR'
VAR(object, ...)
## S3 method for class 'svystatR'
cv(object, ...)
## S3 method for class 'svystatR'
deff(object, ...)
## S3 method for class 'svystatR'
confint(object, ...)

```

Arguments

design	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
num	Formula defining the numerator variables for the ratios.
den	Formula defining the denominator variables for the ratios.
by	Formula specifying the variables that define the "estimation domains". If <code>NULL</code> (the default option) estimates refer to the whole population.
cross	Should ratios be estimated for all the pairs of variables in 'num' and 'den'? The default is <code>FALSE</code> , meaning that ratios get estimated parallel-wise (see 'Details').

<code>vartype</code>	character vector specifying the desired variability estimators. It is possible to choose one or more of: standard error (<code>'se'</code> , the default), coefficient of variation (<code>'cv'</code>), percent coefficient of variation (<code>'cvpct'</code>), or variance (<code>'var'</code>).
<code>conf.int</code>	Compute confidence intervals for the estimates? The default is FALSE.
<code>conf.lev</code>	Probability specifying the desired confidence level: the default value is 0.95.
<code>deff</code>	Should the design effect be computed? The default is FALSE (see 'Details').
<code>na.rm</code>	Should missing values (if any) be removed from the variables of interest? The default is FALSE (see 'Details').
<code>object</code>	An object of class <code>svystatR</code> .
<code>...</code>	Additional arguments to <code>coef</code> , <code>...</code> , <code>confint</code> methods (if any).

Details

This function computes weighted estimates for Ratios between Totals using suitable weights depending on the class of design: calibrated weights for class `cal.analytic` and direct weights otherwise. Standard errors are calculated using the Taylor linearization technique.

The mandatory argument `num` (`den`) identifies the variables whose totals appear as numerators (denominators) in the Ratios: the corresponding formula must be of the type $\text{num} = \sim \text{num}.1 + \dots + \text{num}.k$ ($\text{den} = \sim \text{den}.1 + \dots + \text{den}.l$). The design variables referenced by `num` (`den`) must be numeric.

If `cross=TRUE`, the function computes estimates for *all* the Ratios between pairs of variables coming from `num` and `den` (that is $k \times l$ estimates for the formulae above). If, on the contrary, `cross=FALSE` (the default), Ratios get estimated parallel-wise and R recycling rule is applied whenever $k \neq l$: for the formulae above, this generates r Ratios, where $r = \max(k, l)$.

The optional argument `by` specifies the variables that define the "estimation domains", that is the subpopulations for which the estimates are to be calculated. If `by=NULL` (the default option), the estimates produced by `svystatR` refer to the whole population. Estimation domains must be defined by a formula: for example the statement `by=~B1:B2` selects as estimation domains the subpopulations determined by crossing the modalities of variables `B1` and `B2`. Notice that a formula like `by=~B1+B2` will be automatically translated into the factor-crossing formula `by=~B1:B2`: if you need to compute estimates for domains `B1` and `B2` *separately*, you have to call `svystatR` twice. The design variables referenced by `by` (if any) should be of type `factor`, otherwise they will be coerced.

The `conf.int` argument allows to request the confidence intervals for the estimates. By default `conf.int=FALSE`, that is the confidence intervals are not provided.

Whenever confidence intervals are requested (i.e. `conf.int=TRUE`), the desired confidence level can be specified by means of the `conf.lev` argument. The `conf.lev` value must represent a probability ($0 \leq \text{conf.lev} \leq 1$) and its default is chosen to be 0.95.

The optional argument `deff` allows to request the design effect [Kish 1995] for the estimates. By default `deff=FALSE`, that is the design effect is not provided. The design effect of an estimator is defined as the ratio between the variance of the estimator under the actual sampling design and the variance that would be obtained for an 'equivalent' estimator under a hypothetical simple random sampling without replacement of the same size. To obtain an estimate of the design effect comparing to simple random sampling "*with replacement*", one must use `deff="replace"`.

Being Ratios nonlinear estimators, the design effect is estimated on the linearized version of the estimator (that is: for the estimator of the total of the linearized variable, aka "Woodruff transform"). When dealing with domain estimation, the design effects referring to a given subpopulation are currently computed by taking the ratios between the actual variance estimates and those that would have been obtained if a simple random sampling were carried out *within* that subpopulation. This is the same as the `srssubpop` option for Stata's function `estat`.

Missing values (NA) in interest variables should be avoided. If `na.rm=FALSE` (the default) they generate NAs in estimates (or even an error, if design is calibrated). If `na.rm=TRUE`, observations containing NAs are dropped, and estimates gets computed on non missing values only. This implicitly assumes that missing values hit interest variables *completely at random*: should this be not the case, computed estimates would be *biased*. Notice that the `na.rm=TRUE` option is only allowed for a single Ratio, i.e. if `num` and `den` reference a *single* interest variable.

Value

An object inheriting from the `data.frame` class, whose detailed structure depends on input parameters' values.

Warning

It can happen that, in some subpopulations, the estimate of the Total of some `den` variables turns out to be zero. In such cases `svystatR` estimates are either `NaN` or `Inf`, and `NaN` is returned for the corresponding SE estimates.

Author(s)

Diego Zardetto

References

- Sarndal, C.E., Swensson, B., Wretman, J. (1992) *"Model Assisted Survey Sampling"*, Springer Verlag.
- Kish, L. (1995). *"Methods for design effects"*. Journal of Official Statistics, Vol. 11, pp. 55-77.

See Also

Estimators of Totals and Means [svystatTM](#), Shares [svystatS](#), Ratios between Shares [svystatSR](#), Multiple Regression Coefficients [svystatB](#), Quantiles [svystatQ](#), Complex Analytic Functions of Totals and/or Means [svystatL](#), and all of the above [svystat](#).

Examples

```
# Creation of a design object:
data(sbs)
des<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,
  fpc=~fpc)

# Estimation of the average value added per employee
# at the nation level:
svystatR(des,~va.imp2,~emp.num)

# The same as above by economic activity macro-sector:
svystatR(des,~va.imp2,~emp.num,~nace.macro,vartype="cvpct")

# Another design object:
data(data.examples)
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
  weights=~weight)

# Estimation of the ratios y1/x1, y1/x2, y2/x1 and y2/x2 by region,
```

```

# notice the use of argument cross:
svystatR(des,~y1+y2,~x1+x2,by=~regcod,cross=TRUE)

# ... compare the latter with the default (i.e. cross=FALSE)
svystatR(des,~y1+y2,~x1+x2,by=~regcod)

# Estimation of the ratios z/x1, z/x2 e z/x3
# for the whole population (notice the recycling rule):
svystatR(des,~z,~x1+x2+x3,conf.int=TRUE)

# Estimators of means can be thought as
# estimators of ratios:
svystatTM(des,~income,estimator="Mean")
svystatR(des.addvars(des,ones=1),num=~income,den=~ones)

#####
# Household-level averages in household surveys. #
#####

# For an introduction on this topic, see ?svystatTM examples.

# Load survey data:
data(data.examples)

# Define the survey design (variable famcod identifies households)
exdes<-e.svydesign(data=example,ids=~towcod+famcod,strata=~stratum,
  weights=~weight)

# Collapse strata to eliminate lonely PSUs
exdes<-collapse.strata(design=exdes,block.vars=~sr:procod)

# Now add new convenience variables to the design object:
## 'ones':      to estimate individuals counts
## 'housize':   to classify individuals by household size
## 'houdensity': to estimate households counts
exdes<-des.addvars(exdes,
  ones=1,
  housize=factor(ave(famcod,famcod,FUN = length)),
  houdensity=ave(famcod,famcod,FUN = function(x) 1/length(x))
)

# Estimate the average number of household components by region:
svystatR(exdes,num=~ones,den=~houdensity,by=~regcod,
  vartype="cvpct",conf.int=TRUE)

# Estimate the average household income for the whole population:
svystatR(exdes,num=~income,den=~houdensity,vartype="cvpct",
  conf.int=TRUE)

# ...for household size categories:
svystatR(exdes,num=~income,den=~houdensity,by=~housize,
  vartype="cvpct",conf.int=TRUE)

# ...and for province and household size:
svystatR(exdes,num=~income,den=~houdensity,by=~housize:procod,

```

```
vartype="cvpct")
```

svystatS

Estimation of Shares in Subpopulations

Description

Calculates estimates, standard errors and confidence intervals for Shares of a numeric variable within subpopulations.

Usage

```
svystatS(design, y, classes, by = NULL,
         vartype = c("se", "cv", "cvpct", "var"),
         conf.int = FALSE, conf.lev = 0.95, deff = FALSE,
         na.rm = FALSE)
```

```
## S3 method for class 'svystatS'
coef(object, ...)
## S3 method for class 'svystatS'
SE(object, ...)
## S3 method for class 'svystatS'
VAR(object, ...)
## S3 method for class 'svystatS'
cv(object, ...)
## S3 method for class 'svystatS'
deff(object, ...)
## S3 method for class 'svystatS'
confint(object, ...)
```

Arguments

<code>design</code>	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
<code>y</code>	Formula defining the interest variable.
<code>classes</code>	Formula defining the population groups whose <code>y</code> shares must be estimated.
<code>by</code>	Formula specifying the variables that define the "estimation domains". If <code>NULL</code> (the default option) estimates refer to the whole population.
<code>vartype</code>	character vector specifying the desired variability estimators. It is possible to choose one or more of: standard error (<code>'se'</code> , the default), coefficient of variation (<code>'cv'</code>), percent coefficient of variation (<code>'cvpct'</code>), or variance (<code>'var'</code>).
<code>conf.int</code>	Compute confidence intervals for the estimates? The default is <code>FALSE</code> .
<code>conf.lev</code>	Probability specifying the desired confidence level: the default value is <code>0.95</code> .
<code>deff</code>	Should the design effect be computed? The default is <code>FALSE</code> (see 'Details').
<code>na.rm</code>	Should missing values (if any) be removed from the variables of interest? The default is <code>FALSE</code> (see 'Details').
<code>object</code>	An object of class <code>svystatS</code> .
<code>...</code>	Additional arguments to <code>coef</code> , ..., <code>confint</code> methods (if any).

Details

This function computes weighted estimates for Shares of a numeric variable, using suitable weights depending on the class of design: calibrated weights for class `cal.analytic` and direct weights otherwise. Standard errors are calculated using the Taylor linearization technique.

Shares are a special case of Ratios. Therefore, at the price of some additional (and possibly heavy) data preparation effort, shares could also be estimated using function `svystatR`. However, `svystatS` makes estimation by far easier, in particular when shares have to be estimated for many population groups and/or within many domains.

The mandatory argument `y` identifies the variable of interest, that is the variable for which estimates of shares have to be calculated. The design variable referenced by `y` must be numeric.

The mandatory argument `classes` identifies population groups whose shares of `y` have to be estimated. The design variables referenced by `classes` must be of class `factor`. Groups can be identified by crossing factors, e.g. `statement classes = ~C1:C2` selects as groups the subpopulations determined by crossing the levels of factors `C1` and `C2`.

The optional argument `by` specifies the variables defining the "estimation domains", that is the subpopulations within which shares of `y` by `classes` must be estimated. If `by=NULL` (the default option), the estimates produced by `svystatS` refer to the whole population. Estimation domains must be defined by a formula: for instance the statement `by=~B1:B2` selects as estimation domains the subpopulations determined by crossing the modalities of variables `B1` and `B2`. Notice that a formula like `by=~B1+B2` will be automatically translated into the factor-crossing formula `by=~B1:B2`: if you need to compute estimates for domains `B1` and `B2` *separately*, you have to call `svystatS` twice. The design variables referenced by `by` (if any) should be of type `factor`, otherwise they will be coerced.

The `conf.int` argument allows to request the confidence intervals for the estimates. By default `conf.int=FALSE`, that is the confidence intervals are not provided.

Whenever confidence intervals are requested (i.e. `conf.int=TRUE`), the desired confidence level can be specified by means of the `conf.lev` argument. The `conf.lev` value must represent a probability ($0 \leq \text{conf.lev} \leq 1$) and its default is chosen to be 0.95.

The optional argument `deff` allows to request the design effect [Kish 1995] for the estimates. By default `deff=FALSE`, that is the design effect is not provided. The design effect of an estimator is defined as the ratio between the variance of the estimator under the actual sampling design and the variance that would be obtained for an 'equivalent' estimator under a hypothetical simple random sampling without replacement of the same size. To obtain an estimate of the design effect comparing to simple random sampling "*with replacement*", one must use `deff="replace"`.

Being Ratios nonlinear estimators, the design effect is estimated on the linearized version of the estimator (that is: for the estimator of the total of the linearized variable, aka "Woodruff transform"). When dealing with domain estimation, the design effects referring to a given subpopulation are currently computed by taking the ratios between the actual variance estimates and those that would have been obtained if a simple random sampling were carried out *within* that subpopulation. This is the same as the `srssubpop` option for Stata's function `estat`.

Missing values (NA) in interest variables should be avoided. If `na.rm=FALSE` (the default) they generate NAs in estimates (or even an error, if design is calibrated). If `na.rm=TRUE`, observations containing NAs are dropped, and estimates gets computed on non missing values only. This implicitly assumes that missing values hit interest variables *completely at random*: should this be not the case, computed estimates would be *biased*.

Value

An object inheriting from the `data.frame` class, whose detailed structure depends on input parameters' values.

Author(s)

Diego Zardetto

References

- Sarndal, C.E., Swensson, B., Wretman, J. (1992) *"Model Assisted Survey Sampling"*, Springer Verlag.
- Kish, L. (1995). *"Methods for design effects"*. Journal of Official Statistics, Vol. 11, pp. 55-77.

See Also

Estimators of Totals and Means [svystatTM](#), Ratios between Totals [svystatR](#), Ratios between Shares [svystatSR](#), Multiple Regression Coefficients [svystatB](#), Quantiles [svystatQ](#), Complex Analytic Functions of Totals and/or Means [svystatL](#), and all of the above [svystat](#).

Examples

```
# Load household data:
data(data.examples)

# Create a design object:
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
                weights=~weight)

# Add convenience variable 'ones' to estimate counts:
des<-des.addvars(des,ones=1)

### Simple examples to illustrate the syntax:
# Shares of income for sex classes:
svystatS(des, y=~income, classes=~sex, vartype="cvpct")

# Shares of income for sex and 5 age classes:
svystatS(des, y=~income, classes=~age5c:sex, vartype="cvpct")

# Shares of income for sex classes within region domains:
svystatS(des, y=~income, classes=~sex, by=~regcod, vartype="cvpct")

# Shares of income for sex classes within domains defined by crossing region and
# 5 age classes:
svystatS(des, y=~income, classes=~sex, by=~age5c:regcod, vartype="cvpct")

# MARGINAL, CONDITIONAL and JOINT relative frequencies (see also ?svystatTM)
# MARGINAL: e.g. proportions of people by provinces:
svystatS(des, y=~ones, classes=~procod, vartype="cvpct")
# CONDITIONAL: e.g. proportions of people by sex within provinces:
svystatS(des, y=~ones, classes=~sex, by=~procod, vartype="cvpct")
# JOINT: e.g. proportions of people cross-classified by sex and procod:
svystatS(des, y=~ones, classes=~sex:procod, vartype="cvpct")

### One more complicated example:
#####
# Shares of income held by people for income quintiles #
#####
# First: estimate income quintiles
```

```

inc.Q5 <- svystatQ(des, y=~income, probs=seq(0.2, 0.8, 0.2), ties="rounded")
inc.Q5

# Second: add a convenience factor variable classifying people by income
# quantiles
des<-des.addvars(des, quintile = cut(income, breaks = c(0, coef(inc.Q5), Inf),
                                   labels = 1:5, include.lowest=TRUE)
)

# Third: estimate income shares by income quintiles
svystatS(des, y=~income, classes=~quintile, vartype="cvpct")

### NOTE: Procedure above yields *correct point estimates* of income shares by
###       income quintiles, while *variance estimation is approximated* since
###       we neglected the sampling variability of the estimated quintiles.

```

svystatSR

*Estimation of Share Ratios in Subpopulations***Description**

Calculates estimates, standard errors and confidence intervals for Ratios between Shares of a numeric variables in subpopulations.

Usage

```

svystatSR(design, y, classes, by = NULL,
          vartype = c("se", "cv", "cvpct", "var"),
          conf.int = FALSE, conf.lev = 0.95, deff = FALSE,
          na.rm = FALSE)

```

```

## S3 method for class 'svystatSR'
coef(object, ...)
## S3 method for class 'svystatSR'
SE(object, ...)
## S3 method for class 'svystatSR'
VAR(object, ...)
## S3 method for class 'svystatSR'
cv(object, ...)
## S3 method for class 'svystatSR'
deff(object, ...)
## S3 method for class 'svystatSR'
confint(object, ...)

```

Arguments

design	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
y	Formula defining the interest variable.
classes	Formula defining the population groups among which ratios of y shares must be estimated.

<code>by</code>	Formula specifying the variables that define the "estimation domains". If NULL (the default option) estimates refer to the whole population.
<code>vartype</code>	character vector specifying the desired variability estimators. It is possible to choose one or more of: standard error ('se', the default), coefficient of variation ('cv'), percent coefficient of variation ('cvpct'), or variance ('var').
<code>conf.int</code>	Compute confidence intervals for the estimates? The default is FALSE.
<code>conf.lev</code>	Probability specifying the desired confidence level: the default value is 0.95.
<code>deff</code>	Should the design effect be computed? The default is FALSE (see 'Details').
<code>na.rm</code>	Should missing values (if any) be removed from the variables of interest? The default is FALSE (see 'Details').
<code>object</code>	An object of class <code>svystatSR</code> .
<code>...</code>	Additional arguments to <code>coef</code> , ..., <code>confint</code> methods (if any).

Details

This function computes weighted estimates for Ratios between Shares of a numeric variable, using suitable weights depending on the class of design: calibrated weights for class `cal.analytic` and direct weights otherwise. Standard errors are calculated using the Taylor linearization technique.

Ratios of Shares are a special case of Ratios. Therefore, at the price of some additional and heavy data preparation effort, ratios of shares could also be estimated using function `svyestatR`. However, `svystatSR` makes estimation by far easier, in particular when share ratios have to be estimated for many population groups and/or within many domains.

The mandatory argument `classes` identifies population groups whose ratios of `y` shares have to be estimated. Note that ratios of shares will be estimated and returned *for all the ordered pairs of population groups* defined by `classes`. Therefore, if `classes` defines `G` groups, `svystatSR` will have to compute estimates and sampling errors for $G * (G - 1)$ share ratios. To prevent combinatorial explosions (e.g. $G = 20$ would generate 380 share ratios), `classes` formula can reference just a *single* design variable, which must be a factor.

The optional argument `by` specifies the variables that define the "estimation domains", that is the subpopulations for which the estimates are to be calculated. If `by=NULL` (the default option), the estimates produced by `svystatSR` refer to the whole population. Estimation domains must be defined by a formula: for example the statement `by=~B1:B2` selects as estimation domains the subpopulations determined by crossing the modalities of variables `B1` and `B2`. Notice that a formula like `by=~B1+B2` will be automatically translated into the factor-crossing formula `by=~B1:B2`: if you need to compute estimates for domains `B1` and `B2` *separately*, you have to call `svystatSR` twice. The design variables referenced by `by` (if any) should be of type factor, otherwise they will be coerced.

The `conf.int` argument allows to request the confidence intervals for the estimates. By default `conf.int=FALSE`, that is the confidence intervals are not provided.

Whenever confidence intervals are requested (i.e. `conf.int=TRUE`), the desired confidence level can be specified by means of the `conf.lev` argument. The `conf.lev` value must represent a probability ($0 \leq \text{conf.lev} \leq 1$) and its default is chosen to be 0.95.

The optional argument `deff` allows to request the design effect [Kish 1995] for the estimates. By default `deff=FALSE`, that is the design effect is not provided. The design effect of an estimator is defined as the ratio between the variance of the estimator under the actual sampling design and the variance that would be obtained for an 'equivalent' estimator under a hypothetical simple random sampling without replacement of the same size. To obtain an estimate of the design effect comparing to simple random sampling "*with replacement*", one must use `deff="replace"`.

Being Ratios nonlinear estimators, the design effect is estimated on the linearized version of the

estimator (that is: for the estimator of the total of the linearized variable, aka "Woodruff transform"). When dealing with domain estimation, the design effects referring to a given subpopulation are currently computed by taking the ratios between the actual variance estimates and those that would have been obtained if a simple random sampling were carried out *within* that subpopulation. This is the same as the `srssubpop` option for Stata's function `estat`.

Missing values (NA) in interest variables should be avoided. If `na.rm=FALSE` (the default) they generate NAs in estimates (or even an error, if design is calibrated). If `na.rm=TRUE`, observations containing NAs are dropped, and estimates gets computed on non missing values only. This implicitly assumes that missing values hit interest variables *completely at random*: should this be not the case, computed estimates would be *biased*.

Value

An object inheriting from the `data.frame` class, whose detailed structure depends on input parameters' values.

Author(s)

Diego Zardetto

References

Sarndal, C.E., Swensson, B., Wretman, J. (1992) *"Model Assisted Survey Sampling"*, Springer Verlag.

Kish, L. (1995). *"Methods for design effects"*. Journal of Official Statistics, Vol. 11, pp. 55-77.

See Also

Estimators of Totals and Means [svystatTM](#), Ratios between Totals [svystatR](#), Shares [svystatS](#), Multiple Regression Coefficients [svystatB](#), Quantiles [svystatQ](#), Complex Analytic Functions of Totals and/or Means [svystatL](#), and all of the above [svystat](#).

Examples

```
# Load household data:
data(data.examples)

# Create a design object:
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
  weights=~weight)

# Add convenience variable 'ones' to estimate counts:
des<-des.addvars(des,ones=1)

### Simple examples to illustrate the syntax:
# Population sex ratios:
svystatSR(des, y=~ones, classes=~sex, vartype="cvpct")

# Population sex ratios within provinces:
svystatSR(des, y=~ones, classes=~sex, by=~procod, vartype="cvpct")

# Ratios of population shares for 5 age classes:
# NOTE: This yields 5*(5-1)=20 ratios
svystatSR(des, y=~ones, classes=~age5c, vartype="cvpct")
```

```

### One more complicated example:
#####
# Ratios between shares of income held by people for income quintiles #
#####
# First: estimate income quintiles
inc.Q5 <- svystatQ(des, y=~income, probs=seq(0.2, 0.8, 0.2), ties="rounded")
inc.Q5

# Second: add a convenience factor variable classifying people by income
# quintiles
des<-des.addvars(des, quintile = cut(income, breaks = c(0, coef(inc.Q5), Inf),
                                  labels = 1:5, include.lowest=TRUE)
)

# Third: estimate income shares by income quintiles
QS5 <- svystatSR(des, y=~income, classes=~quintile, vartype="cvpct")
QS5

### Therefore, for instance, the *S80/S20 income quintile share ratio* is:
S80.20 <- QS5["quintile5/quintile1",]
S80.20

### NOTE: Procedure above yields *correct point estimates* of income quintile
###       share ratios, while *variance estimation is approximated* since
###       we neglected the sampling variability of the estimated quintiles.

```

svystatTM

Estimation of Totals and Means in Subpopulations

Description

Computes estimates, standard errors and confidence intervals for Totals and Means in subpopulations.

Usage

```

svystatTM(design, y, by = NULL, estimator = c("Total", "Mean"),
          vartype = c("se", "cv", "cvpct", "var"),
          conf.int = FALSE, conf.lev = 0.95, deff = FALSE,
          na.rm = FALSE)

## S3 method for class 'svystatTM'
coef(object, ...)
## S3 method for class 'svystatTM'
SE(object, ...)
## S3 method for class 'svystatTM'
VAR(object, ...)
## S3 method for class 'svystatTM'
cv(object, ...)
## S3 method for class 'svystatTM'
deff(object, ...)
## S3 method for class 'svystatTM'
confint(object, ...)

```

Arguments

<code>design</code>	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
<code>y</code>	Formula defining the variables of interest.
<code>by</code>	Formula specifying the variables that define the "estimation domains". If <code>NULL</code> (the default option) estimates refer to the whole population.
<code>estimator</code>	character specifying the desired estimator: it may be <code>'Total'</code> (the default) or <code>'Mean'</code> .
<code>vartype</code>	character vector specifying the desired variability estimators. It is possible to choose one or more of: standard error (<code>'se'</code> , the default), coefficient of variation (<code>'cv'</code>), percent coefficient of variation (<code>'cvpct'</code>), or variance (<code>'var'</code>).
<code>conf.int</code>	Compute confidence intervals for the estimates? The default is <code>FALSE</code> .
<code>conf.lev</code>	Probability specifying the desired confidence level: the default value is <code>0.95</code> .
<code>deff</code>	Should the design effect be computed? The default is <code>FALSE</code> (see 'Details').
<code>na.rm</code>	Should missing values (if any) be removed from the variables of interest? The default is <code>FALSE</code> (see 'Details').
<code>object</code>	An object of class <code>svystatTM</code> .
<code>...</code>	Additional arguments to <code>coef</code> , <code>...</code> , <code>confint</code> methods (if any).

Details

This function computes weighted estimates for Totals and Means using suitable weights depending on the class of `design`: calibrated weights for class `cal.analytic` and direct weights otherwise. Standard errors for nonlinear estimators (e.g. calibration estimators) are calculated using the Taylor linearization technique.

The mandatory argument `y` identifies the variables of interest, that is the variables for which estimates are to be calculated. The corresponding formula should be of the type `y=~var1+...+varn`. The design variables referenced by `y` should be `numeric` or `factor` (variables of other types - e.g. `character` - will be coerced). It is admissible to specify for `y` "mixed" formulae that simultaneously contain quantitative (`numeric`) variables and qualitative (`factor`) variables.

To override the restriction to formulae of the type `y=~var1+...+varn`, the `AsIs` operator `I()` can be used (see 'Examples'). Though the latter opportunity could appear quite useful in some occasion, actually it should be almost always possible to find a work-around by using other functions of the **ReGenesees** package.

The optional argument `by` specifies the variables that define the "estimation domains", that is the subpopulations for which the estimates are to be calculated. If `by=NULL` (the default option), the estimates produced by `svystatTM` refer to the whole population. Estimation domains must be defined by a formula: for example the statement `by=~B1:B2` selects as estimation domains the subpopulations determined by crossing the modalities of variables `B1` and `B2`. Notice that a formula like `by=~B1+B2` will be automatically translated into the factor-crossing formula `by=~B1:B2`: if you need to compute estimates for domains `B1` and `B2` *separately*, you have to call `svystatTM` twice. The design variables referenced by `by` (if any) should be of type `factor`, otherwise they will be coerced.

The optional argument `estimator` makes it possible to select the desired estimator. If `estimator="Total"` (the default option), `svystatTM` calculates, for a given variable of interest `vark`, the estimate of the total (when `vark` is `numeric`) or the estimate of the absolute frequency distribution (when `vark` is `factor`). Similarly, if `estimator="Mean"`, the function calculates the estimate of the mean (when `vark` is `numeric`) or the the estimate of the relative frequency distribution (when `vark` is `factor`).

The `conf.int` argument allows to request the confidence intervals for the estimates. By default `conf.int=FALSE`, that is the confidence intervals are not provided.

Whenever confidence intervals are requested (i.e. `conf.int=TRUE`), the desired confidence level can be specified by means of the `conf.lev` argument. The `conf.lev` value must represent a probability ($0 \leq \text{conf.lev} \leq 1$) and its default is chosen to be 0.95.

The optional argument `deff` allows to request the design effect [Kish 1995] for the estimates. By default `deff=FALSE`, that is the design effect is not provided. The design effect of an estimator is defined as the ratio between the variance of the estimator under the actual sampling design and the variance that would be obtained for an 'equivalent' estimator under a hypothetical simple random sampling without replacement of the same size. To obtain an estimate of the design effect comparing to simple random sampling "*with replacement*", one must use `deff="replace"`.

Understanding what 'equivalent' estimator actually means is straightforward when dealing with Horvitz-Thompson estimators of Totals and Means. This is not the case when, on the contrary, the estimator to which the `deff` refers is a nonlinear estimator (e.g. for Calibration estimators of Totals and Means). In such cases, the standard approach is to use as 'equivalent' estimator the linearized version of the original estimator (that is: the estimator of the total of the linearized variable, aka "Woodruff transform").

When dealing with domain estimation, the design effects referring to a given subpopulation are currently computed by taking the ratios between the actual variance estimates and those that would have been obtained if a simple random sampling were carried out *within* that subpopulation. This is the same as the `srssubpop` option for Stata's function `estat`.

Missing values (NA) in interest variables should be avoided. If `na.rm=FALSE` (the default) they generate NAs in estimates (or even an error, if design is calibrated). If `na.rm=TRUE`, observations containing NAs are dropped, and estimates gets computed on non missing values only. This implicitly assumes that missing values hit interest variables *completely at random*: should this be not the case, computed estimates would be *biased*. Notice that the `na.rm=TRUE` option is only allowed if `y` references a *single* interest variable.

Value

An object inheriting from the `data.frame` class, whose detailed structure depends on input parameters' values.

Author(s)

Diego Zardetto

References

- Sarndal, C.E., Swensson, B., Wretman, J. (1992) "*Model Assisted Survey Sampling*", Springer Verlag.
- Kish, L. (1995). "*Methods for design effects*". Journal of Official Statistics, Vol. 11, pp. 55-77.

See Also

Estimators of Ratios between Totals [svyestatR](#), Shares [svyestatS](#), Ratios between Shares [svyestatSR](#), Quantiles [svyestatQ](#), Multiple Regression Coefficients [svyestatB](#), Complex Analytic Functions of Totals and/or Means [svyestatL](#), and all of the above [svyestat](#).

Examples

```
# Load survey data:
data(data.examples)

# Creation of a design object:
des<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
  weights=~weight)

# Estimation of the total of 3 quantitative variables for the whole
# population:
svystatTM(des,~y1+y2+y3)

# Estimation of the total of the same 3 variables by region, with SE
# and CV%:
svystatTM(des,~y1+y2+y3,~regcod,vartype=c("se","cvpct"))

# Estimation of the mean of the same 3 variables by marstat and sex:
svystatTM(des,~y1+y2+y3,~marstat:sex,estimator="Mean")

# Estimation of the absolute frequency distribution of the qualitative
# variable age5c for the whole population, with the design effect:
svystatTM(des,~age5c,deff=TRUE)

# MARGINAL relative frequency distributions
# Estimation of the relative frequency distribution of the qualitative
# variable age5c for the whole population:
svystatTM(des,~age5c,estimator="Mean")

# CONDITIONAL relative frequency distributions
# Estimation of the relative frequency distribution of the qualitative
# variable marstat by sex:
svystatTM(des,~marstat,~sex,estimator="Mean")

# JOINT relative frequency distributions
# Estimation of the relative frequency of the joint distribution of sex
# and marstat:
# *First Solution* (using the AsIs operator I()):
svystatTM(des,~I(sex:marstat),estimator="Mean")
# *Second Solution* (adding a new variable to des):
des2 <- des.addvars(des, sex.marstat=sex:marstat)
svystatTM(des2,~sex.marstat,estimator="Mean")
# *Third Solution* (exploiting estimators of Shares, see also ?svystatS):
# Add new variable 'ones' to estimate counts of final units (individuals)
# and estimate the share of people for classes of sex and marstat
des2 <- des.addvars(des, ones=1)
svystatS(des2,~ones,classes=~sex:marstat)

# Estimation of the mean income inside provinces, with confidence intervals
# at a confidence level of 0.9:
svystatTM(des,~income,~procod,estimator="Mean",conf.int=TRUE,conf.lev=0.9)
```



```

# Quantitative and qualitative variables together: estimation of the
# total of income and of the absolute frequency distribution of sex,
# by marstat:
svystatTM(des,~income+sex,~marstat)

# Estimating totals in domains for "incomplete" partitions: more on
# the AsIs operator I()

# Estimation of the total income (plus cvpct) ONLY in region 7:
svystatTM(des,~I(income*(regcod=="7")),vartype="cvpct")
# Alternative solution (adding a new variable to des):
des2 <- des.addvars(des, inc_reg7=I(income*(regcod=="7")))
svystatTM(des2,~inc_reg7,vartype="cvpct")

# Estimation of the total income (plus cvpct) ONLY in regions 6 and 10:
svystatTM(des,~I(income*as.numeric(regcod %in% c("6","10"))),vartype="cvpct")
# Alternative solution (adding a new variable to des):
des2 <- des.addvars(des, inc_reg6.10=I(income*(regcod %in% c("6","10"))))
svystatTM(des2,~inc_reg6.10,vartype="cvpct")

# Compare with the corresponding estimates for the "complete" partition,
# i.e. for regions:
svystatTM(des,~income,~regcod,vartype="cvpct")

# Under default settings lonely PSUs produce errors in standard
# errors estimation (notice we didn't pass the fpcs):
data(fpcdat)
des.lpsu<-e.svydesign(data=fpcdat,ids=~psu+ssu,strata=~stratum,
                     weights=~w)
## Not run:
svystatTM(des.lpsu,~x+y+z,vartype=c("se","cvpct"))

## End(Not run)

# This can be circumvented in different ways, namely:
old.op <- options("RG.lonely.psu"="adjust")
svystatTM(des.lpsu,~x+y+z,vartype=c("se","cvpct"))
options(old.op)

# or otherwise:
old.op <- options("RG.lonely.psu"="average")
svystatTM(des.lpsu,~x+y+z,vartype=c("se","cvpct"))
options(old.op)

# but see also ?collapse.strata for a better alternative.

#####
# Household-level estimation in household surveys. #
#####

# Large scale household surveys typically adopt a 2-stage sampling
# design with municipalities as PSUs and households as SSUs, in order
# to eventually collect informations on each individual belonging to

```

```

# sampled SSUs. In such a framework (up to possible total nonresponse
# effects), each individual inside a sampled household shares the
# same direct weight, which, in turn, equals the household weight.
# This implies that it is very easy to build estimates referred to
# SSU-level (households) informations, despite estimators actually
# involve only individual values. Some examples are given below.

# Load survey data:
data(data.examples)

# Define the survey design (variable famcod identifies households)
exdes<-e.svydesign(data=example,ids=~towcod+famcod,strata=~stratum,
  weights=~weight)

# Collapse strata to eliminate lonely PSUs
exdes<-collapse.strata(design=exdes,block.vars=~sr:procod)

# Now add new convenience variables to the design object:
## 'ones':      to estimate individuals counts
## 'housize':   to classify individuals by household size
## 'houdensity': to estimate households counts
exdes<-des.addvars(exdes,
  ones=1,
  housize=factor(ave(famcod,famcod,FUN = length)),
  houdensity=ave(famcod,famcod,FUN = function(x) 1/length(x))
)

# Estimate the total number of households:
nhou<-svystatTM(exdes,~houdensity,vartype="cvpct")
nhou

# Estimate the total number of individuals:
nind<-svystatTM(exdes,~ones,vartype="cvpct")
nind

# Thus the average number of individuals per household is:
coef(nind)/coef(nhou)

# ...which can be obtained also as a ratio (along with
# its estimated sampling variability):
svystatR(exdes,~ones,~houdensity,vartype="cvpct")

# Estimate the number and proportion of individuals living in households
# of given sizes:
nind.by.housize<-svystatTM(exdes,~housize,vartype="cvpct")
nind.by.housize

pind.by.housize<-svystatTM(exdes,~housize,estimator="Mean",var="cvpct")
pind.by.housize

# Estimate the number of households by household size:
nhou.by.housize<-svystatTM(exdes,~houdensity,~housize,vartype="cvpct")
nhou.by.housize

# Notice that estimates of individuals and household counts are consistent,
# indeed:
coef(nind.by.housize)/coef(nhou.by.housize)

```

weights

*Retrieve Sampling Units Weights***Description**

Extracts the *current* weights of units belonging to a survey design object.

Usage

```
weights(object, ...)
```

Arguments

object	Object of class <code>analytic</code> (or inheriting from it) containing survey data and sampling design metadata.
...	Arguments for future expansion.

Details

The *current* weights of object are, by definition, those weights that would be used for estimation purposes on that object (e.g. by functions [svyestatTM](#), [svyestatR](#), [svyestatS](#), [svyestatSR](#), [svyestatQ](#), [svyestatB](#), [svyestatL](#), ...). The nature of such weights depends on the class of object: calibrated weights for class `cal.analytic` and direct weights otherwise.

Value

A vector of weights, whose components are positionally tied to the sampling units belonging to object.

Note

If object has undergone multiple, subsequent calibration steps, the function will return the output weights generated by the *last* calibration step.

Author(s)

Diego Zardetto

See Also

Function [g.range](#) to asses the range of the g-weights of a calibrated design object.

Examples

```
# Creation of the object to be calibrated:
data(data.examples)
exdes<-e.svydesign(data=example,ids=~towcod+famcod,strata=~SUPERSTRATUM,
  weights=~weight)

# Retrieve the weights and summarize their distribution:
summary(weights(exdes))

# Now calibrate (global solution) on the joint distribution of sex
```

```
# and marstat (totals in pop03):
excal.1st<-e.calibrate(design=exdes,df.population=pop03,
                      calmodel=~marstat:sex-1,calfun="linear",bounds=bounds)

# Retrieve the current weights (i.e. the calibrated ones) and
# summarize their distribution:
summary(weights(excal.1st))

# Now calibrate once again, this time on the marginal distribution
# of age in 5 classes (age5c) inside provinces (procod) (totals in pop06p)
# with the partitioned solution, the logit distance and bounds=c(0.5, 1.5):
excal.2nd<-e.calibrate(design=excal.1st,df.population=pop06p,
                      calmodel=~age5c-1,partition=~procod,calfun="logit",
                      bounds=c(0.5, 1.5))

# Notice that the print method correctly takes the calibration chain
# into account:
excal.2nd

# Now retrieve the current weights (i.e. the ones generated by the second
# calibration step) and summarize their distribution:
summary(weights(excal.2nd))
```

write.svystat

Export Survey Statistics

Description

Prints survey statistics to a file or connection.

Usage

```
write.svystat(x, ...)
```

Arguments

x	An object containing survey statistics.
...	Arguments to write.table

Details

This function is just a convenience wrapper to [write.table](#), designed to export objects which have been returned by survey statistics functions (e.g. [svystatTM](#), [svystatR](#), [svystatS](#), [svystatSR](#), [svystatB](#), [svystatQ](#), [svystatL](#)).

Author(s)

Diego Zardetto

See Also

[write.table](#) and the 'R Data Import/Export' manual.

Examples

```

# Creation of a design object:
data(sbs)
des<-e.svydesign(data=sbs,ids=~id,strata=~strata,weights=~weight,
  fpc=~fpc)

# Estimation of the average value added per employee
# for economic activity region and macro-sectors,
# with SE, CV% and standard confidence intervals:
stat <- svystatR(des,~va.imp2,~emp.num,by=~region:nace.macro,
  vartype=c("se","cvpct"),conf.int=TRUE)
stat

# In order to export the summary statistics above
# into a CSV file for input to Excel one can use:
## Not run:
write.svystat(stat,file="stat.csv",sep=";")

## End(Not run)

# ...and to read this file back into R one needs
## Not run:
stat.back <- read.table("stat.csv",header=TRUE,sep=";",
  check.names=FALSE)
stat.back

## End(Not run)

# Notice, however, that the latter object has
# lost a lot of meta-data as compared to the
# original one, so that e.g.:
## Not run:
confint(stat.back)

## End(Not run)

# ...while, on the contrary:
confint(stat)

```

Zapsmall

Zapsmall Data Frame Columns and Numeric Vectors

Description

Put to zero values "close" to zero.

Usage

```

## Default S3 method:
Zapsmall(x, digits = getOption("digits"), ...)
## S3 method for class 'data.frame'
Zapsmall(x, digits = getOption("digits"), except = NULL, ...)

```

Arguments

<code>x</code>	A <code>data.frame</code> with numeric columns or a numeric vector.
<code>digits</code>	Integer indicating the precision to be used.
<code>except</code>	Indices of columns not to be zapped (if any).
<code>...</code>	Arguments for future expansion.

Details

This function "extends" to `data.frame` objects function [zapsmall](#) from the package **base**.
 The method for class `data.frame` 'zaps' values close to zero occurring in columns of `x`. Argument `except` can be used to prevent specific columns from being zapped.
 The default method is a bare copy of the original function from package **base**.

Value

An object of the same class of `x`, with values "close" to zero zapped to zero.

Author(s)

Diego Zardetto

See Also

The original function [zapsmall](#) from package **base**.

Examples

```
# Create a test data frame with columns containing
# values of different orders of magnitude:
data <- data.frame(a = pi*10^(-8:1), b = c(rep(1000,8), c(1E-5, 1E-6)))

# Print on screen the test data frame:
data

# Compare with its zapped version:
Zapsmall(data)
```

%into%

Compress Nested Factors

Description

The special binary operator `%into%` transforms nested factors in such a way as to reduce the dimension and/or the sparsity of the model matrix of a calibration problem.

Usage

```
inner %into% outer
"%into%"(inner, outer)
```

Arguments

inner	Factor with levels nested into outer (see ‘Details’).
outer	Factor whose levels are an aggregation of those in inner (see ‘Details’).

Details

Arguments `inner` and `outer` must be both factors and must have the same length. Moreover, `inner` has to be *strictly nested* into `outer`. Nesting is defined by treating elements in `inner` and `outer` as if they were positionally tied (i.e. as if they belonged to columns of a given data frame). The definition is as follows:

`inner` and `outer` are strictly nested if, and only if, 1) every set of equal elements in `inner` correspond to a set of equal elements in `outer`, and 2) `inner` has *more* non-empty levels than `outer`.

If `inner` and `outer` do not fulfill the conditions above, evaluating `inner %into% outer` gives an error.

Suppose `inner` is actually nested into `outer` and define `inner.in.outer <- inner %into% outer`. The output factor `inner.in.outer` is built by recoding `inner` levels in such a way that each of them is mapped into the integer which represents its order inside the corresponding level of `outer` (see ‘Examples’). As a consequence, the levels of `inner.in.outer` will be `1:n.max`, being `n.max` the *maximum* number of levels of `inner` tied to a level of `outer`. Since this number is generally considerably smaller than the number of levels of `inner`, `inner.in.outer` can be seen as a *compressed* representation of `inner`. Obviously, compression comes at a price: indeed `inner.in.outer` can now be used to identify a level of `inner` only *inside* a given level of `outer` (see ‘Examples’).

The usefulness of the `%into%` operator emerges in the calibration context. As we already documented in [e.calibrate](#), factorizing a calibration problem (i.e. exploiting the partition argument of `e.calibrate`) determines a significant reduction in computation complexity, especially for big surveys. Now, it is sometimes the case that a calibration model is actually factorizable, even if this property is not self-apparent, due to factor nesting. In such cases, anyway, trying naively to factorize the outer variable(s) typically leads to very big and sparse model matrices (as well as population totals data frames), with the net result of washing-out the expected efficiency gain. A better alternative is to exploit the `%into%` operator in order to *compress* the inner variable in such a way that the outer variable can be actually factorized *without* giving rise to huge and sparse matrices. Section ‘Examples’ reports some practical illustration of the above line of reasoning.

Value

A factor with levels `1:n.max`, being `n.max` the *maximum* number of levels of `inner` tied to a level of `outer`.

Author(s)

Diego Zardetto

See Also

Further examples can be found in the [fill.template](#) help page.

Examples

```
#####
## General properties of the %into% operator.  #
```

```
#####
# First build a small data frame with 2 nested factors representing
# regions and provinces:
dd <- data.frame(
  reg = factor( rep(LETTERS[1:3], c(6, 3, 1)) ),
  prov = factor( rep(letters[1:6], c(3, 2, 1, 2, 1, 1)) )
)
dd

# Since prov is strictly nested into reg we can compute:
prov.in.reg <- dd$prov %into% dd$reg
prov.in.reg

# Note that prov.in.reg has 3 levels because, as can be seen from dd,
# the maximum number of provinces inside regions is 3. Thus prov.in.reg
# is actually a compressed version of dd$prov (whose levels were 6)
# but, obviously, it can now be used to identify a province only inside
# a given region. This means that the the two factors below are identical (up
# to levels' labels):
dd$prov
interaction(prov.in.reg, dd$reg, drop=TRUE)

# Note that all the statements below generate errors:
## Not run:
dd$reg %into% dd$prov
dd$reg %into% dd$reg
dd$prov %into% dd$prov

## End(Not run)

#####
## A more useful (and complex) example from the calibration context. #
#####
# First define a design object:
data(data.examples)
exdes <- e.svydesign(data=example, ids=~towcod+famcod, strata=~SUPERSTRATUM,
weights=~weight)

# Now suppose you have to perform a calibration process which
# exploits the following known population totals:
# 1) Joint distribution of sex and age10c (age in 10 classes)
#    at the region level;
# 2) Joint distribution of sex and age5c (age in 5 classes)
#    at the province level;
#
# The auxiliary variables corresponding to the population totals above
# can be symbolically represented by a calibration model like the following:
# ~(procod:age5c + regcod:age10c - 1):sex
#
# At first sight it seems that only the sex variable can be factorized
# in the model above. However if one observe that regions are an aggregation
# of provinces, one realizes that also the regcod variable can be factorized.
# Similarly, since categories of age5c are an aggregation of categories of
# age10c, age5c can be factorized too. In both cases, using the %into%
# operator will save computation time and memory usage.
# Let us see it in practice:
#
```



```

## 1) Global calibration (i.e. calmodel=~(procod:age5c + regcod:age10c - 1):sex,
# no partition variable, known totals stored in pop07):
t<-system.time(
  cal07<-e.calibrate(design=exdes,df.population=pop07,
    calmodel=~(procod:age5c + regcod:age10c - 1):sex,
    calfun="logit",bounds=c(0.2,1.8))
)

## 2) Partitioned calibration on the self evident variable sex only
# (i.e. calmodel=~procod:age5c + regcod:age10c - 1, partition=~sex,
# known totals stored in pop07p):
tp<-system.time(
  cal07p<-e.calibrate(design=exdes,df.population=pop07p,
    calmodel=~procod:age5c + regcod:age10c - 1,partition=~sex,
    calfun="logit",bounds=c(0.2,1.8))
)

## 3) Full partitioned calibration on variables sex, regcod and age5c
# by exploiting %into%.
# First add to the design object the new compressed factor variables
# involving nested factors, namely provinces inside regions...
exdes<-des.addvars(exdes,procod.in.regcod=procod %into% regcod)

# ...and age10c inside age5c:
exdes<-des.addvars(exdes,age10c.in.age5c=age10c %into% age5c)

# Now calibrate exploiting the new variables
# (i.e. calmodel=~procod.in.regcod + age10c.in.age5c - 1,
# partition=~sex:regcod:age5c, known totals stored inside cal07pp)
tpp<-system.time(
  cal07pp<-e.calibrate(design=exdes,df.population=pop07pp,
    calmodel=~procod.in.regcod + age10c.in.age5c - 1,
    partition=~sex:regcod:age5c,
    calfun="logit",bounds=c(0.2,1.8))
)

# Now compare execution times:
t
tp
tpp

# thus, tpp < tp < t, as expected.
# Notice also that we obtained identical calibrated weights:
all.equal(weights(cal07),weights(cal07p))
all.equal(weights(cal07),weights(cal07pp))

# as it must be.

```

Index

*Topic **datasets**

- AF.gvf, [5](#)
- data.examples, [27](#)
- fpcdat, [72](#)
- sbs, [112](#)

*Topic **package**

- ReGenesees-package, [2](#)

*Topic **survey**

- %into%, [150](#)
- aux.estimates, [6](#)
- bounds.hint, [8](#)
- check.cal, [11](#)
- collapse.strata, [13](#)
- Corr, [23](#)
- des.addvars, [28](#)
- des.merge, [30](#)
- drop.gvf.points, [32](#)
- e.calibrate, [36](#)
- e.svydesign, [51](#)
- ext.calibrated, [57](#)
- extractors, [61](#)
- fill.template, [62](#)
- find.lon.strata, [66](#)
- fit.gvf, [67](#)
- g.range, [73](#)
- get.residuals, [75](#)
- getBest, [78](#)
- getR2, [80](#)
- GVF.db, [82](#)
- gvf.input, [88](#)
- gvf.misc, [90](#)
- plot.gvf.fit, [93](#)
- pop.desc, [96](#)
- pop.template, [99](#)
- population.check, [102](#)
- predictCV, [104](#)
- ReGenesees.options, [109](#)
- svystat, [113](#)
- svystatB, [118](#)
- svystatL, [123](#)
- svystatQ, [128](#)
- svystatR, [131](#)
- svystatS, [135](#)

- svystatSR, [138](#)

- svystatTM, [141](#)

- weights, [147](#)

- Zapsmall, [149](#)

- [.gvf.fits (fit.gvf), [67](#)

- [[.gvf.fits (fit.gvf), [67](#)

- %into%, [64](#), [150](#)

- AF (AF.gvf), [5](#)

- AF.gvf, [5](#)

- AIC, [80](#)

- AIC (getR2), [80](#)

- analytic, [39](#)

- analytic (e.svydesign), [51](#)

- anova.gvf.fit (gvf.misc), [90](#)

- anova.gvf.fits (gvf.misc), [90](#)

- as.formula, [83](#)

- aux.estimates, [6](#), [17](#), [19](#)

- BIC, [80](#)

- BIC (getR2), [80](#)

- bounds (data.examples), [27](#)

- bounds.hint, [8](#), [40](#), [74](#)

- cal.analytic (e.calibrate), [36](#)

- calmodel (contrasts.RG), [17](#)

- check.cal, [10](#), [11](#), [39](#), [40](#)

- coef, [61](#), [92](#), [115](#)

- coef.gvf.fit (gvf.misc), [90](#)

- coef.gvf.fits (gvf.misc), [90](#)

- coef.svystat.gr (svystat), [113](#)

- coef.svystatB (svystatB), [118](#)

- coef.svystatL (svystatL), [123](#)

- coef.svystatQ (svystatQ), [128](#)

- coef.svystatR (svystatR), [131](#)

- coef.svystatS (svystatS), [135](#)

- coef.svystatSR (svystatSR), [138](#)

- coef.svystatTM (svystatTM), [141](#)

- collapse.strata, [5](#), [13](#), [53](#), [66](#), [67](#), [110](#), [111](#)

- confint, [61](#), [115](#)

- confint.svystat.gr (svystat), [113](#)

- confint.svystatB (svystatB), [118](#)

- confint.svystatL (svystatL), [123](#)

- confint.svystatQ (svystatQ), [128](#)

- confint.svystatR (svystatR), 131
- confint.svystatS (svystatS), 135
- confint.svystatSR (svystatSR), 138
- confint.svystatTM (svystatTM), 141
- contr.off (contrasts.RG), 17
- contr.treatment, 18, 19
- contrasts, 18, 19
- contrasts.off (contrasts.RG), 17
- contrasts.reset (contrasts.RG), 17
- contrasts.RG, 17
- Corr, 23
- CoV (Corr), 23
- cv, 115
- cv (extractors), 61
- cv.svystat.gr (svystat), 113
- cv.svystatB (svystatB), 118
- cv.svystatL (svystatL), 123
- cv.svystatQ (svystatQ), 128
- cv.svystatR (svystatR), 131
- cv.svystatS (svystatS), 135
- cv.svystatSR (svystatSR), 138
- cv.svystatTM (svystatTM), 141
- data.examples, 27
- deff, 115
- deff (extractors), 61
- deff.svystat.gr (svystat), 113
- deff.svystatB (svystatB), 118
- deff.svystatL (svystatL), 123
- deff.svystatR (svystatR), 131
- deff.svystatS (svystatS), 135
- deff.svystatSR (svystatSR), 138
- deff.svystatTM (svystatTM), 141
- des.addvars, 28, 31
- des.merge, 30
- drop.gvf.points, 6, 32, 69, 79, 81, 85, 89, 92, 95, 106, 115
- e.calibrate, 5, 7, 10, 12, 17, 19, 28, 29, 31, 36, 51, 53, 58, 59, 63, 64, 74–76, 97, 100, 103, 151
- e.svydesign, 5, 7, 29, 31, 40, 51, 58, 59, 111
- ecal.status (e.calibrate), 36
- ee.AF (AF.gvf), 5
- effects.gvf.fit (gvf.misc), 90
- effects.gvf.fits (gvf.misc), 90
- estimator.kind, 5, 6, 55, 69, 85, 88, 89, 115
- example (data.examples), 27
- exdes (AF.gvf), 5
- ext.calibrated, 57
- extractors, 61
- fill.template, 7, 17, 19, 37, 38, 40, 62, 97, 100, 103, 151
- find.lon.strata, 66
- fit.gvf, 6, 33, 56, 67, 69, 79, 81, 83, 85, 88, 89, 92, 95, 106, 115
- fitted, 92
- fitted.gvf.fit (gvf.misc), 90
- fitted.gvf.fits (gvf.misc), 90
- formula, 18, 19
- fpcdat, 67, 72, 111
- g.range, 10, 40, 73, 76, 147
- get.residuals, 75
- getBest, 78, 80
- getR2, 33, 79, 80
- glm, 18
- GVF (fit.gvf), 67
- GVF.db, 6, 33, 56, 68, 69, 79, 81, 82, 89, 92, 95, 105, 106, 115
- gvf.fit (fit.gvf), 67
- gvf.fits (fit.gvf), 67
- gvf.input, 6, 33, 56, 68, 69, 79, 81, 83, 85, 88, 92, 95, 106, 115
- gvf.input.gr, 69
- gvf.input.gr (svystat), 113
- gvf.misc, 90
- identify, 33
- list, 69
- lm, 18, 69, 119
- memory.limit, 63
- model.matrix, 18, 19
- plot.gvf.fit, 6, 33, 69, 79, 81, 85, 89, 92, 93, 106, 115
- plot.gvf.fits (plot.gvf.fit), 93
- plot.gvf.input (gvf.input), 88
- plot.gvf.input.gr (svystat), 113
- plot.lm, 33, 94, 95
- pop.desc, 37, 40, 63, 64, 96, 100
- pop.template, 7, 10, 17, 19, 37, 40, 64, 97, 99, 103
- pop01 (data.examples), 27
- pop02 (data.examples), 27
- pop03 (data.examples), 27
- pop03p (data.examples), 27
- pop04 (data.examples), 27
- pop04p (data.examples), 27
- pop05 (data.examples), 27
- pop05p (data.examples), 27
- pop06p (data.examples), 27
- pop07 (data.examples), 27
- pop07p (data.examples), 27

- pop07pp (data.examples), 27
- population.check, 7, 9, 10, 37, 40, 100, 102
- predict.gvf.fit (gvf.misc), 90
- predict.gvf.fits (gvf.misc), 90
- predict.lm, 104, 105
- predictCV, 6, 33, 69, 79, 81, 83–85, 89, 92, 95, 104, 115
- print.default, 68
- print.gvf.fit (fit.gvf), 67
- print.gvf.fits (fit.gvf), 67

- ReGenesees (ReGenesees-package), 2
- ReGenesees-package, 2
- ReGenesees.options, 13, 15, 53, 66, 67, 73, 109
- residuals.gvf.fit (gvf.misc), 90
- residuals.gvf.fits (gvf.misc), 90
- RG.adjust.domain.lonely (ReGenesees.options), 109
- RG.lonely.psu (ReGenesees.options), 109
- RG.ultimate.cluster, 52
- RG.ultimate.cluster (ReGenesees.options), 109
- rstandard.gvf.fit (gvf.misc), 90
- rstandard.gvf.fits (gvf.misc), 90
- rstudent.gvf.fit (gvf.misc), 90
- rstudent.gvf.fits (gvf.misc), 90

- sbs, 112
- SE, 115
- SE (extractors), 61
- SE.svystat.gr (svystat), 113
- SE.svystatB (svystatB), 118
- SE.svystatL (svystatL), 123
- SE.svystatQ (svystatQ), 128
- SE.svystatR (svystatR), 131
- SE.svystatS (svystatS), 135
- SE.svystatSR (svystatSR), 138
- SE.svystatTM (svystatTM), 141
- summary.analytic (e.svdesign), 51
- summary.gvf.fit (fit.gvf), 67
- summary.gvf.fits (fit.gvf), 67
- summary.svystatB (svystatB), 118
- svystat, 6, 33, 55, 56, 58, 61, 68, 69, 79, 81, 85, 89, 92, 95, 106, 113, 120, 125, 130, 133, 137, 140, 143
- svystatB, 24, 40, 53, 55, 58, 61, 88, 118, 125, 130, 133, 137, 140, 143, 147, 148
- svystatL, 24, 40, 53, 55, 58, 61, 88, 120, 123, 130, 133, 137, 140, 143, 147, 148
- svystatQ, 24, 40, 53, 55, 58, 61, 88, 120, 125, 128, 133, 137, 140, 143, 147, 148
- svystatR, 24, 40, 53, 55, 58, 61, 88, 120, 125, 130, 131, 136, 137, 139, 140, 143, 147, 148
- svystatS, 24, 40, 53, 55, 58, 61, 88, 120, 125, 130, 133, 135, 140, 143, 147, 148
- svystatSR, 24, 40, 53, 55, 58, 61, 88, 120, 125, 130, 133, 137, 138, 143, 147, 148
- svystatTM, 7, 24, 40, 51, 53, 55, 58, 61, 75, 88, 114, 120, 125, 130, 133, 137, 140, 141, 147, 148
- symnum, 68

- VAR, 115
- VAR (extractors), 61
- VAR.svystat.gr (svystat), 113
- VAR.svystatB (svystatB), 118
- VAR.svystatL (svystatL), 123
- VAR.svystatQ (svystatQ), 128
- VAR.svystatR (svystatR), 131
- VAR.svystatS (svystatS), 135
- VAR.svystatSR (svystatSR), 138
- VAR.svystatTM (svystatTM), 141
- vcov.gvf.fit (gvf.misc), 90
- vcov.gvf.fits (gvf.misc), 90

- weights, 39, 53, 59, 74, 76, 147
- write.svystat, 148
- write.table, 148

- Zapsmall, 149
- zapsmall, 150